

## Safety Data Sheet

# 8 Mix VOC in Carbon disulfide

Version : V2.0.0.1

Report No. : BWQ7552-2016-MSDS-EP

Creation Date : 2026/02/03

Revision Date : -



\*Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)

## 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product Name	8 Mix VOC in Carbon disulfide
Cat No.	BWQ7552-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable
REACH Registration Number	-
UFI	No information available

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

### 1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

### 1.4 Emergency telephone number

Emergency telephone number	010-58103678
Opening hours	24h

## 2 Hazards identification

### 2.1 CLP classification according to Regulation ( EC ) No. 1272/2008 with amendment 2023/707

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious eye damage/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity - repeated exposure	Category 1

## 2.2 Label elements

Hazard pictograms	
Signal word	<b>Danger</b>

## Hazard statements

H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H361df	Suspected of damaging fertility and the unborn child
H372	Causes damage to organs through prolonged or repeated exposure (hearing organ)

## Precautionary statements

### ◆ Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### ◆ Response

P314	Get medical advice/ attention if you feel unwell.
P321	Specific treatment (see related instructions on the label).
P302+P352	IF ON SKIN: Wash with plenty of water.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## ◆ Storage

	<b>P405</b>	Store locked up.
	<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.

## ◆ Disposal

	<b>P501</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
--	-------------	---

## | 2.3 Other hazards

## ◆ Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
<b>Benzene</b>	Not PBT/vPvB
<b>Toluene</b>	Not PBT/vPvB
<b>Ethylbenzene</b>	Not PBT/vPvB
<b>o-xylene</b>	Not PBT/vPvB
<b>m-xylene</b>	Not PBT/vPvB
<b>p-xylene</b>	Not PBT/vPvB
<b>Styrene</b>	Not PBT/vPvB
<b>Cumene</b>	Not PBT/vPvB
<b>Carbon disulphide</b>	Not PBT/vPvB

## ◆ Results of endocrine disrupting properties assessment

Component	Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605]
<b>Benzene</b>	Insufficient information, temporarily unable to evaluate
<b>Toluene</b>	Insufficient information, temporarily unable to evaluate
<b>Ethylbenzene</b>	Insufficient information, temporarily unable to evaluate
<b>o-xylene</b>	Insufficient information, temporarily unable to evaluate
<b>m-xylene</b>	Insufficient information, temporarily unable to evaluate
<b>p-xylene</b>	Insufficient information, temporarily unable to evaluate
<b>Styrene</b>	Insufficient information, temporarily unable to evaluate
<b>Cumene</b>	Insufficient information, temporarily unable to evaluate
<b>Carbon disulphide</b>	not ED

## ◆ Other

	Not applicable.
--	-----------------

## 3 Composition/information on ingredients

## | 3.1 Substance

	Not applicable
--	----------------

## | 3.2 Mixture

Component	Weight % content(or range)	Classification according to Regulation ( EC ) No. 1272/2008 with amendment 2023/707 [CLP]	Specific Conc. Limits, M-factors
<b>Benzene</b> CAS : 71-43-2 EC : 200-753-7 Index No. : 601-020-00-8	0.001	Flammable liquids, Category 2, H225; Aspiration hazard, Category 1, H304; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Germ cell mutagenicity, Category 1B, H340; Carcinogenicity, Category 1A, H350; Specific target organ toxicity - repeated exposure, Category 1, H372	-
<b>Toluene</b> CAS : 108-88-3 EC : 203-625-9 Index No. : 601-021-00-3	0.001	Flammable liquids, Category 2, H225; Aspiration hazard, Category 1, H304; Skin Corrosion/Irritation, Category 2, H315; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 2, H373	-
<b>Ethylbenzene</b> CAS : 100-41-4 EC : 202-849-4 Index No. : 601-023-00-4	0.001	Flammable liquids, Category 2, H225; Aspiration hazard, Category 1, H304; Acute Toxicity - Inhalation, Category 4, H332; Specific target organ toxicity - repeated exposure, Category 2, H373	-
<b>o-xylene</b> CAS : 95-47-6 EC : 202-422-2 Index No. : 601-022-00-9	0.001	Flammable liquids, Category 3, H226; Acute Toxicity - Dermal, Category 4, H312; Skin Corrosion/Irritation, Category 2, H315; Acute Toxicity - Inhalation, Category 4, H332	-
<b>m-xylene</b> CAS : 108-38-3 EC : 203-576-3 Index No. : 601-022-00-9	0.001	Flammable liquids, Category 3, H226; Acute Toxicity - Dermal, Category 4, H312; Skin Corrosion/Irritation, Category 2, H315; Acute Toxicity - Inhalation, Category 4, H332	-
<b>p-xylene</b> CAS : 106-42-3 EC : 203-396-5 Index No. : 601-022-00-9	0.001	Flammable liquids, Category 3, H226; Acute Toxicity - Dermal, Category 4, H312; Skin Corrosion/Irritation, Category 2, H315; Acute Toxicity - Inhalation, Category 4, H332	-
<b>Styrene</b> CAS : 100-42-5 EC : 202-851-5 Index No. : 601-026-00-0	0.001	Flammable liquids, Category 3, H226; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Acute Toxicity - Inhalation, Category 4, H332; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 1, H372	-
<b>Cumene</b> CAS : 98-82-8 EC : 202-704-5 Index No. : 601-024-00-X	0.001	Flammable liquids, Category 3, H226; Aspiration hazard, Category 1, H304; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Carcinogenicity, Category 1B, H350; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 2, H411	-
<b>Carbon disulphide</b> CAS : 75-15-0 EC : 200-843-6 Index No. : 006-003-00-3	99.992	Flammable liquids, Category 2, H225; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 1, H372	H361:C ≥ 1% H372:C ≥ 1% H373:0.2% ≤ C < 1%

## 4 First-aid measures

### 4.1 Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
<b>Eye contact</b>	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
<b>Skin contact</b>	First rinse with plenty of water, then remove contaminated clothes and rinse again. Refer for medical attention.
<b>Ingestion</b>	Give nothing to drink. Refer for medical attention.
<b>Inhalation</b>	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
<b>Protecting of first-aiders</b>	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

### 4.2 Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

### 4.3 Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

## 5 Fire-fighting measures

### 5.1 Extinguishing media

<b>Suitable extinguishing media</b>	Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
<b>Unsuitable extinguishing media</b>	Use of water spray when fighting fire may be inefficient.

### 5.2 Specific hazards arising from the substance or mixture

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
4	Liquid and vapour are flammable.
5	Development of hazardous combustion gases or vapor possible in the event of fire.
6	May expansion or decompose explosively when heated or involved in fire.

### 5.3 Advice for firefighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

## 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

1	Avoid breathing vapours and contacting with skin and eye.
2	Beware of vapours accumulating to form explosive concentrations.
3	Vapours can accumulate in low areas.
4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
6	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
7	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

### 6.2 Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

### 6.3 Methods and materials for containment and cleaning up

1	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
2	In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
3	In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Cut off the source of the leak as much as possible.
9	Keep leaks in a ventilated place.
10	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
11	Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
12	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
13	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4 Reference to other sections

1	Personal Protective Equipment advice is contained in Section 8 of the SDS.
2	Disposal considerations advice is contained in Section 13 of the SDS.

## 7 Handling and storage

### 7.1 Precautions for safe handling

#### ◆ Protective measures

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.

◆ Measures to prevent fire

1	Use only non-sparking tools.
2	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
3	Use explosion proof equipment.
4	Keep away from heat/sparks/open flames/ hot surfaces.

◆ Measures to prevent aerosol and dust generation

1	Not applicable.
---	-----------------

◆ Advice on general occupational hygiene

1	Wash hands and face after using the substances.
2	Replace the contaminated clothing immediately.

**7.2 Conditions for safe storage, including any incompatibilities**

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

**7.3 Specific end use(s)**

1	In addition to use mentioned in the Section 1.2, unforeseen other specific end uses.
---	--

**8 Exposure controls/personal protection**

**8.1 Control parameters**

◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
<b>Benzene</b>	Japan - JSOH(2024–2025)	1(individual excess lifetime risk of cancer 10 <sup>-3</sup> )	-	-	-
	Permissible exposure standards for workers in the workplace	1	3.2	2	6.4
	European Union	0.2	0.66	-	-
	France	1	3.25	-	-
	Germany (AGS)	0.6	1.9	4.8	15.2
	Italy	1	3.25	-	-
<b>Toluene</b>	Japan - JSOH(2024–2025)	50	188	-	-
	Permissible exposure standards for workers in the workplace	50	188	75	235
	European Union	50	192	100	384

	France	20	76.8	100	384
	Germany (AGS)	50	190	100	380
	Germany (DFG)	50	190	100	380
<b>Ethylbenzene</b>	Japan - JSOH(2024-2025)	20	87	-	-
	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	European Union	100	442	200	884
	France	20	88.4	100	442
	Germany (AGS)	20	88	40	176
	Germany (DFG)	20	88	40	176
<b>o-xylene</b>	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	European Union	50	221	100	442
	Germany (AGS)	50	220	100	440
	Germany (DFG)	50	220	100	440
	Italy	50	221	100	442
	United Kingdom	50	220	100	441
<b>m-xylene</b>	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	European Union	50	221	100	442
	France	50	221	100	442
	Germany (AGS)	50	220	100	440
	Germany (DFG)	50	220	100	440
	Italy	50	221	100	442
<b>p-xylene</b>	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	European Union	50	221	100	442
	France	50	221	100	442
	Germany (AGS)	50	220	100	440
	Germany (DFG)	50	220	100	440
	Italy	50	221	100	442
<b>Styrene</b>	Japan - JSOH(2024-2025)	10	42.6	-	-

	Permissible exposure standards for workers in the workplace	50	213	75	266.25
	France	23.3	100	46.6	200
	Germany (AGS)	20	86	40	172
	Germany (DFG)	20	86	40	172
	United Kingdom	100	430	250	1080
<b>Cumene</b>	Japan - JSOH(2024-2025)	10	50	-	-
	Permissible exposure standards for workers in the workplace	50	246	75	307.5
	European Union	10	50	50	250
	France	10	50	50	250
	Germany (AGS)	10	50	40	200
	Germany (DFG)	10	50	40	200
	<b>Carbon disulphide</b>	Japan - JSOH(2024-2025)	1	3.13	-
Permissible exposure standards for workers in the workplace		10	31	15	46.5
European Union		5	15	-	-
France		5	15	-	-
Germany (AGS)		10	30	20	60
Germany (DFG)		5	16	10	32

◆ Biological limit values

Component	Standard	Biological monitoring index	Biological limits value	Sampling time	Remark
<b>Benzene</b>	SCOEL(EU)	benzene/blood	28 µg/L	immediately end of shift	
		phenylmercapturic acid/urine	46 µg/L creatinine	end of exposure/shift	
		S-Phenylmercapturic acid(Creatinine in urine)	25µg/g	End of shift	
		t,t-Muconic acid(Creatinine in urine)	500µg/g	End of shift	
<b>Toluene</b>	USA -ACGIH	o-Cresol, with hydrolysis(Creatinine in urine)	0.3mg/g	End of shift	
		Toluene(Urine)	0.03mg/L	End of shift	

		Toluene(Blood)	0.02mg/L	Prior to last shift of work week	
<b>Ethylbenzene</b>	USA -ACGIH	Sum of mandelic acid and phenylglyoxylic acid(Creatinine in urine)	150mg/g	End of shift	
<b>o-xylene</b>	USA -ACGIH	Methylhippuric acids(Creatinine in urine)	0.3g/g	End of shift	
<b>m-xylene</b>	USA -ACGIH	Methylhippuric acids(Creatinine in urine)	0.3g/g	End of shift	
<b>p-xylene</b>	USA -ACGIH	Methylhippuric acids(Creatinine in urine)	0.3g/g	End of shift	
<b>Styrene</b>	USA -ACGIH	Mandelic acid plus phenylglyoxylic acid(Creatinine in urine)	150mg/g	End of shift	
		Styrene(Urine)	20µg/L	End of shift	
<b>Carbon disulphide</b>	SCOEL(EU)	2-thiothiazolidin e-4-carboxylic acid/urine	1.5mg/g creatinine	end of shift	
		2-Thiothiazolidin e-4-carboxylic acid (TTCA)(Creatinine in urine)	0.5mg/g	End of shift	

◆ Monitoring methods

1	EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
2	GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.

◆ Derived No effect level (DNEL)

Component	Route of exposure	DNEL for Workers			
		Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
<b>Benzene</b>	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Toluene</b>	Inhalation	No data available	No data available	192 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Ethylbenzene</b>	Inhalation	No data available	No data available	No data available	77 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>o-xylene</b>	Inhalation	No data available	No data available	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

<b>m-xylene</b>	Inhalation	No data available	No data available	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>p-xylene</b>	Inhalation	No data available	No data available	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Styrene</b>	Inhalation	No data available	No data available	100 mg/m <sup>3</sup>	100 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Cumene</b>	Inhalation	No data available	No data available	No data available	100 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Carbon disulphide</b>	Inhalation	No data available	No data available	No data available	15.8 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

◆ Predicted No Effect Concentration (PNEC)

Component	A	B	C	D	E	F	G	H
<b>Benzene</b>	80 µg/L	8 µg/L	39 mg/L	1.36 mg/kg sediment dw	136 µg/kg sediment dw	No data available	225 µg/kg soil dw	No potential for bioaccumulation
<b>Toluene</b>	74 - 680 µg/L	7.4 - 680 µg/L	840 - 13610 µg/L	1.78 - 16.39 mg/kg sediment dw	178 - 16390 µg/kg sediment dw	No hazard identified	313 - 2890 µg/kg soil dw	No potential for bioaccumulation
<b>Ethylbenzene</b>	100 µg/L	10 - 100 µg/L	9.6 mg/L	13.7 mg/kg sediment dw	1.37 mg/kg sediment dw	No hazard identified	2.68 mg/kg soil dw	20 mg/kg food
<b>o-xylene</b>	8.8 - 250 µg/L	880 - 250000 ng/L	1.6 - 5 mg/L	500 - 14330 µg/kg sediment dw	50 - 14330 µg/kg sediment dw	No hazard identified	95 - 2410 µg/kg soil dw	No potential for bioaccumulation
<b>m-xylene</b>	44 µg/L	4.4 µg/L	1.6 mg/L	2.52 mg/kg sediment dw	252 µg/kg sediment dw	No hazard identified	852 µg/kg soil dw	No potential for bioaccumulation
<b>p-xylene</b>	44 µg/L	4.4 µg/L	1.6 mg/L	2.52 mg/kg sediment dw	252 µg/kg sediment dw	No hazard identified	852 µg/kg soil dw	No potential for bioaccumulation
<b>Styrene</b>	28 - 40 µg/L	14 - 40 µg/L	5 mg/L	418 - 614 µg/kg sediment dw	307 - 418 µg/kg sediment dw	No hazard identified	146 - 200 µg/kg soil dw	No potential for bioaccumulation

<b>Cumene</b>	35 µg/L	3.5 µg/L	200 mg/L	3.22 mg/kg sediment dw	322 µg/kg sediment dw	No hazard identified	624 µg/kg soil dw	No potential for bioaccumulation
<b>Carbon disulphide</b>	10 µg/L	1 µg/L	130 µg/L	70 µg/kg sediment dw	7 µg/kg sediment dw	No hazard identified	8.1 µg/kg soil dw	No potential for bioaccumulation

**Note 1:**

A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).

**Note 2:**

The PNEC values of the remaining components not shown in the product are not available yet.

## 8.2 Exposure controls

### 8.2.1 Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

### 8.2.2 Personal protection equipment

<b>General requirement</b>	
<b>Eye protection</b>	Must wear appropriate safety goggles.
<b>Hand protection</b>	Must wear anti static chemical protective gloves.
<b>Respiratory protection</b>	Must wear appropriate personal respiratory protective equipment.
<b>Skin and body protection</b>	Must wear anti static chemical protective clothing and anti static shoes.

### 8.2.3 Environmental exposure controls

<b>Environmental exposure controls</b>	No information available
--	--------------------------

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Physical state</b>	Colorless to pale yellow liquid
<b>Colour</b>	Colorless to pale yellow liquid
<b>Odor</b>	Solvent odor
<b>Odor threshold</b>	No information available
<b>pH</b>	No information available
<b>Melting point/freezing point(°C)</b>	-111 ( Carbon disulphide )
<b>Initial boiling point and boiling range(°C)</b>	46 ( Carbon disulphide )
<b>Flash point(Closed cup, °C)</b>	-30 ( Carbon disulphide )
<b>Evaporation rate</b>	No information available

<b>Flammability</b>	No information available
<b>Upper/lower explosive limits[%(v/v)]</b>	Upper limit : 50 ( Carbon disulphide ); Lower limit : 1 ( Carbon disulphide )
<b>Vapor pressure</b>	48kPa ( 25°C,Carbon disulphide )
<b>Vapor density(Air = 1)</b>	2.63 ( Carbon disulphide )
<b>Relative density(Water=1)</b>	1.26 ( Carbon disulphide )
<b>Solubility</b>	2.9g/L ( 20 °C,Carbon disulphide )
<b>n-octanol/water partition coefficient</b>	1.84 ( Carbon disulphide )
<b>Auto-ignition temperature(°C)</b>	90 ( Carbon disulphide )
<b>Decomposition temperature(°C)</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Particle characteristics</b>	Not applicable

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

<b>Information with regard to physical hazard classes</b>	No information available
---	--------------------------

### 9.2.2 Other safety characteristics

<b>Other safety characteristics</b>	No information available
-------------------------------------	--------------------------

## 10 Stability and reactivity

### Stability and reactivity

<b>10.1 Reactivity</b>	Contact with incompatible substances can cause decomposition or other chemical reactions.
<b>10.2 Chemical stability</b>	Stable under proper operation and storage conditions.
<b>10.3 Possibility of hazardous reactions</b>	In contact with halides may cause an active reaction. May catch fire spontaneously in the air.
<b>10.4 Conditions to avoid</b>	Incompatible materials, heat, flame and spark.
<b>10.5 Incompatible materials</b>	Halides, oxidants and halogen. Nitrate and nitrite, halogens oxyacid salts, potassium permanganate, persulfate, halogen and strong oxidants.
<b>10.6 Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11 Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

8 Mix VOC in Carbon disulfide	
<b>Skin corrosion/irritation</b>	Causes skin irritation(Category 2)
<b>Serious eye damage/irritation</b>	Causes serious eye irritation(Category 2)
<b>Skin sensitization</b>	Based on available data, the classification criteria are not met
<b>Respiratory sensitization</b>	Based on available data, the classification criteria are not met
<b>Reproductive toxicity</b>	Suspected of damaging fertility and the unborn child(Category 2)
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met

<b>STOT-repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure(hearing organ)(Category 1)
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met

### | Acute toxicity

Component	LD <sub>50</sub> (oral)	LD <sub>50</sub> (dermal)	LC <sub>50</sub> (inhalation,4h)
<b>Styrene</b>	2650mg/kg(Rat)	No information available	12mg/L(Rat)
<b>Carbon disulphide</b>	1200mg/kg(Rat)	No information available	No information available
<b>Ethylbenzene</b>	3500mg/kg(Rat)	15400mg/kg(Rabbit)	No information available
<b>m-xylene</b>	5000mg/kg(Rat)	12200mg/kg(Rabbit)	No information available
<b>Benzene</b>	930mg/kg(Rat)	> 8260mg/kg(Rabbit)	No information available
<b>Cumene</b>	1400mg/kg(Rat)	10600mg/kg(Rabbit)	No information available
<b>p-xylene</b>	5000mg/kg(Rat)	No information available	19.758mg/L(Rat)
<b>Toluene</b>	636mg/kg(Rat)	12200mg/kg(Rabbit)	49mg/L(Rat)

### | Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP
<b>Benzene</b>	Category 1	Category K
<b>Toluene</b>	Category 3	Not Listed
<b>Ethylbenzene</b>	Category 2B	Not Listed
<b>o-xylene</b>	Not Listed	Not Listed
<b>m-xylene</b>	Not Listed	Not Listed
<b>p-xylene</b>	Not Listed	Not Listed
<b>Styrene</b>	Category 2A	Category R
<b>Cumene</b>	Category 2B	Category R
<b>Carbon disulphide</b>	Not Listed	Not Listed

## | 11.2 Information on other hazards

### | 11.2.1 Endocrine disrupting properties

Component	Endocrine disrupting properties
<b>Benzene</b>	No information available
<b>Toluene</b>	No information available
<b>Ethylbenzene</b>	No information available
<b>o-xylene</b>	No information available
<b>m-xylene</b>	No information available
<b>p-xylene</b>	No information available
<b>Styrene</b>	No information available
<b>Cumene</b>	No information available

<b>Carbon disulphide</b>	Existing research data indicates that this substance is not a reproductive or developmental toxicant, nor does it possess potential endocrine-disrupting properties; therefore, it is not considered a human endocrine disruptor.
--------------------------	---

### 11.2.2 Other Information

Other Information	See Section 11.1
-------------------	------------------

## 12 Ecological information

### 12.1 Toxicity

#### Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
<b>Styrene</b>	LC <sub>50</sub> : 4.02mg/L (96h)(Fish)	EC <sub>50</sub> : 4.7mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 0.72mg/L (96h)(Algae)
<b>o-xylene</b>	LC <sub>50</sub> : 16.1mg/L (96h)(Fish)	EC <sub>50</sub> : 1.1mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 0.80mg/L (72h)(Algae)
<b>Carbon disulphide</b>	LC <sub>50</sub> : 3mg/L (96h)(Fish)	No information available	ErC <sub>50</sub> : 21mg/L (96h)(Algae)
<b>Ethylbenzene</b>	LC <sub>50</sub> : 4.2mg/L (96h)(Fish)	EC <sub>50</sub> : 4.75mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 3.6mg/L (96h)(Algae)
<b>m-xylene</b>	LC <sub>50</sub> : 10.6mg/L (96h)(Fish)	EC <sub>50</sub> : 2.4mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 8.9mg/L (72h)(Algae)
<b>Benzene</b>	LC <sub>50</sub> : 21.6mg/L (96h)(Fish)	EC <sub>50</sub> : 10.9mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 1600mg/L (96h)(Algae)
<b>Cumene</b>	LC <sub>50</sub> : 4.8mg/L (96h)(Fish)	EC <sub>50</sub> : 10.6mg/L (48h)(Crustaceans)	No information available
<b>p-xylene</b>	LC <sub>50</sub> : 5.5mg/L (96h)(Fish)	EC <sub>50</sub> : 6.9mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 9.6mg/L (72h)(Algae)
<b>Toluene</b>	LC <sub>50</sub> : 25mg/L (96h)(Fish)	EC <sub>50</sub> : 4.1mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 29mg/L (72h)(Algae)

#### Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
<b>o-xylene</b>	No information available	NOEC : 0.63mg/L(Crustaceans)	NOEC : 0.73mg/L(Algae)
<b>m-xylene</b>	No information available	NOEC : 0.41mg/L(Crustaceans)	NOEC : 5.3mg/L(Algae)
<b>p-xylene</b>	No information available	NOEC : 1.3mg/L(Crustaceans)	NOEC : 4.4mg/L(Algae)
<b>Toluene</b>	No information available	NOEC : 1.2mg/L(Crustaceans)	NOEC : 9.1mg/L(Algae)

#### 12.2 Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
<b>o-xylene</b>	High(Half-life = 360 days)	Low(Half-life = 1.83 days)
<b>m-xylene</b>	High(Half-life = 360 days)	Low(Half-life = 1.08 days)
<b>p-xylene</b>	High(Half-life = 360 days)	Low(Half-life = 1.75 days)

### 12.3 Bioaccumulative potential

Component	Bioaccumulative potential	Comments
o-xylene	Low	BCF=219
m-xylene	Low	BCF=1.37
p-xylene	Low	BCF=2.2

### 12.4 Mobility in soil

Component	log Koc	Remark
Benzene	2.13	20 °C
Toluene	2.31	20 °C
Ethylbenzene	3.12	20 °C
o-xylene	2.73	20 °C
m-xylene	2.73	20 °C
p-xylene	2.73	20 °C
Styrene	2.55	
Cumene	2.95	20 °C
Carbon disulphide	1.53	20 °C

### 12.5 Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Benzene	Not PBT/vPvB
Toluene	Not PBT/vPvB
Ethylbenzene	Not PBT/vPvB
o-xylene	Not PBT/vPvB
m-xylene	Not PBT/vPvB
p-xylene	Not PBT/vPvB
Styrene	Not PBT/vPvB
Cumene	Not PBT/vPvB
Carbon disulphide	Not PBT/vPvB

### 12.6 Endocrine disrupting properties

Component	Endocrine disrupting properties
Benzene	No information available
Toluene	No information available
Ethylbenzene	No information available
o-xylene	No information available
m-xylene	No information available
p-xylene	No information available

<b>Styrene</b>	No information available
<b>Cumene</b>	No information available
<b>Carbon disulphide</b>	Existing research data indicates that this substance is not a reproductive or developmental toxicant, nor does it possess potential endocrine-disrupting properties; therefore, it is not considered an environmental endocrine disruptor.

### 12.7 Other adverse effects

	No information available
--	--------------------------

## 13 Disposal considerations

### 13.1 Waste treatment methods

<b>Waste chemicals</b>	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
<b>Contaminated packaging</b>	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
<b>Disposal recommendations</b>	Refer to section waste chemicals and contaminated packaging.

## 14 Transport information

### Label and Mark

<b>Transporting Label</b>	
---------------------------	--

### IMDG-CODE

<b>14.1 UN number</b>	1993
<b>14.2 UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3 Transport hazard class</b>	3
<b>14.4 Packing group</b>	II
<b>14.5 Environmental hazards (Yes or no)</b>	No

### IATA-DGR

<b>14.1 UN number</b>	1993
<b>14.2 UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3 Transport hazard class</b>	3
<b>14.4 Packing group</b>	II
<b>14.5 Environmental hazards (Yes or no)</b>	No

### UN-ADR

<b>14.1 UN number</b>	1993
<b>14.2 UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3 Transport hazard class</b>	3
<b>14.4 Packing group</b>	II
<b>14.5 Environmental hazards (Yes or no)</b>	No

## Special precautions for user

Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

## Maritime transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

## 15 Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International chemical inventory

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
Benzene	√	√	√	√	√	√	√	√	√	√	√	√	√
Toluene	√	√	√	√	√	√	√	√	√	√	√	√	√
Ethylbenzene	√	√	√	√	√	√	√	√	√	√	√	√	√
o-xylene	√	√	√	√	√	√	√	√	√	√	√	√	√
m-xylene	√	√	√	√	√	√	√	√	√	√	√	√	√
p-xylene	√	√	√	√	√	√	√	√	√	√	√	√	√
Styrene	√	√	√	√	√	√	√	√	√	√	√	√	√
Cumene	√	√	√	√	√	√	√	√	√	√	√	√	√
Carbon disulphide	√	√	√	√	√	√	√	√	√	√	√	√	√

- [A] China Inventory of Existing Chemical Substances(IECSC)  
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)  
 [C] United States Toxic Substances Control Act Inventory(TSCA)  
 [D] Canadian Domestic Substances List(DSL)  
 [E] New Zealand Inventory of Chemicals(NZIoC)  
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)  
 [G] Korea Existing Chemicals Inventory(KECL)  
 [H] Australian. Inventory of Industrial Chemical (AIICS)  
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)  
 [J] Thailand Existing Chemicals Inventory(TECI)  
 [K] Mexico National Inventory of Chemical Substances (INSQ)

- 【L】 Russia Inventory of Existing Substances (DRAFT)  
 【M】 Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

### List of Chemical Substances under International Conventions

Component	A	B	C
Benzene	×	×	×
Toluene	×	×	×
Ethylbenzene	×	×	×
o-xylene	×	×	×
m-xylene	×	×	×
p-xylene	×	×	×
Styrene	×	×	×
Cumene	×	×	×
Carbon disulphide	×	×	×

- 【A】 The Montreal Protocol on Substances that Deplete the Ozone Layer  
 【B】 Stockholm Convention on Persistent Organic Pollutants (POPs)  
 【C】 Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

### European chemical inventory

Component	A	B	C	D	E	F	G	H	I
Benzene	×	×	√	√	√	×	√	×	×
Toluene	×	×	√	√	√	√	×	×	×
Ethylbenzene	×	×	×	√	√	×	×	×	×
o-xylene	×	×	×	√	√	√	×	×	×
m-xylene	×	×	×	√	√	√	×	×	×
p-xylene	×	×	×	√	√	√	×	×	×
Styrene	×	×	×	√	√	×	×	×	×
Cumene	×	×	×	√	√	×	×	×	×
Carbon disulphide	×	×	×	√	√	√	×	×	×

- 【A】 Candidate list of Substances of Very High Concern for authorization under EU REACH regulation  
 【B】 Substances requiring authorisation under EU REACH regulation  
 【C】 Substances restricted under EU REACH  
 【D】 Pre-registered substances under EU REACH  
 【E】 Registered substances under EU REACH  
 【F】 Substance Evaluation – CoRAP under EU REACH  
 【G】 List of priority substances under EU water policy ( Directive 2455/2001/EC )  
 【H】 Substances subject to POPs Regulation  
 【I】 Substances proposed as POPs

Note:

“√” Indicates that the substance included in the regulations.

“×” No data or not included in the regulations.

### German water hazard class(WGK)

Component	WGK	Remark
-----------	-----	--------

<b>Benzene</b>	WGK 3	
<b>Toluene</b>	WGK 3	
<b>Ethylbenzene</b>	WGK 1	
<b>o-xylene</b>	WGK 2	
<b>m-xylene</b>	WGK 2	
<b>p-xylene</b>	WGK 2	
<b>Styrene</b>	WGK 2	
<b>Cumene</b>	WGK 3	
<b>Carbon disulphide</b>	WGK 2	

【WGK 1】 slightly hazardous to water  
 【WGK 2】 obviously hazardous to water  
 【WGK 3】 highly hazardous to water  
 【nwg】 non-hazardous to water  
 【awg】 hazardous to water in general

### German technical instructions on air quality control(TA LUFT)

Component	TA LUFT	Remark
<b>Benzene</b>	Chapter 5.2.7.1.1 Carcinogenic substances. Class II. As minimum requirement, the following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 1,5 g/hr or Mass conc.: 0,5 mg/m <sup>3</sup>	
<b>Toluene</b>	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m <sup>3</sup>	
<b>Ethylbenzene</b>	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
<b>o-xylene</b>	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
<b>m-xylene</b>	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5	

	Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
<b>p-xylene</b>	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
<b>Styrene</b>	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m <sup>3</sup>	
<b>Cumene</b>	Chapter 5.2.7.1.1 Carcinogenic Substances. The substance must be assigned to the class (I, II or III) whose substances have the nearest potency. We can not accomplish this evaluation due to insufficiency of data. Carcinogenic substances not mentioned by name and for which no information on potency is available should be assigned to Class I as a precautionary measure.	

### German technical rules for hazardous substances (TRGS)

Component	TRGS	Remark
<b>Benzene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 410 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>Toluene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>Ethylbenzene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>o-xylene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>m-xylene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	

	724	
<b>p-xylene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>Styrene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>Cumene</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 410 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
<b>Carbon disulphide</b>	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 TRGS 523	

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16 Other information

### Information on revision

<b>Creation Date</b>	2026/02/03
<b>Revision Date</b>	-
<b>Reason for revision</b>	-

### Reference

- [1] IPCS: The International Chemical SafetyCards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

### Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC <sub>50</sub>	Lethal Concentration 50%	NFPA	National Fire Protection Association

---

LD <sub>50</sub>	Lethal Dose 50%	NTP	National Toxicology Program
EC <sub>50</sub>	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC <sub>x</sub>	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P <sub>ow</sub>	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor		

## **Disclaimer**

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.