

## Safety Data Sheet

# 10 Mix TVOC in carbon disulfide

Version : V2.0.0.1

Report No. : BWQ7798-2016-MSDS-EP

Creation Date : 2025/12/30

Revision Date : -



\*Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)

## 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

|                           |                                 |
|---------------------------|---------------------------------|
| Product Name              | 10 Mix TVOC in carbon disulfide |
| Cat No.                   | BWQ7798-2016                    |
| CAS No.                   | Not applicable                  |
| EC No.                    | Not applicable                  |
| Molecular Formula         | Not applicable                  |
| REACH Registration Number | -                               |
| UFI                       | No information available        |

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

|                          |                              |
|--------------------------|------------------------------|
| Relevant identified uses | Please consult manufacturer. |
| Uses advised against     | Please consult manufacturer. |

### 1.3 Details of the supplier of the Safety Data Sheet

|                        |                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------|
| Name of the company    | Weiyel Inc                                                                                           |
| Address of the company | Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China |
| Post code              | 465350                                                                                               |
| Telephone number       | 010-58103678                                                                                         |
| Fax number             | 010-84840368                                                                                         |
| E-mail address         | info@weiyel.com                                                                                      |

### 1.4 Emergency telephone number

|                            |              |
|----------------------------|--------------|
| Emergency telephone number | 010-58103678 |
| Opening hours              | 24h          |

## 2 Hazards identification

### 2.1 CLP classification according to Regulation ( EC ) No. 1272/2008 with amendment 2023/707

|                                  |            |
|----------------------------------|------------|
| Flammable liquids                | Category 2 |
| Acute Toxicity - Oral            | Category 4 |
| Skin Corrosion/Irritation        | Category 2 |
| Serious eye damage/irritation    | Category 2 |
| Reproductive toxicity            | Category 2 |
| Specific target organ toxicity - | Category 1 |

|                                                                   |            |
|-------------------------------------------------------------------|------------|
| repeated exposure                                                 |            |
| Hazardous to the aquatic environment - long-term (chronic) hazard | Category 3 |

## 2.2 Label elements

|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Hazard pictograms |  |
| Signal word       | <b>Danger</b>                                                                      |

## Hazard statements

|        |                                                                                                |
|--------|------------------------------------------------------------------------------------------------|
| H225   | Highly flammable liquid and vapour                                                             |
| H302   | Harmful if swallowed                                                                           |
| H315   | Causes skin irritation                                                                         |
| H319   | Causes serious eye irritation                                                                  |
| H361df | Suspected of damaging fertility and the unborn child                                           |
| H372   | Causes damage to organs through prolonged or repeated exposure (hearing organ, nervous system) |
| H412   | Harmful to aquatic life with long lasting effects                                              |

## Precautionary statements

### ◆ Prevention

|      |                                                                                                |
|------|------------------------------------------------------------------------------------------------|
| P201 | Obtain special instructions before use.                                                        |
| P202 | Do not handle until all safety precautions have been read and understood.                      |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed.                                                                 |
| P240 | Ground and bond container and receiving equipment.                                             |
| P241 | Use explosion-proof [electrical/ventilating/lighting] equipment.                               |
| P242 | Use non-sparking tools.                                                                        |
| P243 | Take action to prevent static discharges.                                                      |
| P260 | Do not breathe gas/mist/vapour/spray.                                                          |
| P264 | Wash hands and other parts of the body (if related) thoroughly after handling.                 |
| P270 | Do not eat, drink or smoke when using this product.                                            |
| P273 | Avoid release to the environment.                                                              |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.                     |

### ◆ Response

|           |                                                               |
|-----------|---------------------------------------------------------------|
| P314      | Get medical advice/ attention if you feel unwell.             |
| P321      | Specific treatment (see related instructions on the label).   |
| P330      | Rinse mouth.                                                  |
| P301+P312 | IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. |
| P302+P352 | IF ON SKIN: Wash with plenty of water.                        |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.        |
| P332+P313 | If skin irritation occurs: Get medical advice/attention.      |

|                       |                                                                                                                                                                                                                                                                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>P337+P313</b>      | If eye irritation persists: Get medical advice/attention.                                                                                                                                                                                                                                                                                  |
| <b>P362+P364</b>      | Take off contaminated clothing and wash it before reuse.                                                                                                                                                                                                                                                                                   |
| <b>P370+P378</b>      | Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. |
| <b>P303+P361+P353</b> | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].                                                                                                                                                                                                                         |
| <b>P305+P351+P338</b> | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.                                                                                                                                                                                                           |

◆ Storage

|                  |                                              |
|------------------|----------------------------------------------|
| <b>P405</b>      | Store locked up.                             |
| <b>P403+P235</b> | Store in a well-ventilated place. Keep cool. |

◆ Disposal

|             |                                                                                                     |
|-------------|-----------------------------------------------------------------------------------------------------|
| <b>P501</b> | Dispose of contents/container in accordance with local/regional/national/international regulations. |
|-------------|-----------------------------------------------------------------------------------------------------|

## 2.3 Other hazards

◆ Results of PBT and vPvB assessment

| Component                | Results of PBT and vPvB assessment [according to (EC) No 1907/2006] |
|--------------------------|---------------------------------------------------------------------|
| <b>Carbon disulphide</b> | Not PBT/vPvB                                                        |
| <b>Benzene</b>           | Not PBT/vPvB                                                        |
| <b>Toluene</b>           | Not PBT/vPvB                                                        |
| <b>Ethylbenzene</b>      | Not PBT/vPvB                                                        |
| <b>o-xylene</b>          | Not PBT/vPvB                                                        |
| <b>p-xylene</b>          | Not PBT/vPvB                                                        |
| <b>Styrene</b>           | Not PBT/vPvB                                                        |
| <b>N-butyl acetate</b>   | Not PBT/vPvB                                                        |
| <b>Undecane</b>          | Not PBT/vPvB                                                        |
| <b>Hexadecane</b>        | Not PBT/vPvB                                                        |
| <b>N-hexane</b>          | Not PBT/vPvB                                                        |

◆ Results of endocrine disrupting properties assessment

| Component                | Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605] |
|--------------------------|------------------------------------------------------------------------------------------------------------|
| <b>Carbon disulphide</b> | Insufficient information, temporarily unable to evaluate                                                   |
| <b>Benzene</b>           | Insufficient information, temporarily unable to evaluate                                                   |
| <b>Toluene</b>           | Insufficient information, temporarily unable to evaluate                                                   |
| <b>Ethylbenzene</b>      | Insufficient information, temporarily unable to evaluate                                                   |
| <b>o-xylene</b>          | Insufficient information, temporarily unable to evaluate                                                   |
| <b>p-xylene</b>          | Insufficient information, temporarily unable to evaluate                                                   |
| <b>Styrene</b>           | Insufficient information, temporarily unable to evaluate                                                   |

|                        |                                                          |
|------------------------|----------------------------------------------------------|
| <b>N-butyl acetate</b> | Insufficient information, temporarily unable to evaluate |
| <b>Undecane</b>        | Insufficient information, temporarily unable to evaluate |
| <b>Hexadecane</b>      | Insufficient information, temporarily unable to evaluate |
| <b>N-hexane</b>        | Insufficient information, temporarily unable to evaluate |

◆ Other

Not applicable.

### 3 Composition/information on ingredients

#### 3.1 Substance

Not applicable

#### 3.2 Mixture

| Component                                                                               | Weight %<br>content(or<br>range) | Classification according to Regulation<br>( EC ) No. 1272/2008 with amendment<br>2023/707 [CLP]                                                                                                                                                                                                                                                  | Specific Conc. Limits,<br>M-factors          |
|-----------------------------------------------------------------------------------------|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| <b>Carbon disulphide</b><br>CAS : 75-15-0<br>EC : 200-843-6<br>Index No. : 006-003-00-3 | 99.6                             | Flammable liquids, Category 2, H225;<br>Skin Corrosion/Irritation, Category 2,<br>H315; Serious eye damage/irritation,<br>Category 2, H319; Reproductive toxicity,<br>Category 2, H361; Specific target organ<br>toxicity - repeated exposure, Category 1,<br>H372                                                                               | H361:C ≥ 1% H372:C ≥<br>1% H373:0.2% ≤C < 1% |
| <b>Benzene</b><br>CAS : 71-43-2<br>EC : 200-753-7<br>Index No. : 601-020-00-8           | 0.04                             | Flammable liquids, Category 2, H225;<br>Aspiration hazard, Category 1, H304; Skin<br>Corrosion/Irritation, Category 2, H315;<br>Serious eye damage/irritation, Category 2,<br>H319; Germ cell mutagenicity, Category<br>1B, H340; Carcinogenicity, Category 1A,<br>H350; Specific target organ toxicity -<br>repeated exposure, Category 1, H372 | -                                            |
| <b>Toluene</b><br>CAS : 108-88-3<br>EC : 203-625-9<br>Index No. : 601-021-00-3          | 0.04                             | Flammable liquids, Category 2, H225;<br>Aspiration hazard, Category 1, H304; Skin<br>Corrosion/Irritation, Category 2, H315;<br>Specific target organ toxicity - single<br>exposure; narcotic effects, Category 3,<br>H336; Reproductive toxicity, Category 2,<br>H361; Specific target organ toxicity -<br>repeated exposure, Category 2, H373  | -                                            |
| <b>Ethylbenzene</b><br>CAS : 100-41-4<br>EC : 202-849-4<br>Index No. : 601-023-00-4     | 0.04                             | Flammable liquids, Category 2, H225;<br>Aspiration hazard, Category 1, H304;<br>Acute Toxicity - Inhalation, Category 4,<br>H332; Specific target organ toxicity -<br>repeated exposure, Category 2, H373                                                                                                                                        | -                                            |
| <b>o-xylene</b><br>CAS : 95-47-6<br>EC : 202-422-2<br>Index No. : 601-022-00-9          | 0.04                             | Flammable liquids, Category 3, H226;<br>Acute Toxicity - Dermal, Category 4, H312;<br>Skin Corrosion/Irritation, Category 2,<br>H315; Acute Toxicity - Inhalation, Category<br>4, H332                                                                                                                                                           | -                                            |
| <b>p-xylene</b><br>CAS : 106-42-3<br>EC : 203-396-5<br>Index No. : 601-022-00-9         | 0.04                             | Flammable liquids, Category 3, H226;<br>Acute Toxicity - Dermal, Category 4, H312;<br>Skin Corrosion/Irritation, Category 2,<br>H315; Acute Toxicity - Inhalation, Category<br>4, H332                                                                                                                                                           | -                                            |
| <b>Styrene</b><br>CAS : 100-42-5<br>EC : 202-851-5                                      | 0.04                             | Flammable liquids, Category 3, H226;<br>Skin Corrosion/Irritation, Category 2,<br>H315; Serious eye damage/irritation,                                                                                                                                                                                                                           | -                                            |

|                                                                                        |      |                                                                                                                                                                                                                                                                                                                                                                                                                 |   |
|----------------------------------------------------------------------------------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| Index No. : 601-026-00-0                                                               |      | Category 2, H319; Acute Toxicity - Inhalation, Category 4, H332; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 1, H372                                                                                                                                                                                                                                  |   |
| <b>N-butyl acetate</b><br>CAS : 123-86-4<br>EC : 204-658-1<br>Index No. : 607-025-00-1 | 0.04 | Flammable liquids, Category 3, H226; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Repeated exposure may cause skin dryness or cracking, EUH066                                                                                                                                                                                                                         | - |
| <b>Undecane</b><br>CAS : 1120-21-4<br>EC : 214-300-6<br>Index No. : -                  | 0.04 | Aspiration hazard, Category 1, H304                                                                                                                                                                                                                                                                                                                                                                             | - |
| <b>Hexadecane</b><br>CAS : 544-76-3<br>EC : 208-878-9<br>Index No. : -                 | 0.04 | Aspiration hazard, Category 1, H304                                                                                                                                                                                                                                                                                                                                                                             | - |
| <b>N-hexane</b><br>CAS : 110-54-3<br>EC : 203-777-6<br>Index No. : 601-037-00-0        | 0.04 | Flammable liquids, Category 2, H225; Aspiration hazard, Category 1, H304; Skin Corrosion/Irritation, Category 2, H315; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 1, H372; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 2, H411 | - |

## 4 First-aid measures

### 4.1 Description of first aid measures

|                                   |                                                                                                                                                                                                                                             |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General advice</b>             | Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.                                                                                                                                     |
| <b>Eye contact</b>                | First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.                                                                                                                     |
| <b>Skin contact</b>               | First rinse with plenty of water, then remove contaminated clothes and rinse again. Refer for medical attention.                                                                                                                            |
| <b>Ingestion</b>                  | Give nothing to drink. Refer for medical attention.                                                                                                                                                                                         |
| <b>Inhalation</b>                 | Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately. |
| <b>Protecting of first-aiders</b> | Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.                                                                                              |

### 4.2 Most important symptoms/effects, acute and delayed

|   |                                                                                                                                        |
|---|----------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. |
|---|----------------------------------------------------------------------------------------------------------------------------------------|

### 4.3 Indication of any immediate medical attention and special treatment needed

|   |                          |
|---|--------------------------|
| 1 | Treat symptomatically.   |
| 2 | Symptoms may be delayed. |

## 5 Fire-fighting measures

### 5.1 Extinguishing media

|                                       |                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable extinguishing media</b>   | Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. |
| <b>Unsuitable extinguishing media</b> | Use of water spray when fighting fire may be inefficient.                                                                                                                                                                                                                                                                                  |

## 5.2 Specific hazards arising from the substance or mixture

|   |                                                                                                                                         |
|---|-----------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Will form explosive mixtures with air.                                                                                                  |
| 2 | Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration. |
| 3 | Vapours may travel to source of ignition and flash back.                                                                                |
| 4 | Liquid and vapour are flammable.                                                                                                        |
| 5 | Development of hazardous combustion gases or vapor possible in the event of fire.                                                       |
| 6 | May expansion or decompose explosively when heated or involved in fire.                                                                 |

## 5.3 Advice for firefighters

|   |                                                                                                                       |
|---|-----------------------------------------------------------------------------------------------------------------------|
| 1 | As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. |
| 2 | Fight fire from a safe distance, with adequate cover.                                                                 |
| 3 | Prevent fire extinguishing water from contaminating surface water or the ground water system.                         |

# 6 Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

|   |                                                                                                                                                            |
|---|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Avoid breathing vapours and contacting with skin and eye.                                                                                                  |
| 2 | Beware of vapours accumulating to form explosive concentrations.                                                                                           |
| 3 | Vapours can accumulate in low areas.                                                                                                                       |
| 4 | Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves. |
| 5 | Use personal protective equipment, do not breathe gas/mist/vapour/spray.                                                                                   |
| 6 | Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.                                        |
| 7 | Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.                                                                          |

## 6.2 Environmental precautions

|   |                                                       |
|---|-------------------------------------------------------|
| 1 | Prevent further leakage or spillage if safe to do so. |
| 2 | Discharge into the environment must be avoided.       |

## 6.3 Methods and materials for containment and cleaning up

|   |                                                                                                                                                                                                                                                            |
|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.                                                                                                                        |
| 2 | In case of small amount of spillage, use clean non sparking tools to collect absorption materials.                                                                                                                                                         |
| 3 | In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space. |
| 4 | Collect absorbent material using a clean, non-sparking tool.                                                                                                                                                                                               |
| 5 | Cover with anti-solvent foam to reduce evaporation.                                                                                                                                                                                                        |
| 6 | Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.                                                                                                                   |

|    |                                                                                                                             |
|----|-----------------------------------------------------------------------------------------------------------------------------|
| 7  | Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.                          |
| 8  | Cut off the source of the leak as much as possible.                                                                         |
| 9  | Keep leaks in a ventilated place.                                                                                           |
| 10 | Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.    |
| 11 | Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.                                        |
| 12 | Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container. |
| 13 | Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.                                        |

## 6.4 Reference to other sections

|   |                                                                            |
|---|----------------------------------------------------------------------------|
| 1 | Personal Protective Equipment advice is contained in Section 8 of the SDS. |
| 2 | Disposal considerations advice is contained in Section 13 of the SDS.      |

## 7 Handling and storage

### 7.1 Precautions for safe handling

#### ◆ Protective measures

|   |                                                   |
|---|---------------------------------------------------|
| 1 | Handling is performed in a well ventilated place. |
| 2 | Wear suitable protective equipment.               |
| 3 | Avoid contact with skin and eyes.                 |

#### ◆ Measures to prevent fire

|   |                                                                                                           |
|---|-----------------------------------------------------------------------------------------------------------|
| 1 | Use only non-sparking tools.                                                                              |
| 2 | To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded. |
| 3 | Use explosion proof equipment.                                                                            |
| 4 | Keep away from heat/sparks/open flames/ hot surfaces.                                                     |

#### ◆ Measures to prevent aerosol and dust generation

|   |                 |
|---|-----------------|
| 1 | Not applicable. |
|---|-----------------|

#### ◆ Advice on general occupational hygiene

|   |                                                 |
|---|-------------------------------------------------|
| 1 | Wash hands and face after using the substances. |
| 2 | Replace the contaminated clothing immediately.  |

### 7.2 Conditions for safe storage, including any incompatibilities

|   |                                                                  |
|---|------------------------------------------------------------------|
| 1 | Keep containers tightly closed.                                  |
| 2 | Keep containers in a dry, cool and well-ventilated place.        |
| 3 | Keep away from heat/sparks/open flames/hot surfaces.             |
| 4 | Store away from incompatible materials and foodstuff containers. |

### 7.3 Specific end use(s)

|   |                                                                                      |
|---|--------------------------------------------------------------------------------------|
| 1 | In addition to use mentioned in the Section 1.2, unforeseen other specific end uses. |
|---|--------------------------------------------------------------------------------------|

## 8 Exposure controls/personal protection

### 8.1 Control parameters

#### ◆ Occupational exposure limit values

| Component | Country/Region | Limit value - Eight hours | Limit value - Short term |
|-----------|----------------|---------------------------|--------------------------|
|-----------|----------------|---------------------------|--------------------------|

|                          |                                                             | ppm                                                            | mg/m <sup>3</sup> | ppm | mg/m <sup>3</sup> |
|--------------------------|-------------------------------------------------------------|----------------------------------------------------------------|-------------------|-----|-------------------|
| <b>Carbon disulphide</b> | Japan - JSOH(2024–2025)                                     | 1                                                              | 3.13              | -   | -                 |
|                          | Permissible exposure standards for workers in the workplace | 10                                                             | 31                | 15  | 46.5              |
|                          | European Union                                              | 5                                                              | 15                | -   | -                 |
|                          | France                                                      | 5                                                              | 15                | -   | -                 |
|                          | Germany (AGS)                                               | 10                                                             | 30                | 20  | 60                |
|                          | Germany (DFG)                                               | 5                                                              | 16                | 10  | 32                |
| <b>Benzene</b>           | Japan - JSOH(2024–2025)                                     | 1(individual excess lifetime risk of cancer 10 <sup>-3</sup> ) | -                 | -   | -                 |
|                          | Permissible exposure standards for workers in the workplace | 1                                                              | 3.2               | 2   | 6.4               |
|                          | European Union                                              | 0.2                                                            | 0.66              | -   | -                 |
|                          | France                                                      | 1                                                              | 3.25              | -   | -                 |
|                          | Germany (AGS)                                               | 0.6                                                            | 1.9               | 4.8 | 15.2              |
|                          | Italy                                                       | 1                                                              | 3.25              | -   | -                 |
| <b>Toluene</b>           | Japan - JSOH(2024–2025)                                     | 50                                                             | 188               | -   | -                 |
|                          | Permissible exposure standards for workers in the workplace | 50                                                             | 188               | 75  | 235               |
|                          | European Union                                              | 50                                                             | 192               | 100 | 384               |
|                          | France                                                      | 20                                                             | 76.8              | 100 | 384               |
|                          | Germany (AGS)                                               | 50                                                             | 190               | 100 | 380               |
|                          | Germany (DFG)                                               | 50                                                             | 190               | 100 | 380               |
| <b>Ethylbenzene</b>      | Japan - JSOH(2024–2025)                                     | 20                                                             | 87                | -   | -                 |
|                          | Permissible exposure standards for workers in the workplace | 100                                                            | 434               | 125 | 542.5             |
|                          | European Union                                              | 100                                                            | 442               | 200 | 884               |
|                          | France                                                      | 20                                                             | 88.4              | 100 | 442               |
|                          | Germany (AGS)                                               | 20                                                             | 88                | 40  | 176               |
|                          | Germany (DFG)                                               | 20                                                             | 88                | 40  | 176               |



|                        |                                                             |      |      |       |        |
|------------------------|-------------------------------------------------------------|------|------|-------|--------|
| <b>o-xylene</b>        | Permissible exposure standards for workers in the workplace | 100  | 434  | 125   | 542.5  |
|                        | European Union                                              | 50   | 221  | 100   | 442    |
|                        | Germany (AGS)                                               | 50   | 220  | 100   | 440    |
|                        | Germany (DFG)                                               | 50   | 220  | 100   | 440    |
|                        | Italy                                                       | 50   | 221  | 100   | 442    |
|                        | United Kingdom                                              | 50   | 220  | 100   | 441    |
| <b>p-xylene</b>        | Permissible exposure standards for workers in the workplace | 100  | 434  | 125   | 542.5  |
|                        | European Union                                              | 50   | 221  | 100   | 442    |
|                        | France                                                      | 50   | 221  | 100   | 442    |
|                        | Germany (AGS)                                               | 50   | 220  | 100   | 440    |
|                        | Germany (DFG)                                               | 50   | 220  | 100   | 440    |
|                        | Italy                                                       | 50   | 221  | 100   | 442    |
| <b>Styrene</b>         | Japan - JSOH(2024–2025)                                     | 10   | 42.6 | -     | -      |
|                        | Permissible exposure standards for workers in the workplace | 50   | 213  | 75    | 266.25 |
|                        | France                                                      | 23.3 | 100  | 46.6  | 200    |
|                        | Germany (AGS)                                               | 20   | 86   | 40    | 172    |
|                        | Germany (DFG)                                               | 20   | 86   | 40    | 172    |
|                        | United Kingdom                                              | 100  | 430  | 250   | 1080   |
| <b>N-butyl acetate</b> | Japan - JSOH(2024–2025)                                     | 100  | 475  | -     | -      |
|                        | Permissible exposure standards for workers in the workplace | 150  | 712  | 187.5 | 890    |
|                        | European Union                                              | 50   | 241  | 150   | 723    |
|                        | France                                                      | 50   | 241  | 150   | 723    |
|                        | Germany (AGS)                                               | 62   | 300  | 124   | 600    |
|                        | Germany (DFG)                                               | 100  | 480  | 200   | 960    |
| <b>N-hexane</b>        | Japan - JSOH(2024–2025)                                     | 40   | 140  | -     | -      |
|                        | Permissible exposure standards for                          | 50   | 176  | 75    | 220    |

|  |                          |    |     |     |      |
|--|--------------------------|----|-----|-----|------|
|  | workers in the workplace |    |     |     |      |
|  | European Union           | 20 | 72  | -   | -    |
|  | France                   | 20 | 72  | -   | -    |
|  | Germany (AGS)            | 50 | 180 | 400 | 1440 |
|  | Germany (DFG)            | 50 | 180 | 400 | 1440 |

◆ Biological limit values

| Component                | Standard   | Biological monitoring index                                        | Biological limits value | Sampling time                    | Remark |
|--------------------------|------------|--------------------------------------------------------------------|-------------------------|----------------------------------|--------|
| <b>Carbon disulphide</b> | SCOEL(EU)  | 2-thiothiazolidine-4-carboxylic acid/urine                         | 1.5mg/g creatinine      | end of shift                     |        |
|                          |            | 2-Thiothiazolidine-4-carboxylic acid (TTCA)(Creatinine in urine)   | 0.5mg/g                 | End of shift                     |        |
| <b>Benzene</b>           | SCOEL(EU)  | benzene/blood                                                      | 28 µg/L                 | immediately end of shift         |        |
|                          |            | phenylmercapturic acid/urine                                       | 46 µg/L creatinine      | end of exposure/shift            |        |
|                          |            | S-Phenylmercapturic acid(Creatinine in urine)                      | 25µg/g                  | End of shift                     |        |
|                          |            | t,t-Muconic acid(Creatinine in urine)                              | 500µg/g                 | End of shift                     |        |
| <b>Toluene</b>           | USA -ACGIH | o-Cresol, with hydrolysis(Creatinine in urine)                     | 0.3mg/g                 | End of shift                     |        |
|                          |            | Toluene(Urine)                                                     | 0.03mg/L                | End of shift                     |        |
|                          |            | Toluene(Blood)                                                     | 0.02mg/L                | Prior to last shift of work week |        |
| <b>Ethylbenzene</b>      | USA -ACGIH | Sum of mandelic acid and phenylglyoxylic acid(Creatinine in urine) | 150mg/g                 | End of shift                     |        |
| <b>o-xylene</b>          | USA -ACGIH | Methylhippuric acids(Creatinine in urine)                          | 0.3g/g                  | End of shift                     |        |
| <b>p-xylene</b>          | USA -ACGIH | Methylhippuric acids(Creatinine in urine)                          | 0.3g/g                  | End of shift                     |        |
| <b>Styrene</b>           | USA -ACGIH | Mandelic acid plus phenylglyoxylic acid(Creatinine in urine)       | 150mg/g                 | End of shift                     |        |
|                          |            | Styrene(Urine)                                                     | 20µg/L                  | End of shift                     |        |
| <b>N-hexane</b>          | USA -ACGIH | 2,5-Hexanedione, without hydrolysis(Urine)                         | 0.5mg/L                 | End of shift                     |        |

◆ Monitoring methods

|   |                                                                                                                                                   |
|---|---------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. |
| 2 | GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.                                                       |

◆ Derived No effect level (DNEL)

| Component         | Route of exposure | DNEL for Workers      |                          |                         |                            |
|-------------------|-------------------|-----------------------|--------------------------|-------------------------|----------------------------|
|                   |                   | Acute effects (local) | Acute effects (systemic) | Chronic effects (local) | Chronic effects (systemic) |
| Carbon disulphide | Inhalation        | No data available     | No data available        | No data available       | 15.8 mg/m3                 |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| Benzene           | Inhalation        | No data available     | No data available        | No data available       | No data available          |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| Toluene           | Inhalation        | No data available     | No data available        | 192 mg/m3               | 192 mg/m3                  |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| Ethylbenzene      | Inhalation        | No data available     | No data available        | No data available       | 77 mg/m3                   |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| o-xylene          | Inhalation        | No data available     | No data available        | 221 mg/m3               | 221 mg/m3                  |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| p-xylene          | Inhalation        | No data available     | No data available        | 221 mg/m3               | 221 mg/m3                  |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| Styrene           | Inhalation        | No data available     | No data available        | 100 mg/m3               | 100 mg/m3                  |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| N-butyl acetate   | Inhalation        | No data available     | No data available        | 300 mg/m3               | 300 mg/m3                  |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| Undecane          | Inhalation        | No data available     | No data available        | No data available       | No data available          |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| Hexadecane        | Inhalation        | No data available     | No data available        | No data available       | No data available          |
|                   | Oral              | No data available     | No data available        | No data available       | No data available          |
|                   | Dermal            | No data available     | No data available        | No data available       | No data available          |
| N-hexane          | Inhalation        | No data available     | No data available        | No data available       | 75 mg/m3                   |

|  |        |                   |                   |                   |                   |
|--|--------|-------------------|-------------------|-------------------|-------------------|
|  | Oral   | No data available | No data available | No data available | No data available |
|  | Dermal | No data available | No data available | No data available | No data available |

◆ Predicted No Effect Concentration (PNEC)

| Component                | A                 | B                 | C                 | D                              | E                             | F                    | G                        | H                                |
|--------------------------|-------------------|-------------------|-------------------|--------------------------------|-------------------------------|----------------------|--------------------------|----------------------------------|
| <b>Carbon disulphide</b> | 10 µg/L           | 1 µg/L            | 130 µg/L          | 70 µg/kg sediment dw           | 7 µg/kg sediment dw           | No hazard identified | 8.1 µg/kg soil dw        | No potential for bioaccumulation |
| <b>Benzene</b>           | 80 µg/L           | 8 µg/L            | 39 mg/L           | 1.36 mg/kg sediment dw         | 136 µg/kg sediment dw         | No data available    | 225 µg/kg soil dw        | No potential for bioaccumulation |
| <b>Toluene</b>           | 74 - 680 µg/L     | 7.4 - 680 µg/L    | 840 - 13610 µg/L  | 1.78 - 16.39 mg/kg sediment dw | 178 - 16390 µg/kg sediment dw | No hazard identified | 313 - 2890 µg/kg soil dw | No potential for bioaccumulation |
| <b>Ethylbenzene</b>      | 100 µg/L          | 10 - 100 µg/L     | 9.6 mg/L          | 13.7 mg/kg sediment dw         | 1.37 mg/kg sediment dw        | No hazard identified | 2.68 mg/kg soil dw       | 20 mg/kg food                    |
| <b>o-xylene</b>          | 8.8 - 250 µg/L    | 880 - 250000 ng/L | 1.6 - 5 mg/L      | 500 - 14330 µg/kg sediment dw  | 50 - 14330 µg/kg sediment dw  | No hazard identified | 95 - 2410 µg/kg soil dw  | No potential for bioaccumulation |
| <b>p-xylene</b>          | 44 µg/L           | 4.4 µg/L          | 1.6 mg/L          | 2.52 mg/kg sediment dw         | 252 µg/kg sediment dw         | No hazard identified | 852 µg/kg soil dw        | No potential for bioaccumulation |
| <b>Styrene</b>           | 28 - 40 µg/L      | 14 - 40 µg/L      | 5 mg/L            | 418 - 614 µg/kg sediment dw    | 307 - 418 µg/kg sediment dw   | No hazard identified | 146 - 200 µg/kg soil dw  | No potential for bioaccumulation |
| <b>N-butyl acetate</b>   | 180 µg/L          | 18 µg/L           | 35.6 mg/L         | 981 µg/kg sediment dw          | 98.1 µg/kg sediment dw        | No hazard identified | 90.3 µg/kg soil dw       | No potential for bioaccumulation |
| <b>Undecane</b>          | No data available | No data available | No data available | No data available              | No data available             | No hazard identified | No data available        | No data available                |
| <b>Hexadecane</b>        | No data available | No data available | No data available | No data available              | No data available             | No hazard identified | No data available        | No data available                |
| <b>N-hexane</b>          | No data available | No data available | No data available | No data available              | No data available             | No hazard identified | No data available        | No potential for                 |

|                                                                                                                                                                                                                                                                                                                         |  |  |  |  |  |  |  |                 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|--|-----------------|
|                                                                                                                                                                                                                                                                                                                         |  |  |  |  |  |  |  | bioaccumulation |
| <p><b>Note 1:</b><br/>A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).</p> <p><b>Note 2:</b><br/>The PNEC values of the remaining components not shown in the product are not available yet.</p> |  |  |  |  |  |  |  |                 |

## 8.2 Exposure controls

### 8.2.1 Engineering controls

|   |                                                                                        |
|---|----------------------------------------------------------------------------------------|
| 1 | Ensure adequate ventilation, especially in confined areas.                             |
| 2 | Ensure that eyewash stations and safety showers are close to the workstation location. |
| 3 | Use explosion-proof electrical/ventilating/lighting/equipment.                         |
| 4 | Set up emergency exit and necessary risk-elimination area.                             |

### 8.2.2 Personal protection equipment

| General requirement      |      |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye protection           | Must wear appropriate safety goggles.                                                                                                                                                                                                                                                                                                                                                                                        |
| Hand protection          | Must wear anti static chemical protective gloves.                                                                                                                                                                                                                                                                                                                                                                            |
| Respiratory protection   | Must wear appropriate personal respiratory protective equipment.                                                                                                                                                                                                                                                                                                                                                             |
| Skin and body protection | Must wear anti static chemical protective clothing and anti static shoes.                                                                                                                                                                                                                                                                                                                                                    |

### 8.2.3 Environmental exposure controls

|                                 |                          |
|---------------------------------|--------------------------|
| Environmental exposure controls | No information available |
|---------------------------------|--------------------------|

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|                                             |                                                                               |
|---------------------------------------------|-------------------------------------------------------------------------------|
| Physical state                              | colorless liquid                                                              |
| Colour                                      | colorless liquid                                                              |
| Odor                                        | No information available                                                      |
| Odor threshold                              | No information available                                                      |
| pH                                          | No information available                                                      |
| Melting point/freezing point(°C)            | -111 ( Carbon disulphide )                                                    |
| Initial boiling point and boiling range(°C) | 46 ( Carbon disulphide )                                                      |
| Flash point(Closed cup,°C)                  | -30 ( Carbon disulphide )                                                     |
| Evaporation rate                            | No information available                                                      |
| Flammability                                | No information available                                                      |
| Upper/lower explosive limits[% (v/v)]       | Upper limit : 50 ( Carbon disulphide ); Lower limit : 1 ( Carbon disulphide ) |
| Vapor pressure                              | 48kPa ( 25°C,Carbon disulphide )                                              |
| Vapor density(Air = 1)                      | 2.63 ( Carbon disulphide )                                                    |

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Relative density(Water=1)             | 1.26 ( Carbon disulphide )         |
| Solubility                            | 2.9g/L ( 20 °C,Carbon disulphide ) |
| n-octanol/water partition coefficient | 1.84 ( Carbon disulphide )         |
| Auto-ignition temperature(°C)         | 90 ( Carbon disulphide )           |
| Decomposition temperature(°C)         | No information available           |
| Kinematic viscosity                   | No information available           |
| Explosive properties                  | No information available           |
| Oxidizing properties                  | No information available           |
| Particle characteristics              | Not applicable                     |

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

|                                                    |                          |
|----------------------------------------------------|--------------------------|
| Information with regard to physical hazard classes | No information available |
|----------------------------------------------------|--------------------------|

### 9.2.2 Other safety characteristics

|                              |                          |
|------------------------------|--------------------------|
| Other safety characteristics | No information available |
|------------------------------|--------------------------|

## 10 Stability and reactivity

### Stability and reactivity

|                                         |                                                                                                                                                                                                                                                               |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity                         | Contact with incompatible substances can cause decomposition or other chemical reactions.                                                                                                                                                                     |
| 10.2 Chemical stability                 | Stable under proper operation and storage conditions.                                                                                                                                                                                                         |
| 10.3 Possibility of hazardous reactions | May catch fire spontaneously in the air. In contact with halides may cause an active reaction. In contact with metal alkoxides may cause a fire. In contact with an open flame may cause a fire or explosion.                                                 |
| 10.4 Conditions to avoid                | Incompatible materials, heat, flame and spark.                                                                                                                                                                                                                |
| 10.5 Incompatible materials             | Nitrate and nitrite, halogens oxyacid salts, potassium permanganate, persulfate, halogen and strong oxidants. Halides, oxidants and halogen. Metal alkyl oxide, metal hydride, inorganic peroxide, nitrate and halogens oxyacid salts. Oxidantss and halogen. |
| 10.6 Hazardous decomposition products   | Under normal conditions of storage and use, hazardous decomposition products should not be produced.                                                                                                                                                          |

## 11 Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

| 10 Mix TVOC in carbon disulfide |                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------|
| Skin corrosion/irritation       | Causes skin irritation(Category 2)                                                                        |
| Serious eye damage/irritation   | Causes serious eye irritation(Category 2)                                                                 |
| Skin sensitization              | Based on available data, the classification criteria are not met                                          |
| Respiratory sensitization       | Based on available data, the classification criteria are not met                                          |
| Reproductive toxicity           | Suspected of damaging fertility and the unborn child(Category 2)                                          |
| STOT-single exposure            | Based on available data, the classification criteria are not met                                          |
| STOT-repeated exposure          | Causes damage to organs through prolonged or repeated exposure(hearing organ, nervous system)(Category 1) |

|                               |                                                                  |
|-------------------------------|------------------------------------------------------------------|
| <b>Aspiration hazard</b>      | Based on available data, the classification criteria are not met |
| <b>Germ cell mutagenicity</b> | Based on available data, the classification criteria are not met |

### | Acute toxicity

| Component                | LD <sub>50</sub> (oral) | LD <sub>50</sub> (dermal) | LC <sub>50</sub> (inhalation,4h) |
|--------------------------|-------------------------|---------------------------|----------------------------------|
| <b>Ethylbenzene</b>      | 3500mg/kg(Rat)          | 15400mg/kg(Rabbit)        | No information available         |
| <b>Benzene</b>           | 930mg/kg(Rat)           | > 8260mg/kg(Rabbit)       | No information available         |
| <b>Styrene</b>           | 2650mg/kg(Rat)          | No information available  | 12mg/L(Rat)                      |
| <b>p-xylene</b>          | 5000mg/kg(Rat)          | No information available  | 19.758mg/L(Rat)                  |
| <b>Toluene</b>           | 636mg/kg(Rat)           | 12200mg/kg(Rabbit)        | 49mg/L(Rat)                      |
| <b>N-butyl acetate</b>   | 10768mg/kg(Rat)         | > 17600mg/kg(Rabbit)      | No information available         |
| <b>N-hexane</b>          | 25000mg/kg(Rat)         | No information available  | 169.188mg/L(Rat)                 |
| <b>Carbon disulphide</b> | 1200mg/kg(Rat)          | No information available  | No information available         |

### | Carcinogenicity

| Component                | List of carcinogens by the IARC Monographs | Report on Carcinogens by NTP |
|--------------------------|--------------------------------------------|------------------------------|
| <b>Carbon disulphide</b> | Not Listed                                 | Not Listed                   |
| <b>Benzene</b>           | Category 1                                 | Category K                   |
| <b>Toluene</b>           | Category 3                                 | Not Listed                   |
| <b>Ethylbenzene</b>      | Category 2B                                | Not Listed                   |
| <b>o-xylene</b>          | Not Listed                                 | Not Listed                   |
| <b>p-xylene</b>          | Not Listed                                 | Not Listed                   |
| <b>Styrene</b>           | Category 2A                                | Category R                   |
| <b>N-butyl acetate</b>   | Not Listed                                 | Not Listed                   |
| <b>Undecane</b>          | Not Listed                                 | Not Listed                   |
| <b>Hexadecane</b>        | Not Listed                                 | Not Listed                   |
| <b>N-hexane</b>          | Not Listed                                 | Not Listed                   |

## | 11.2 Information on other hazards

### | 11.2.1 Endocrine disrupting properties

| Component                | Endocrine disrupting properties |
|--------------------------|---------------------------------|
| <b>Carbon disulphide</b> | No information available        |
| <b>Benzene</b>           | No information available        |
| <b>Toluene</b>           | No information available        |
| <b>Ethylbenzene</b>      | No information available        |
| <b>o-xylene</b>          | No information available        |
| <b>p-xylene</b>          | No information available        |
| <b>Styrene</b>           | No information available        |

|                        |                          |
|------------------------|--------------------------|
| <b>N-butyl acetate</b> | No information available |
| <b>Undecane</b>        | No information available |
| <b>Hexadecane</b>      | No information available |
| <b>N-hexane</b>        | No information available |

### 11.2.2 Other Information

|                          |                  |
|--------------------------|------------------|
| <b>Other Information</b> | See Section 11.1 |
|--------------------------|------------------|

## 12 Ecological information

### 12.1 Toxicity

#### Acute aquatic toxicity

| Component                | Fish                                      | Crustaceans                                     | Algae or other aquatic plants                |
|--------------------------|-------------------------------------------|-------------------------------------------------|----------------------------------------------|
| <b>Ethylbenzene</b>      | LC <sub>50</sub> : 4.2mg/L (96h)(Fish)    | EC <sub>50</sub> : 4.75mg/L (48h)(Crustaceans)  | ErC <sub>50</sub> : 3.6mg/L (96h)(Algae)     |
| <b>o-xylene</b>          | LC <sub>50</sub> : 16.1mg/L (96h)(Fish)   | EC <sub>50</sub> : 1.1mg/L (48h)(Crustaceans)   | ErC <sub>50</sub> : 0.80mg/L (72h)(Algae)    |
| <b>Benzene</b>           | LC <sub>50</sub> : 21.6mg/L (96h)(Fish)   | EC <sub>50</sub> : 10.9mg/L (48h)(Crustaceans)  | ErC <sub>50</sub> : 1600mg/L (96h)(Algae)    |
| <b>Styrene</b>           | LC <sub>50</sub> : 4.02mg/L (96h)(Fish)   | EC <sub>50</sub> : 4.7mg/L (48h)(Crustaceans)   | ErC <sub>50</sub> : 0.72mg/L (96h)(Algae)    |
| <b>p-xylene</b>          | LC <sub>50</sub> : 5.5mg/L (96h)(Fish)    | EC <sub>50</sub> : 6.9mg/L (48h)(Crustaceans)   | ErC <sub>50</sub> : 9.6mg/L (72h)(Algae)     |
| <b>Toluene</b>           | LC <sub>50</sub> : 25mg/L (96h)(Fish)     | EC <sub>50</sub> : 4.1mg/L (48h)(Crustaceans)   | ErC <sub>50</sub> : 29mg/L (72h)(Algae)      |
| <b>N-butyl acetate</b>   | LC <sub>50</sub> : 18mg/L (96h)(Fish)     | No information available                        | No information available                     |
| <b>Undecane</b>          | LC <sub>50</sub> : >0.013mg/L (96h)(Fish) | EC <sub>50</sub> : 0.011mg/L (48h)(Crustaceans) | ErC <sub>50</sub> : >0.0059mg/L (72h)(Algae) |
| <b>N-hexane</b>          | LC <sub>50</sub> : 57.8mg/L (96h)(Fish)   | No information available                        | No information available                     |
| <b>Carbon disulphide</b> | LC <sub>50</sub> : 3mg/L (96h)(Fish)      | No information available                        | ErC <sub>50</sub> : 21mg/L (96h)(Algae)      |

#### Chronic aquatic toxicity

| Component       | Fish                     | Crustaceans                    | Algae or other aquatic plants |
|-----------------|--------------------------|--------------------------------|-------------------------------|
| <b>o-xylene</b> | No information available | NOEC : 0.63mg/L(Crustaceans)   | NOEC : 0.73mg/L(Algae)        |
| <b>p-xylene</b> | No information available | NOEC : 1.3mg/L(Crustaceans)    | NOEC : 4.4mg/L(Algae)         |
| <b>Toluene</b>  | No information available | NOEC : 1.2mg/L(Crustaceans)    | NOEC : 9.1mg/L(Algae)         |
| <b>Undecane</b> | No information available | NOEC : 0.0057mg/L(Crustaceans) | NOEC : 0.0059mg/L(Algae)      |

### 12.2 Persistence and degradability

| Component | Persistence (water/soil) | Persistence (air) |
|-----------|--------------------------|-------------------|
|-----------|--------------------------|-------------------|



|                   |                            |                            |
|-------------------|----------------------------|----------------------------|
| <b>o-xylene</b>   | High(Half-life = 360 days) | Low(Half-life = 1.83 days) |
| <b>p-xylene</b>   | High(Half-life = 360 days) | Low(Half-life = 1.75 days) |
| <b>Hexadecane</b> | Low                        | Low                        |
| <b>N-hexane</b>   | Low                        | Low                        |

### 12.3 Bioaccumulative potential

| Component         | Bioaccumulative potential | Comments      |
|-------------------|---------------------------|---------------|
| <b>o-xylene</b>   | Low                       | BCF=219       |
| <b>p-xylene</b>   | Low                       | BCF=2.2       |
| <b>Hexadecane</b> | Low                       | Log Kow=8.199 |
| <b>N-hexane</b>   | Medium                    | Log Kow=3.9   |

### 12.4 Mobility in soil

| Component                | log Koc           | Remark         |
|--------------------------|-------------------|----------------|
| <b>Carbon disulphide</b> | 1.53              | 20 °C          |
| <b>Benzene</b>           | 2.13              | 20 °C          |
| <b>Toluene</b>           | 2.31              | 20 °C          |
| <b>Ethylbenzene</b>      | 3.12              | 20 °C          |
| <b>o-xylene</b>          | 2.73              | 20 °C          |
| <b>p-xylene</b>          | 2.73              | 20 °C          |
| <b>Styrene</b>           | 2.55              |                |
| <b>Undecane</b>          | ≥4.35 - ≤5.15     | 20 °C , pH=7.0 |
| <b>Hexadecane</b>        | ≥6.3779 - ≤7.5362 | 20 °C , pH=7   |
| <b>N-hexane</b>          | ≥2.37 - ≤3.16     | 20 °C , pH=7.0 |

### 12.5 Results of PBT and vPvB assessment

| Component                | Results of PBT and vPvB assessment [according to (EC) No 1907/2006] |
|--------------------------|---------------------------------------------------------------------|
| <b>Carbon disulphide</b> | Not PBT/vPvB                                                        |
| <b>Benzene</b>           | Not PBT/vPvB                                                        |
| <b>Toluene</b>           | Not PBT/vPvB                                                        |
| <b>Ethylbenzene</b>      | Not PBT/vPvB                                                        |
| <b>o-xylene</b>          | Not PBT/vPvB                                                        |
| <b>p-xylene</b>          | Not PBT/vPvB                                                        |
| <b>Styrene</b>           | Not PBT/vPvB                                                        |
| <b>N-butyl acetate</b>   | Not PBT/vPvB                                                        |
| <b>Undecane</b>          | Not PBT/vPvB                                                        |
| <b>Hexadecane</b>        | Not PBT/vPvB                                                        |
| <b>N-hexane</b>          | Not PBT/vPvB                                                        |

## 12.6 Endocrine disrupting properties

| Component         | Endocrine disrupting properties |
|-------------------|---------------------------------|
| Carbon disulphide | No information available        |
| Benzene           | No information available        |
| Toluene           | No information available        |
| Ethylbenzene      | No information available        |
| o-xylene          | No information available        |
| p-xylene          | No information available        |
| Styrene           | No information available        |
| N-butyl acetate   | No information available        |
| Undecane          | No information available        |
| Hexadecane        | No information available        |
| N-hexane          | No information available        |

## 12.7 Other adverse effects

|  |                          |
|--|--------------------------|
|  | No information available |
|--|--------------------------|

## 13 Disposal considerations

### 13.1 Waste treatment methods

|                          |                                                                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste chemicals          | Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.                       |
| Contaminated packaging   | Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible. |
| Disposal recommendations | Refer to section waste chemicals and contaminated packaging.                                                                                           |

## 14 Transport information

### Label and Mark

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Transporting Label |  |
|--------------------|-------------------------------------------------------------------------------------|

### IMDG-CODE

|                                        |                          |
|----------------------------------------|--------------------------|
| 14.1 UN number                         | 1993                     |
| 14.2 UN proper shipping name           | FLAMMABLE LIQUID, N.O.S. |
| 14.3 Transport hazard class            | 3                        |
| 14.4 Packing group                     | II                       |
| 14.5 Environmental hazards (Yes or no) | No                       |

### IATA-DGR

|                              |                          |
|------------------------------|--------------------------|
| 14.1 UN number               | 1993                     |
| 14.2 UN proper shipping name | FLAMMABLE LIQUID, N.O.S. |

|                                           |    |
|-------------------------------------------|----|
| 14.3 Transport hazard class               | 3  |
| 14.4 Packing group                        | II |
| 14.5 Environmental hazards<br>(Yes or no) | No |

## UN-ADR

|                                           |                          |
|-------------------------------------------|--------------------------|
| 14.1 UN number                            | 1993                     |
| 14.2 UN proper shipping name              | FLAMMABLE LIQUID, N.O.S. |
| 14.3 Transport hazard class               | 3                        |
| 14.4 Packing group                        | II                       |
| 14.5 Environmental hazards<br>(Yes or no) | No                       |

## Special precautions for user

|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.</p> |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Maritime transport in bulk according to IMO instruments

### ◆ Transport in bulk according to Annex II of MARPOL and the IBC code

|  |               |
|--|---------------|
|  | Not Available |
|--|---------------|

### ◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

|  |               |
|--|---------------|
|  | Not Available |
|--|---------------|

### ◆ Transport in bulk in accordance with the IGC Code

|  |               |
|--|---------------|
|  | Not Available |
|--|---------------|

## 15 Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International chemical inventory

| Component         | A | B | C | D | E | F | G | H | I | J | K | L | M |
|-------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Carbon disulphide | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ |
| Benzene           | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ |
| Toluene           | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ |
| Ethylbenzene      | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ |
| o-xylene          | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ |
| p-xylene          | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ | √ |

|                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
|------------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| <b>Styrene</b>         | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| <b>N-butyl acetate</b> | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| <b>Undecane</b>        | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| <b>Hexadecane</b>      | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | × | × | ✓ | ✓ |
| <b>N-hexane</b>        | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

- 【A】 China Inventory of Existing Chemical Substances(IECSC)  
 【B】 European Inventory of Existing Commercial Chemical Substances(EC inventory)  
 【C】 United States Toxic Substances Control Act Inventory(TSCA)  
 【D】 Canadian Domestic Substances List(DSL)  
 【E】 New Zealand Inventory of Chemicals(NZIoC)  
 【F】 Philippines Inventory of Chemicals and Chemical Substances(PICCS)  
 【G】 Korea Existing Chemicals Inventory(KECL)  
 【H】 Australian Inventory of Industrial Chemical (AIICS)  
 【I】 Japan Inventory of Existing & New Chemical Substances(ENCS)  
 【J】 Thailand Existing Chemicals Inventory(TECI)  
 【K】 Mexico National Inventory of Chemical Substances (INSQ)  
 【L】 Russia Inventory of Existing Substances (DRAFT)  
 【M】 Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

### List of Chemical Substances under International Conventions

| Component                | A | B | C |
|--------------------------|---|---|---|
| <b>Carbon disulphide</b> | × | × | × |
| <b>Benzene</b>           | × | × | × |
| <b>Toluene</b>           | × | × | × |
| <b>Ethylbenzene</b>      | × | × | × |
| <b>o-xylene</b>          | × | × | × |
| <b>p-xylene</b>          | × | × | × |
| <b>Styrene</b>           | × | × | × |
| <b>N-butyl acetate</b>   | × | × | × |
| <b>Undecane</b>          | × | × | × |
| <b>Hexadecane</b>        | × | × | × |
| <b>N-hexane</b>          | × | × | × |

- 【A】 The Montreal Protocol on Substances that Deplete the Ozone Layer  
 【B】 Stockholm Convention on Persistent Organic Pollutants (POPs)  
 【C】 Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

### European chemical inventory

| Component                | A | B | C | D | E | F | G | H | I |
|--------------------------|---|---|---|---|---|---|---|---|---|
| <b>Carbon disulphide</b> | × | × | × | ✓ | ✓ | ✓ | × | × | × |
| <b>Benzene</b>           | × | × | ✓ | ✓ | ✓ | × | ✓ | × | × |
| <b>Toluene</b>           | × | × | ✓ | ✓ | ✓ | ✓ | × | × | × |
| <b>Ethylbenzene</b>      | × | × | × | ✓ | ✓ | × | × | × | × |
| <b>o-xylene</b>          | × | × | × | ✓ | ✓ | ✓ | × | × | × |

|                        |   |   |   |   |   |   |   |   |   |
|------------------------|---|---|---|---|---|---|---|---|---|
| <b>p-xylene</b>        | × | × | × | ✓ | ✓ | ✓ | × | × | × |
| <b>Styrene</b>         | × | × | × | ✓ | ✓ | × | × | × | × |
| <b>N-butyl acetate</b> | × | × | × | ✓ | ✓ | × | × | × | × |
| <b>Undecane</b>        | × | × | × | ✓ | ✓ | × | × | × | × |
| <b>Hexadecane</b>      | × | × | × | ✓ | ✓ | × | × | × | × |
| <b>N-hexane</b>        | × | × | × | ✓ | ✓ | ✓ | × | × | × |

[A] Candidate list of Substances of Very High Concern for authorization under EU REACH regulation

[B] Substances requiring authorisation under EU REACH regulation

[C] Substances restricted under EU REACH

[D] Pre-registered substances under EU REACH

[E] Registered substances under EU REACH

[F] Substance Evaluation – CoRAP under EU REACH

[G] List of priority substances under EU water policy ( Directive 2455/2001/EC )

[H] Substances subject to POPs Regulation

[I] Substances proposed as POPs

Note:

“✓” Indicates that the substance included in the regulations.

“×” No data or not included in the regulations.

### German water hazard class(WGK)

| Component                | WGK   | Remark |
|--------------------------|-------|--------|
| <b>Carbon disulphide</b> | WGK 2 |        |
| <b>Benzene</b>           | WGK 3 |        |
| <b>Toluene</b>           | WGK 3 |        |
| <b>Ethylbenzene</b>      | WGK 1 |        |
| <b>o-xylene</b>          | WGK 2 |        |
| <b>p-xylene</b>          | WGK 2 |        |
| <b>Styrene</b>           | WGK 2 |        |
| <b>N-butyl acetate</b>   | WGK 1 |        |
| <b>Hexadecane</b>        | WGK 1 |        |
| <b>N-hexane</b>          | WGK 3 |        |

【WGK 1】 slightly hazardous to water

【WGK 2】 obviously hazardous to water

【WGK 3】 highly hazardous to water

【nwg】 non-hazardous to water

【awg】 hazardous to water in general

### German technical instructions on air quality control(TA LUFT)

| Component      | TA LUFT                                                                                                                                                                                                              | Remark |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>Benzene</b> | Chapter 5.2.7.1.1 Carcinogenic substances. Class II. As minimum requirement, the following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 1,5 g/hr or Mass conc.: 0,5 mg/m <sup>3</sup> |        |
| <b>Toluene</b> | Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the                                                                                                         |        |

|                        |                                                                                                                                                                                                                                                                                                                                                   |  |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|                        | exhaust gas:Mass flow:0,10 kg/hr or<br>Mass conc.:20 mg/m <sup>3</sup>                                                                                                                                                                                                                                                                            |  |
| <b>Ethylbenzene</b>    | Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h. |  |
| <b>o-xylene</b>        | Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h. |  |
| <b>p-xylene</b>        | Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h. |  |
| <b>Styrene</b>         | Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas:Mass flow:0,10 kg/hr or Mass conc.:20 mg/m <sup>3</sup>                                                                                                                                                                  |  |
| <b>N-butyl acetate</b> | Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h. |  |
| <b>Undecane</b>        | Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h. |  |
| <b>Hexadecane</b>      | Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or                                                                                                                                                                                  |  |

|                 |                                                                                                                                                                                  |  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|                 | Mass conc.:50 mg/m <sup>3</sup> At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h. |  |
| <b>N-hexane</b> | Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas:Mass flow:0,10 kg/hr or Mass conc.:20 mg/m <sup>3</sup> |  |

### **German technical rules for hazardous substances(TRGS)**

| <b>Component</b>         | <b>TRGS</b>                                                                                                                                     | <b>Remark</b> |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <b>Carbon disulphide</b> | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 TRGS 523 |               |
| <b>Benzene</b>           | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 410 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 |               |
| <b>Toluene</b>           | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724          |               |
| <b>Ethylbenzene</b>      | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724          |               |
| <b>o-xylene</b>          | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724          |               |
| <b>p-xylene</b>          | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724          |               |
| <b>Styrene</b>           | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724          |               |
| <b>N-butyl acetate</b>   | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724          |               |

|                   |                                                                                                                                        |  |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------|--|
| <b>Undecane</b>   | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800                                                       |  |
| <b>Hexadecane</b> | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800                                                       |  |
| <b>N-hexane</b>   | TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 |  |

## 15.2 Chemical safety assessment

|  |                                                                                                |
|--|------------------------------------------------------------------------------------------------|
|  | No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier. |
|--|------------------------------------------------------------------------------------------------|

## 16 Other information

### Information on revision

|                            |            |
|----------------------------|------------|
| <b>Creation Date</b>       | 2025/12/30 |
| <b>Revision Date</b>       | -          |
| <b>Reason for revision</b> | -          |

### Reference

- [1] IPCS: The International Chemical SafetyCards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

### Abbreviations and acronyms

|                  |                                      |           |                                                           |
|------------------|--------------------------------------|-----------|-----------------------------------------------------------|
| CAS              | Chemical Abstracts Service           | UN        | The United Nations                                        |
| PC-STEL          | Short term exposure limit            | OECD      | Organization for Economic Co-operation and Development    |
| PC-TWA           | Time Weighted Average                | IMDG-CODE | International Maritime Dangerous Goods CODE               |
| MAC              | Maximum Allowable Concentration      | IARC      | International Agency for Research on Cancer               |
| DNEL             | Derived No Effect Level              | ICAO      | International Civil Aviation Organization                 |
| PNEC             | Predicted No Effect Concentration    | IATA      | International Air Transportation Association              |
| NOEC             | No Observed Effect Concentration     | ACGIH     | American Conference of Governmental Industrial Hygienists |
| LC <sub>50</sub> | Lethal Concentration 50%             | NFPA      | National Fire Protection Association                      |
| LD <sub>50</sub> | Lethal Dose 50%                      | NTP       | National Toxicology Program                               |
| EC <sub>50</sub> | Effective Concentration 50%          | PBT       | Persistent, Bioaccumulative, Toxic                        |
| EC <sub>x</sub>  | Effective Concentration X%           | vPvB      | very Persistent, very Bioaccumulative                     |
| P <sub>ow</sub>  | Partition coefficient Octanol: Water | CMR       | Carcinogens, mutagens or substances toxic to reproduction |
| BCF              | Bioconcentration factor              | RPE       | Respiratory Protective Equipment                          |
| ED               | Endocrine disruptor                  |           |                                                           |

### Disclaimer

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of



---

information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.