

Safety Data Sheet

16 Mix aldehyde/ketone DNPHs in acetonitrile

Version : V2.0.0.1

Report No. : BWQ8733-2016-MSDS-EP

Creation Date : 2025/12/20

Revision Date : -



***Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)**

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name	16 Mix aldehyde/ketone DNPHs in acetonitrile
Cat No.	BWQ8733-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable
REACH Registration Number	-
UFI	No information available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

1.4 Emergency telephone number

Emergency telephone number	010-58103678
Opening hours	24h

2 Hazards identification

2.1 CLP classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Acute Toxicity - Dermal	Category 4
Serious eye damage/irritation	Category 2
Acute Toxicity - Inhalation	Category 3

2.2 Label elements

Hazard pictograms	 
Signal word	Danger

Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H319	Causes serious eye irritation
H331	Toxic if inhaled
EUH208	Contains sensitising substance. May produce an allergic reaction

Precautionary statements

◆ Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

◆ Response

P311	Call a POISON CENTER/ doctor.
P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P301+P312	IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

		lenses, if present and easy to do. Continue rinsing.
◆ Storage		
	P405	Store locked up.
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.
	P403+P235	Store in a well-ventilated place. Keep cool.
◆ Disposal		
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

◆ Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Acetonitrile	Not PBT/vPvB
Formaldehyde	Not PBT/vPvB
Acetaldehyde	Not PBT/vPvB
Acrylaldehyde	Not PBT/vPvB
Acetone	Not PBT/vPvB
Propionaldehyde	Insufficient information, temporarily unable to evaluate
(E)-crotonaldehyde	Insufficient information, temporarily unable to evaluate
Butyraldehyde	Not applicable
Butanone	Not PBT/vPvB
Benzaldehyde	Not PBT/vPvB
Isovaleraldehyde	Insufficient information, temporarily unable to evaluate
Valeraldehyde	Insufficient information, temporarily unable to evaluate
2-tolualdehyde	Insufficient information, temporarily unable to evaluate
m-tolualdehyde	Insufficient information, temporarily unable to evaluate
p-tolualdehyde	Insufficient information, temporarily unable to evaluate
Hexanal	Not PBT/vPvB
2,5-dimethylbenzaldehyde	Insufficient information, temporarily unable to evaluate

◆ Results of endocrine disrupting properties assessment

Component	Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605]
Acetonitrile	Insufficient information, temporarily unable to evaluate
Formaldehyde	Insufficient information, temporarily unable to evaluate
Acetaldehyde	Insufficient information, temporarily unable to evaluate
Acrylaldehyde	Insufficient information, temporarily unable to evaluate
Acetone	Insufficient information, temporarily unable to evaluate
Propionaldehyde	Insufficient information, temporarily unable to evaluate

(E)-crotonaldehyde	Insufficient information, temporarily unable to evaluate
Butyraldehyde	Insufficient information, temporarily unable to evaluate
Butanone	Insufficient information, temporarily unable to evaluate
Benzaldehyde	Insufficient information, temporarily unable to evaluate
Isovaleraldehyde	Insufficient information, temporarily unable to evaluate
Valeraldehyde	Insufficient information, temporarily unable to evaluate
2-tolualdehyde	Insufficient information, temporarily unable to evaluate
m-tolualdehyde	Insufficient information, temporarily unable to evaluate
p-tolualdehyde	Insufficient information, temporarily unable to evaluate
Hexanal	Insufficient information, temporarily unable to evaluate
2,5-dimethylbenzaldehyde	Insufficient information, temporarily unable to evaluate

◆ Other

Not applicable.

3 Composition/information on ingredients

3.1 Substance

Not applicable

3.2 Mixture

Component	Weight % content(or range)	Classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707 [CLP]	Specific Conc. Limits, M-factors
Acetonitrile CAS : 75-05-8 EC : 200-835-2 Index No. : 608-001-00-3	99.237	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 4, H302; Acute Toxicity - Dermal, Category 4, H312; Serious eye damage/irritation, Category 2, H319; Acute Toxicity - Inhalation, Category 4, H332	-
Formaldehyde CAS : 50-00-0 EC : 200-001-8 Index No. : 605-001-00-5	0.090	Acute Toxicity - Oral, Category 4, H302; Skin corrosion/irritation, Category 1B, H314; Sensitization - skin, Category 1A, H317; Acute Toxicity - Inhalation, Category 2, H330; Germ cell mutagenicity, Category 2, H341; Carcinogenicity, Category 1B, H350; Corrosive to the respiratory tract, EUH071	H335:C≥5% H314B:C≥25% H315:5%≤C < 25% H319:5%≤C < 25%;H3302:ATE = 100 ppmV (gases) H302:ATE = 500 mg/kg bw
Acetaldehyde CAS : 75-07-0 EC : 200-836-8 Index No. : 605-003-00-6	0.065	Flammable liquids, Category 1, H224; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Germ cell mutagenicity, Category 2, H341; Carcinogenicity, Category 1B, H350	-
Acrylaldehyde CAS : 107-02-8 EC : 203-453-4 Index No. : 605-008-00-3	0.054	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 2, H300; Acute Toxicity - Dermal, Category 3, H311; Skin corrosion/irritation, Category 1B, H314; Acute Toxicity - Inhalation, Category 1, H330; Hazardous to the aquatic environment - short-term (acute) hazard,	H314B:C ≥ 0.1%;M=100;M(Chronic)= 1

		Category 1, H400; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 1, H410; Corrosive to the respiratory tract, EUH071	
Acetone CAS : 67-64-1 EC : 200-662-2 Index No. : 606-001-00-8	0.053	Flammable liquids, Category 2, H225; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Repeated exposure may cause skin dryness or cracking, EUH066	-
Propionaldehyde CAS : 123-38-6 EC : 204-623-0 Index No. : 605-018-00-8	0.053	Flammable liquids, Category 2, H225; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	-
(E)-crotonaldehyde CAS : 123-73-9 EC : 204-647-1 Index No. : 605-009-00-9	0.046	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 3, H301; Acute Toxicity - Dermal, Category 3, H311; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 1, H318; Acute Toxicity - Inhalation, Category 2, H330; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Germ cell mutagenicity, Category 2, H341; Specific target organ toxicity - repeated exposure, Category 2, H373; Hazardous to the aquatic environment - short-term (acute) hazard, Category 1, H400	-
Butyraldehyde CAS : 123-72-8 EC : 204-646-6 Index No. : 605-006-00-2	0.046	Flammable liquids, Category 2, H225	-
Butanone CAS : 78-93-3 EC : 201-159-0 Index No. : 606-002-00-3	0.046	Flammable liquids, Category 2, H225; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Repeated exposure may cause skin dryness or cracking, EUH066	-
Benzaldehyde CAS : 100-52-7 EC : 202-860-4 Index No. : 605-012-00-5	0.035	Acute Toxicity - Oral, Category 4, H302	-
Isovaleraldehyde CAS : 590-86-3 EC : 209-691-5 Index No. : -	0.04	Flammable liquids, Category 2, H225; Sensitization - skin, Category 1B, H317; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 2, H411	-
Valeraldehyde CAS : 110-62-3 EC : 203-784-4 Index No. : -	0.041	Flammable liquids, Category 2, H225; Sensitization - skin, Category 1, H317; Serious eye damage/irritation, Category 2, H319; Acute Toxicity - Inhalation, Category 4, H332; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	-

2-tolualdehyde CAS : 529-20-4 EC : 208-452-2 Index No. : -	0.032	Acute Toxicity - Oral, Category 4, H302; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 1, H318; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	-
m-tolualdehyde CAS : 620-23-5 EC : 210-632-0 Index No. : -	0.032	Serious eye damage/irritation, Category 2, H319	-
p-tolualdehyde CAS : 104-87-0 EC : 203-246-9 Index No. : -	0.032	Acute Toxicity - Oral, Category 4, H302	-
Hexanal CAS : 66-25-1 EC : 200-624-5 Index No. : -	0.036	Flammable liquids, Category 3, H226; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319	-
2,5-dimethylbenzaldehyd e CAS : 5779-94-2 EC : 227-303-2 Index No. : -	0.03	Not Classified	-

4 First-aid measures

4.1 Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse skin with plenty of water or shower. Refer for medical attention.
Ingestion	Rinse mouth. Induce vomiting (ONLY IN CONSCIOUS PERSONS!). Give plenty of water to drink. Refer for medical attention.
Inhalation	Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

4.2 Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

4.3 Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
-------------------------------------	--

Unsuitable extinguishing media	Use of water spray when fighting fire may be inefficient.
---------------------------------------	---

5.2 Specific hazards arising from the substance or mixture

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
4	Liquid and vapour are flammable.
5	May emit poisonous fumes on fire.
6	Development of hazardous combustion gases or vapor possible in the event of fire.
7	May expansion or decompose explosively when heated or involved in fire.

5.3 Advice for firefighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

1	Avoid breathing vapours and contacting with skin and eye.
2	Beware of vapours accumulating to form explosive concentrations.
3	Vapours can accumulate in low areas.
4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
6	Do not touch or walk through spilled material.
7	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
8	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
9	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
10	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

1	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
2	In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
3	In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.

6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Do not touch or cross spills.
9	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-virus suits.
10	Spray water disperses the vapor and dilutes the liquid spill.
11	Do not touch broken containers and spills before putting on appropriate protective clothing.
12	Cut off the source of the leak as much as possible.
13	Keep leaks in a ventilated place.
14	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
15	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
16	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
17	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4 Reference to other sections

1	Personal Protective Equipment advice is contained in Section 8 of the SDS.
2	Disposal considerations advice is contained in Section 13 of the SDS.

7 Handling and storage

7.1 Precautions for safe handling

◆ Protective measures

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.

◆ Measures to prevent fire

1	Use only non-sparking tools.
2	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
3	Use explosion proof equipment.
4	Keep away from heat/sparks/open flames/ hot surfaces.

◆ Measures to prevent aerosol and dust generation

1	Not applicable.
---	-----------------

◆ Advice on general occupational hygiene

1	Wash hands and face after using the substances.
2	Replace the contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

7.3 Specific end use(s)

1 | In addition to use mentioned in the Section 1.2, unforeseen other specific end uses.

8 Exposure controls/personal protection

8.1 Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m ³	ppm	mg/m ³
Acetonitrile	Permissible exposure standards for workers in the workplace	40	67	60	100.5
	European Union	40	70	-	-
	France	40	70	-	-
	Germany (AGS)	10	17	20	34
	Germany (DFG)	10	17	20	34
	Italy	20	35	-	-
Formaldehyde	Japan - JSOH(2024-2025)	0.1	0.12	-	-
	Permissible exposure standards for workers in the workplace	0.75	0.9	2.25	2.7
	European Union	0.3	0.37	0.6	0.74
	France	0.3	0.37	0.6	0.74
	Germany (AGS)	0.3	0.37	0.6	0.74
	Germany (DFG)	0.3	0.37	0.6	0.74
	Japan - JSOH(2024-2025)	-	-	-	-
Acetaldehyde	Permissible exposure standards for workers in the workplace	100	180	125	225
	France	100	180	-	-
	Germany (AGS)	50	91	50	91
	Germany (DFG)	50	91	50	91
	United Kingdom	20	37	50	92
	Japan - JSOH(2024-2025)	0.1	0.23	-	-
	Permissible exposure standards for workers in the workplace	0.1	0.23	0.3	0.69
Acrylaldehyde	Japan - JSOH(2024-2025)	0.1	0.23	-	-
	Permissible exposure standards for workers in the workplace	0.1	0.23	0.3	0.69

	workplace				
	European Union	0.02	0.05	0.05	0.12
	France	0.02	0.05	0.05	0.12
	Germany (AGS)	0.09	0.2	0.18	0.4
	Italy	0.02	0.05	0.05	0.12
Acetone	Japan - JSOH(2024–2025)	200	475	-	-
	Permissible exposure standards for workers in the workplace	200	475	250	593.75
	European Union	500	1210	-	-
	France	500	1210	1000	2420
	Germany (AGS)	500	1200	1000	2400
	Germany (DFG)	500	1200	1000	2400
	Propionaldehyde	Belgium	20	48	-
Finland		20	48	-	-
Ireland		20	-	-	-
Latvia		-	5	-	-
Canada - Ontario		20	-	-	-
Canada - Québec		20	-	-	-
(E)-crotonaldehyde	France	2	6	-	-
	Austria	0.34	1	1.36	4
	Denmark	2	6	4	12
	Finland	0.1	0.29	0.3	0.87
	Ireland	2	6	6	18
	Norway	2	6	-	-
Butyraldehyde	Germany (AGS)	20	64	20	64
	Austria	20	64	20	64
	Finland	25	74	-	-
	Latvia	-	5	-	-
	Romania	-	-	9	25
Butanone	Japan - JSOH(2024–2025)	75	221	-	-
	Permissible exposure standards for workers in the workplace	200	590	250	737.5
	European Union	200	600	300	900

	France	200	600	300	900
	Germany (AGS)	200	600	200	600
	Germany (DFG)	200	600	200	600
Benzaldehyde	Finland	1	4.4	4	17.4
	Hungary	-	3.25	-	-
	Latvia	-	5	-	-
	Poland	-	10	-	40
	Canada - Ontario	-	-	4	17
Isovaleraldehyde	Germany (AGS)	10	39	10	39
	Austria	10	39	10	39
Valeraldehyde	Permissible exposure standards for workers in the workplace	50	176	75	220
	France	50	175	-	-
	Austria	50	175	100	350
	Belgium	50	179	-	-
	Denmark	50	175	100	350
	Finland	30	110	-	-
Hexanal	Finland	-	-	10	42
	Poland	-	40	-	80

◆ Biological limit values

Component	Standard	Biological monitoring index	Biological limits value	Sampling time	Remark
Acetone	USA -ACGIH	Acetone(Urine)	25mg/L	End of shift	
Butanone	USA -ACGIH	MEK(Urine)	2mg/L	End of shift	

◆ Monitoring methods

1	EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
2	GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.

◆ Derived No effect level (DNEL)

Component	Route of exposure	DNEL for Workers			
		Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Acetonitrile	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Formaldehyde	Inhalation	No data available	No data available	0.375 mg/m ³	9 mg/m ³
	Oral	No data available	No data available	No data available	No data available

	Dermal	No data available	No data available	No data available	No data available
Acetaldehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Acrylaldehyde	Inhalation	No data available	No data available	0.2 mg/m ³	0.2 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Acetone	Inhalation	No data available	No data available	No data available	1210 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Propionaldehyde	Inhalation	No data available	No data available	12.1 mg/m ³	6.1 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
(E)-crotonaldehyd e	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Butyraldehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Butanone	Inhalation	No data available	No data available	No data available	600 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Benzaldehyde	Inhalation	No data available	No data available	9.8 mg/m ³	9.8 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Isovaleraldehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Valeraldehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2-tolualdehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
m-tolualdehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

p-tolualdehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Hexanal	Inhalation	No data available	No data available	No data available	16.46 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2,5-dimethylbenzaldehyde	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

◆ Predicted No Effect Concentration (PNEC)

Component	A	B	C	D	E	F	G	H
Acetonitrile	10 mg/L	1 mg/L	32 mg/L	40.5 mg/kg sediment dw	4.05 mg/kg sediment dw	No hazard identified	2.23 mg/kg soil dw	No potential for bioaccumulation
Formaldehyde	No hazard identified	No hazard identified	No data available	No data available	No data available	No hazard identified	No data available	No potential for bioaccumulation
Acrylaldehyde	100 ng/L	100 ng/L	2 µg/L	No data available	No data available	No data available	10 ng/kg soil dw	No data available
Acetone	10.6 mg/L	1.06 mg/L	100 mg/L	30.4 mg/kg sediment dw	3.04 mg/kg sediment dw	No hazard identified	29.5 mg/kg soil dw	No potential for bioaccumulation
Propionaldehyde	14 µg/L	1.4 µg/L	12.4 mg/L	30.7 µg/kg sediment dw	3.07 µg/kg sediment dw	No hazard identified	2.63 µg/kg soil dw	No potential for bioaccumulation
Butyraldehyde	17.8 mg/L	1.78 mg/L	100 mg/L	73 µg/kg sediment dw	7.3 µg/kg sediment dw	No data available	4.15 µg/kg soil dw	No potential for bioaccumulation
Butanone	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Benzaldehyde	410 ng/L	41 ng/L	7.59 mg/L	4 µg/kg sediment dw	400 ng/kg sediment dw	No hazard identified	500 ng/kg soil dw	No potential for bioaccumulation
Hexanal	71.6 µg/L	7.16 µg/L	6.7 mg/L	490 µg/kg sediment dw	49 µg/kg sediment dw	No hazard identified	55.8 µg/kg soil dw	No potential for bioaccumulation

Note 1:

A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).

Note 2:

The PNEC values of the remaining components not shown in the product are not available yet.

8.2 Exposure controls

8.2.1 Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

8.2.2 Personal protection equipment

General requirement	
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear anti static chemical protective gloves.
Respiratory protection	Must wear appropriate personal dust proof gas mask.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

8.2.3 Environmental exposure controls

Environmental exposure controls	No information available
---------------------------------	--------------------------

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	clear or yellow liquid
Colour	clear or yellow liquid
Odor	No information available
Odor threshold	No information available
pH	No information available
Melting point/freezing point(°C)	-46 (Acetonitrile)
Initial boiling point and boiling range(°C)	82 (Acetonitrile)
Flash point(Closed cup, °C)	2 (Acetonitrile)
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit : 17 (Acetonitrile); Lower limit : 3 (Acetonitrile)
Vapor pressure	9.9kPa (25°C,Acetonitrile)

Vapor density(Air = 1)	1.4 (Acetonitrile)
Relative density(Water=1)	0.8 (Acetonitrile)
Solubility	1000000mg/L (25 °C,Acetonitrile)
n-octanol/water partition coefficient	-0.3 (Acetonitrile)
Auto-ignition temperature(°C)	524 (Acetonitrile)
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Particle characteristics	Not applicable

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Information with regard to physical hazard classes	No information available
--	--------------------------

9.2.2 Other safety characteristics

Other safety characteristics	No information available
------------------------------	--------------------------

10 Stability and reactivity

Stability and reactivity

10.1 Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
10.2 Chemical stability	Stable under proper operation and storage conditions.
10.3 Possibility of hazardous reactions	In contact with N-halogen compounds may cause a potensive explosive hazardous. In contact with oxidants may cause a fire. In contact with oxidants may cause a fire or an explosion.
10.4 Conditions to avoid	Incompatible materials, heat, flame and spark.
10.5 Incompatible materials	N - halogenated compounds, sulfuric acid and strong oxidants. Oxidants, acids and alkalis. Oxidants, chloroform and bromoform
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

16 Mix aldehyde/ketone DNPHs in acetonitrile	
Skin corrosion/irritation	Based on available data, the classification criteria are not met
Serious eye damage/irritation	Causes serious eye irritation(Category 2)
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

Germ cell mutagenicity	Based on available data, the classification criteria are not met
-------------------------------	--

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Acetonitrile	2460mg/kg(Rat)	> 2000mg/kg(Rabbit)	4.748mg/L(Rabbit)
Hexanal	4890mg/kg(Rat)	No information available	No information available
Benzaldehyde	1300mg/kg(Rat)	No information available	No information available
Formaldehyde	100mg/kg(Rat)	292mg/kg(Rabbit)	0.454mg/L(Mouse)
Acetone	5800mg/kg(Rat)	> 15800mg/kg(Rabbit)	76mg/L(Rat)
p-tolualdehyde	1600mg/kg(Rat)	2500mg/kg(Rat)	No information available
Acrylaldehyde	29mg/kg(Rat)	200mg/kg(Rabbit)	0.018mg/L(Rat)
Isovaleraldehyde	5600mg/kg(Rat)	2530mg/kg(Rabbit)	42.7mg/L(Rat)
Butanone	2737mg/kg(Rat)	6480mg/kg(Rabbit)	32mg/L(Mouse)
Butyraldehyde	2490mg/kg(Rat)	2910mg/kg(Rabbit)	No information available
Acetaldehyde	661mg/kg(Rat)	3540mg/kg(Rabbit)	23.962mg/L(Rat)
Propionaldehyde	1410mg/kg(Rat)	2460mg/kg(Rabbit)	> 4.6mg/L(Rat)
Valeraldehyde	4580mg/kg(Rat)	4050mg/kg(Rabbit)	No information available
(E)-crotonaldehyde	240mg/kg(Mouse)	380mg/kg(Rabbit)	No information available

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP
Acetonitrile	Not Listed	Not Listed
Formaldehyde	Category 1	Category K
Acetaldehyde	Category 2B; Category 1(Remark 1)	Category R
Acrylaldehyde	Category 2A	Not Listed
Acetone	Not Listed	Not Listed
Propionaldehyde	Not Listed	Not Listed
(E)-crotonaldehyde	Not Listed	Not Listed
Butyraldehyde	Not Listed	Not Listed
Butanone	Not Listed	Not Listed
Benzaldehyde	Not Listed	Not Listed
Isovaleraldehyde	Not Listed	Not Listed
Valeraldehyde	Not Listed	Not Listed
2-tolualdehyde	Not Listed	Not Listed
m-tolualdehyde	Not Listed	Not Listed
p-tolualdehyde	Not Listed	Not Listed
Hexanal	Not Listed	Not Listed

2,5-dimethylbenzaldehyde	Not Listed	Not Listed
--------------------------	------------	------------

Remark 1: associated with consumption of alcoholic beverages

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Component	Endocrine disrupting properties
Acetonitrile	No information available
Formaldehyde	No information available
Acetaldehyde	No information available
Acrylaldehyde	No information available
Acetone	No information available
Propionaldehyde	No information available
(E)-crotonaldehyde	No information available
Butyraldehyde	No information available
Butanone	No information available
Benzaldehyde	No information available
Isovaleraldehyde	No information available
Valeraldehyde	No information available
2-tolualdehyde	No information available
m-tolualdehyde	No information available
p-tolualdehyde	No information available
Hexanal	No information available
2,5-dimethylbenzaldehyde	No information available

11.2.2 Other Information

Other Information	See Section 11.1
-------------------	------------------

12 Ecological information

12.1 Toxicity

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Butanone	LC ₅₀ : 3220mg/L (96h)(Fish)	EC ₅₀ : 5090mg/L (48h)(Crustaceans)	ErC ₅₀ : >1200mg/L (72h)(Algae)
Isovaleraldehyde	LC ₅₀ : 3.25mg/L (96h)(Fish)	No information available	No information available
Butyraldehyde	LC ₅₀ : 16mg/L (96h)(Fish)	No information available	No information available
Acetaldehyde	LC ₅₀ : 30.8mg/L (96h)(Fish)	EC ₅₀ : 30mg/L (48h)(Crustaceans)	ErC ₅₀ : 26mg/L (72h)(Algae)
Acetonitrile	LC ₅₀ : > 100mg/L	EC ₅₀ : > 1000mg/L	ErC ₅₀ : >700mg/L

	(96h)(Fish)	(48h)(Crustaceans)	(72h)(Algae)
Hexanal	LC ₅₀ : 14mg/L (96h)(Fish)	EC ₅₀ : 7.16mg/L (48h)(Crustaceans)	ErC ₅₀ : 22.6mg/L (72h)(Algae)
Propionaldehyde	LC ₅₀ : 115mg/L (96h)(Fish)	EC ₅₀ : 88.7mg/L (48h)(Crustaceans)	ErC ₅₀ : 260mg/L (72h)(Algae)
Valeraldehyde	LC ₅₀ : 12.9mg/L (96h)(Fish)	EC ₅₀ : 32mg/L (48h)(Crustaceans)	ErC ₅₀ : >9.3mg/L (72h)(Algae)
Formaldehyde	LC ₅₀ : 52.5mg/L (96h)(Fish)	EC ₅₀ : 14mg/L (48h)(Crustaceans)	No information available
Benzaldehyde	LC ₅₀ : 1.07mg/L (96h)(Fish)	No information available	ErC ₅₀ : 32mg/L (72h)(Algae)
Acetone	LC ₅₀ : 5540mg/L (96h)(Fish)	EC ₅₀ : 18500mg/L (48h)(Crustaceans)	ErC ₅₀ : 7200mg/L (96h)(Algae)
Acrylaldehyde	LC ₅₀ : 0.019mg/L (96h)(Fish)	EC ₅₀ : 0.09mg/L (48h)(Crustaceans)	No information available

Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Butanone	No information available	NOEC : 100mg/L(Crustaceans)	NOEC : 93mg/L(Algae)
Acetaldehyde	No information available	No information available	NOEC : 1.9mg/L(Algae)
Acetonitrile	NOEC : 102mg/L(Fish)	NOEC : >960mg/L(Crustaceans)	NOEC : 700mg/L(Algae)
Valeraldehyde	No information available	NOEC : 2.5mg/L(Crustaceans)	NOEC : 4.1mg/L(Algae)
Benzaldehyde	NOEC : 0.12mg/L(Fish)	No information available	NOEC : 2mg/L(Algae)

12.2 Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Formaldehyde	Low(Half-life = 14 days)	Low(Half-life = 2.97 days)
Butanone	Low(Half-life = 14 days)	Low(Half-life = 26.75 days)
Benzaldehyde	Low	Low
Isovaleraldehyde	Low	Low
2-tolualdehyde	Low	Low
m-tolualdehyde	Low	Low
p-tolualdehyde	Low	Low

12.3 Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Formaldehyde	Low	Log Kow=0.35
Butanone	Low	Log Kow=0.29
Benzaldehyde	Low	Log Kow=1.48
Isovaleraldehyde	Low	Log Kow=1.31

2-tolualdehyde	Low	Log Kow=2.26
m-tolualdehyde	Low	Log Kow=2.2575
p-tolualdehyde	Low	Log Kow=2.2575

12.4 Mobility in soil

Component	log Koc	Remark
Acetonitrile	0.653	
Formaldehyde	1.202	
Propionaldehyde	-0.007	25 °C , MCI method
Butyraldehyde	0.708	
Butanone	0.654	25 °C
Benzaldehyde	1.05	25 °C
Isovaleraldehyde	0.896	
2-tolualdehyde	1.733	
m-tolualdehyde	1.724	
p-tolualdehyde	1.724	
Hexanal	1.51	25 °C , pH=5.5

12.5 Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Acetonitrile	Not PBT/vPvB
Formaldehyde	Not PBT/vPvB
Acetaldehyde	Not PBT/vPvB
Acrylaldehyde	Not PBT/vPvB
Acetone	Not PBT/vPvB
Propionaldehyde	Insufficient information, temporarily unable to evaluate
(E)-crotonaldehyde	Insufficient information, temporarily unable to evaluate
Butyraldehyde	Not applicable
Butanone	Not PBT/vPvB
Benzaldehyde	Not PBT/vPvB
Isovaleraldehyde	Insufficient information, temporarily unable to evaluate
Valeraldehyde	Insufficient information, temporarily unable to evaluate
2-tolualdehyde	Insufficient information, temporarily unable to evaluate
m-tolualdehyde	Insufficient information, temporarily unable to evaluate
p-tolualdehyde	Insufficient information, temporarily unable to evaluate
Hexanal	Not PBT/vPvB
2,5-dimethylbenzaldehyde	Insufficient information, temporarily unable to evaluate

12.6 Endocrine disrupting properties

Component	Endocrine disrupting properties
Acetonitrile	No information available
Formaldehyde	No information available
Acetaldehyde	No information available
Acrylaldehyde	No information available
Acetone	No information available
Propionaldehyde	No information available
(E)-crotonaldehyde	No information available
Butyraldehyde	No information available
Butanone	No information available
Benzaldehyde	No information available
Isovaleraldehyde	No information available
Valeraldehyde	No information available
2-tolualdehyde	No information available
m-tolualdehyde	No information available
p-tolualdehyde	No information available
Hexanal	No information available
2,5-dimethylbenzaldehyde	No information available

12.7 Other adverse effects

No information available

13 Disposal considerations

13.1 Waste treatment methods

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label	
--------------------	---

IMDG-CODE

14.1 UN number	1992
----------------	------

14.2 UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
14.3 Transport hazard class	3+6.1
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

IATA-DGR

14.1 UN number	1992
14.2 UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
14.3 Transport hazard class	3+6.1
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

UN-ADR

14.1 UN number	1992
14.2 UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
14.3 Transport hazard class	3+6.1
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

Special precautions for user

	<p>Transit should be anti-exposure, rain, high temperature. Strictly prohibited shipping or transportation with acids, alkalis, oxidants, food and food additives etc. Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.</p>
--	---

Maritime transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code	Not Available
◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code	Not Available
◆ Transport in bulk in accordance with the IGC Code	Not Available

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International chemical inventory

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
Acetonitrile	√	√	√	√	√	√	√	√	√	√	√	√	√
Formaldehyde	√	√	√	√	√	√	√	√	√	√	√	√	√
Acetaldehyde	√	√	√	√	√	√	√	√	√	√	√	√	√
Acrylaldehyde	√	√	√	√	√	√	√	√	√	√	√	√	√
Acetone	√	√	√	√	√	√	√	√	√	√	√	√	√
Propionaldehyde	√	√	√	√	√	√	√	√	√	√	√	√	√
(E)-crotonaldehyde	√	√	√	√	√	√	√	√	√	×	√	√	√
Butyraldehyde	√	√	√	√	√	√	√	√	√	√	√	√	√
Butanone	√	√	√	√	√	√	√	√	√	√	√	√	√
Benzaldehyde	√	√	√	√	√	√	√	√	√	√	√	√	√
Isovaleraldehyde	√	√	√	√	√	√	√	√	√	×	√	√	√
Valeraldehyde	√	√	√	√	√	√	√	√	√	×	√	√	√
2-tolualdehyde	√	√	×	×	√	√	×	√	√	×	×	√	√
m-tolualdehyde	√	√	√	√	√	√	√	√	√	×	×	√	√
p-tolualdehyde	√	√	√	√	√	√	√	√	√	×	×	√	√
Hexanal	√	√	√	√	√	√	√	√	√	×	√	√	√
2,5-dimethylbenzaldehyde	×	√	×	×	×	×	×	√	×	×	×	×	×

- [A] China Inventory of Existing Chemical Substances(IECSC)
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
 [C] United States Toxic Substances Control Act Inventory(TSCA)
 [D] Canadian Domestic Substances List(DSL)
 [E] New Zealand Inventory of Chemicals(NZIoC)
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
 [G] Korea Existing Chemicals Inventory(KECL)
 [H] Australian. Inventory of Industrial Chemical (AIICS)
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)
 [J] Thailand Existing Chemicals Inventory(TECI)
 [K] Mexico National Inventory of Chemical Substances (INSQ)
 [L] Russia Inventory of Existing Substances(DRAFT)
 [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	B	C
Acetonitrile	×	×	×
Formaldehyde	×	×	×
Acetaldehyde	×	×	×
Acrylaldehyde	×	×	×
Acetone	×	×	×

Propionaldehyde	x	x	x
(E)-crotonaldehyde	x	x	x
Butyraldehyde	x	x	x
Butanone	x	x	x
Benzaldehyde	x	x	x
Isovaleraldehyde	x	x	x
Valeraldehyde	x	x	x
2-tolualdehyde	x	x	x
m-tolualdehyde	x	x	x
p-tolualdehyde	x	x	x
Hexanal	x	x	x
2,5-dimethylbenzaldehyde	x	x	x

[A] The Montreal Protocol on Substances that Deplete the Ozone Layer

[B] Stockholm Convention on Persistent Organic Pollutants (POPs)

[C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

European chemical inventory

Component	A	B	C	D	E	F	G	H	I
Acetonitrile	x	x	x	√	√	x	x	x	x
Formaldehyde	x	x	√	√	√	√	x	x	x
Acetaldehyde	x	x	√	√	√	x	x	x	x
Acrylaldehyde	x	x	x	√	√	x	x	x	x
Acetone	x	x	x	√	√	x	x	x	x
Propionaldehyde	x	x	x	√	√	x	x	x	x
(E)-crotonaldehyde	x	x	x	√	x	x	x	x	x
Butyraldehyde	x	x	x	√	√	x	x	x	x
Butanone	x	x	x	√	√	√	x	x	x
Benzaldehyde	x	x	x	√	√	√	x	x	x
Isovaleraldehyde	x	x	x	√	√	x	x	x	x
Valeraldehyde	x	x	x	√	√	x	x	x	x
2-tolualdehyde	x	x	x	√	x	x	x	x	x
m-tolualdehyde	x	x	x	√	x	x	x	x	x
p-tolualdehyde	x	x	x	√	√	x	x	x	x
Hexanal	x	x	x	√	√	x	x	x	x
2,5-dimethylbenzaldehyde	x	x	x	√	x	x	x	x	x

[A] Candidate list of Substances of Very High Concern for authorization under EU REACH regulation

[B] Substances requiring authorisation under EU REACH regulation

[C] Substances restricted under EU REACH

- [D] Pre-registered substances under EU REACH
 [E] Registered substances under EU REACH
 [F] Substance Evaluation – CoRAP under EU REACH
 [G] List of priority substances under EU water policy (Directive 2455/2001/EC)
 [H] Substances subject to POPs Regulation
 [I] Substances proposed as POPs

Note:

- “√” Indicates that the substance included in the regulations.
 “x” No data or not included in the regulations.

German water hazard class(WGK)

Component	WGK	Remark
Acetonitrile	WGK 2	
Formaldehyde	WGK 3	
Acetaldehyde	WGK 3	
Acrylaldehyde	WGK 3	
Acetone	WGK 1	
Propionaldehyde	WGK 1	
(E)-crotonaldehyde	WGK 3	
Butyraldehyde	WGK 1	
Butanone	WGK 1	
Benzaldehyde	WGK 3	
Isovaleraldehyde	WGK 2	
Valeraldehyde	WGK 1	
p-tolualdehyde	WGK 1	
Hexanal	WGK 1	

- [WGK 1] slightly hazardous to water
 [WGK 2] obviously hazardous to water
 [WGK 3] highly hazardous to water
 [nwg] non-hazardous to water
 [awg] hazardous to water in general

German technical instructions on air quality control(TA LUFT)

Component	TA LUFT	Remark
Formaldehyde	Chapter 5.2.7.1.1 Carcinogenic substances. Formaldehyde. As minimum requirement, the following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 12,5 g/hr or Mass conc.: 5 mg/m ³	
Acetaldehyde	Chapter 5.2.7.1.1 Carcinogenic Substances The substance must be assigned to the class (I, II or III) whose substances have the nearest potency. We can not accomplish this evaluation due to insufficiency of data. Carcinogenic substances not	

	mentioned by name and for which no information on potency is available should be assigned to Class I as a precautionary measure.	
Acrylaldehyde	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
Acetone	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Propionaldehyde	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
(E)-crotonaldehyde	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
Butyraldehyde	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Butanone	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Benzaldehyde	Chapter 5.2.7.1.3 Substances toxic to reproduction Mass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Isovaleraldehyde	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all	

	not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Valeraldehyde	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
2-tolualdehyde	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
m-tolualdehyde	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
p-tolualdehyde	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Hexanal	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	

| German technical rules for hazardous substances(TRGS)

Component	TRGS	Remark
-----------	------	--------

Acetonitrile	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Formaldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 410 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 513 TRGS 522	
Acetaldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 410 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Acrylaldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 TRGS 523	
Acetone	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Propionaldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
(E)-crotonaldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Butyraldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Butanone	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Benzaldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Isovaleraldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	

Valeraldehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
2-tolualdehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
m-tolualdehyde	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
p-tolualdehyde	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Hexanal	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	

15.2 Chemical safety assessment

	No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.
--	--

16 Other information

Information on revision

Creation Date	2025/12/20
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC _x	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P _{ow}	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment

ED Endocrine disruptor

Disclaimer

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.