

## Safety Data Sheet

# 5 Mix acrylic esters in carbon disulfide

Version : V2.0.0.1

Report No. : BWQ9139-2016-MSDS-EP

Creation Date : 2025/12/22

Revision Date : -



\*Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)

## 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product Name	5 Mix acrylic esters in carbon disulfide
Cat No.	BWQ9139-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable
REACH Registration Number	-
UFI	No information available

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

### 1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

### 1.4 Emergency telephone number

Emergency telephone number	010-58103678
Opening hours	24h

## 2 Hazards identification

### 2.1 CLP classification according to Regulation ( EC ) No. 1272/2008 with amendment 2023/707

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity -	Category 1

repeated exposure	
-------------------	--

## 2.2 Label elements

Hazard pictograms	
Signal word	<b>Danger</b>

## Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H361df	Suspected of damaging fertility and the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
EUH208	Contains sensitising substance. May produce an allergic reaction

## Precautionary statements

### ◆ Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### ◆ Response

P314	Get medical advice/ attention if you feel unwell.
P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P301+P312	IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor

	nozzles. Cool containers with flooding quantities of water until well after fire is out.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
◆ Storage	
<b>P405</b>	Store locked up.
<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.
◆ Disposal	
<b>P501</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### ◆ Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Carbon disulphide	Not PBT/vPvB
Methyl acrylate	Not PBT/vPvB
Ethyl acrylate	Not PBT/vPvB
Propyl acrylate	Insufficient information, temporarily unable to evaluate
Butyl acrylate	Not PBT/vPvB
Pentyl acrylate	Insufficient information, temporarily unable to evaluate

#### ◆ Results of endocrine disrupting properties assessment

Component	Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605]
Carbon disulphide	Insufficient information, temporarily unable to evaluate
Methyl acrylate	Insufficient information, temporarily unable to evaluate
Ethyl acrylate	Insufficient information, temporarily unable to evaluate
Propyl acrylate	Insufficient information, temporarily unable to evaluate
Butyl acrylate	Insufficient information, temporarily unable to evaluate
Pentyl acrylate	Insufficient information, temporarily unable to evaluate

#### ◆ Other

	Not applicable.
--	-----------------

## 3 Composition/information on ingredients

### 3.1 Substance

	Not applicable
--	----------------

### 3.2 Mixture

Component	Weight % content(or range)	Classification according to Regulation ( EC ) No. 1272/2008 with amendment 2023/707 [CLP]	Specific Conc. Limits, M-factors
Carbon disulphide CAS : 75-15-0	99.21	Flammable liquids, Category 2, H225; Skin Corrosion/Irritation, Category 2,	H361:C ≥ 1% H372:C ≥ 1% H373:0.2% ≤ C < 1%

EC : 200-843-6 Index No. : 006-003-00-3		H315; Serious eye damage/irritation, Category 2, H319; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 1, H372	
<b>Methyl acrylate</b> CAS : 96-33-3 EC : 202-500-6 Index No. : 607-034-00-0	0.157	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 4, H302; Acute Toxicity - Dermal, Category 4, H312; Skin Corrosion/Irritation, Category 2, H315; Sensitization - skin, Category 1, H317; Serious eye damage/irritation, Category 2, H319; Acute Toxicity - Inhalation, Category 3, H331; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	H331:ATE = 3 mg/L (vapours) H312:ATE = 1100 mg/kg bw H302:ATE = 500 mg/kg bw
<b>Ethyl acrylate</b> CAS : 140-88-5 EC : 205-438-8 Index No. : 607-032-00-X	0.157	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 4, H302; Acute Toxicity - Dermal, Category 4, H312; Skin Corrosion/Irritation, Category 2, H315; Sensitization - skin, Category 1, H317; Serious eye damage/irritation, Category 2, H319; Acute Toxicity - Inhalation, Category 3, H331; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	H315:C ≥ 5% H319:C ≥ 5% H335:C ≥ 5%;H302:ATE = 1120 mg/kg bw H312:ATE = 1800 mg/kg bw H331:ATE = 9 mg/L (vapours)
<b>Propyl acrylate</b> CAS : 925-60-0 EC : 213-120-5 Index No. : 607-133-00-9	0.157	Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 2, H411	H335:C ≥10.0%
<b>Butyl acrylate</b> CAS : 141-32-2 EC : 205-480-7 Index No. : 607-062-00-3	0.157	Flammable liquids, Category 3, H226; Skin Corrosion/Irritation, Category 2, H315; Sensitization - skin, Category 1, H317; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	-
<b>Pentyl acrylate</b> CAS : 2998-23-4 EC : 221-074-2 Index No. : 607-133-00-9	0.157	Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 2, H411	H335:C ≥10.0%

## 4 First-aid measures

### 4.1 Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
<b>Eye contact</b>	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
<b>Skin contact</b>	First rinse with plenty of water, then remove contaminated clothes and rinse again. Refer for medical attention.
<b>Ingestion</b>	Give nothing to drink. Refer for medical attention.

<b>Inhalation</b>	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
<b>Protecting of first-aiders</b>	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

#### 4.2 Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

#### 4.3 Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

### 5 Fire-fighting measures

#### 5.1 Extinguishing media

<b>Suitable extinguishing media</b>	Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
<b>Unsuitable extinguishing media</b>	Use of water spray when fighting fire may be inefficient.

#### 5.2 Specific hazards arising from the substance or mixture

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
4	Liquid and vapour are flammable.
5	Development of hazardous combustion gases or vapor possible in the event of fire.
6	May expansion or decompose explosively when heated or involved in fire.

#### 5.3 Advice for firefighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

### 6 Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

1	Avoid breathing vapours and contacting with skin and eye.
2	Beware of vapours accumulating to form explosive concentrations.
3	Vapours can accumulate in low areas.
4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
6	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
7	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

## 6.2 Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

## 6.3 Methods and materials for containment and cleaning up

1	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
2	In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
3	In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Cut off the source of the leak as much as possible.
9	Keep leaks in a ventilated place.
10	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
11	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
12	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
13	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 6.4 Reference to other sections

1	Personal Protective Equipment advice is contained in Section 8 of the SDS.
2	Disposal considerations advice is contained in Section 13 of the SDS.

# 7 Handling and storage

## 7.1 Precautions for safe handling

### ◆ Protective measures

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.

### ◆ Measures to prevent fire

1	Use only non-sparking tools.
2	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
3	Use explosion proof equipment.
4	Keep away from heat/sparks/open flames/ hot surfaces.

### ◆ Measures to prevent aerosol and dust generation

1	Not applicable.
---	-----------------

### ◆ Advice on general occupational hygiene

1	Wash hands and face after using the substances.
2	Replace the contaminated clothing immediately.

## 7.2 Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

## 7.3 Specific end use(s)

1	In addition to use mentioned in the Section 1.2, unforeseen other specific end uses.
---	--

# 8 Exposure controls/personal protection

## 8.1 Control parameters

### ◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Carbon disulphide	Japan - JSOH(2024–2025)	1	3.13	-	-
	Permissible exposure standards for workers in the workplace	10	31	15	46.5
	European Union	5	15	-	-
	France	5	15	-	-
	Germany (AGS)	10	30	20	60
	Germany (DFG)	5	16	10	32
Methyl acrylate	Japan - JSOH(2024–2025)	2	7	-	-
	Permissible exposure standards for workers in the workplace	10	35	15	52.5
	European Union	5	18	10	36
	France	5	18	10	36
	Germany (AGS)	2	7.1	4	14.2
	Germany (DFG)	2	7.1	4	14.2
Ethyl acrylate	Permissible exposure standards for workers in the workplace	25	102	37.5	127.5
	European Union	5	21	10	42
	France	5	21	10	42
	Germany (AGS)	2	8.3	4	16.6
	Germany (DFG)	2	8.3	4	16.6

	Italy	5	21	10	42
<b>Butyl acrylate</b>	European Union	2	11	10	53
	France	2	11	10	53
	Germany (AGS)	2	11	4	22
	Germany (DFG)	2	11	4	22
	Italy	2	11	10	53
	United Kingdom	1	5	5	26

◆ Biological limit values

Component	Standard	Biological monitoring index	Biological limits value	Sampling time	Remark
<b>Carbon disulphide</b>	SCOEL(EU)	2-thiothiazolidine-4-carboxylic acid/urine	1.5mg/g creatinine	end of shift	
		2-Thiothiazolidine-4-carboxylic acid (TTCA)(Creatinine in urine)	0.5mg/g	End of shift	

◆ Monitoring methods

1	EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
2	GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.

◆ Derived No effect level (DNEL)

Component	Route of exposure	DNEL for Workers			
		Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
<b>Carbon disulphide</b>	Inhalation	No data available	No data available	No data available	15.8 mg/m <sup>3</sup>
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Methyl acrylate</b>	Inhalation	No data available	No data available	18 mg/m <sup>3</sup>	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Ethyl acrylate</b>	Inhalation	No data available	No data available	21 mg/m <sup>3</sup>	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Propyl acrylate</b>	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Butyl acrylate</b>	Inhalation	No data available	No data available	11 mg/m <sup>3</sup>	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
<b>Pentyl acrylate</b>	Inhalation	No data available	No data available	No data available	No data available

	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

◆ Predicted No Effect Concentration (PNEC)

Component	A	B	C	D	E	F	G	H
<b>Carbon disulphide</b>	10 µg/L	1 µg/L	130 µg/L	70 µg/kg sediment dw	7 µg/kg sediment dw	No hazard identified	8.1 µg/kg soil dw	No potential for bioaccumulation
<b>Methyl acrylate</b>	2.72 µg/L	270 ng/L	10 mg/L	11.5 µg/kg sediment dw	11.5 µg/kg sediment dw	No hazard identified	1 mg/kg soil dw	1.1 mg/kg food
<b>Ethyl acrylate</b>	2.72 µg/L	270 ng/L	10 mg/L	21.3 µg/kg sediment dw	2.13 µg/kg sediment dw	No hazard identified	1 mg/kg soil dw	10 mg/kg food
<b>Butyl acrylate</b>	2.72 µg/L	272 ng/L	3.5 mg/L	33.8 µg/kg sediment dw	3.38 µg/kg sediment dw	No hazard identified	1 mg/kg soil dw	No potential for bioaccumulation

**Note 1:**

A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).

**Note 2:**

The PNEC values of the remaining components not shown in the product are not available yet.

## 8.2 Exposure controls

### 8.2.1 Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

### 8.2.2 Personal protection equipment

General requirement	
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear anti static chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

### 8.2.3 Environmental exposure controls

Environmental exposure controls	No information available
---------------------------------	--------------------------

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	Clear, colorless liquid
Colour	Clear, colorless liquid
Odor	No information available
Odor threshold	No information available
pH	No information available
Melting point/freezing point(°C)	-111 ( Carbon disulphide )
Initial boiling point and boiling range(°C)	46 ( Carbon disulphide )
Flash point(Closed cup, °C)	-30 ( Carbon disulphide )
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[% (v/v)]	Upper limit : 50 ( Carbon disulphide ); Lower limit : 1 ( Carbon disulphide )
Vapor pressure	48kPa ( 25°C, Carbon disulphide )
Vapor density(Air = 1)	2.63 ( Carbon disulphide )
Relative density(Water=1)	1.26 ( Carbon disulphide )
Solubility	2.9g/L ( 20 °C, Carbon disulphide )
n-octanol/water partition coefficient	1.84 ( Carbon disulphide )
Auto-ignition temperature(°C)	90 ( Carbon disulphide )
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Particle characteristics	Not applicable

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

Information with regard to physical hazard classes	No information available
--	--------------------------

#### 9.2.2 Other safety characteristics

Other safety characteristics	No information available
------------------------------	--------------------------

## 10 Stability and reactivity

### Stability and reactivity

10.1 Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
10.2 Chemical stability	Stable under proper operation and storage conditions.
10.3 Possibility of hazardous reactions	May catch fire spontaneously in the air. In contact with inorganic acids and organic peroxides causes a severe polymerization.
10.4 Conditions to avoid	Incompatible materials, heat, flame and spark.

<b>10.5 Incompatible materials</b>	Nitrate and nitrite, halogens oxyacid salts, potassium permanganate, persulfate, halogen and strong oxidants. Inorganic acids, alkali and organic peroxides.
<b>10.6 Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11 Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

5 Mix acrylic esters in carbon disulfide	
<b>Skin corrosion/irritation</b>	Causes skin irritation(Category 2)
<b>Serious eye damage/irritation</b>	Causes serious eye irritation(Category 2)
<b>Skin sensitization</b>	Based on available data, the classification criteria are not met
<b>Respiratory sensitization</b>	Based on available data, the classification criteria are not met
<b>Reproductive toxicity</b>	Suspected of damaging fertility and the unborn child(Category 2)
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met
<b>STOT-repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure(Category 1)
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met

#### Acute toxicity

Component	LD <sub>50</sub> (oral)	LD <sub>50</sub> (dermal)	LC <sub>50</sub> (inhalation,4h)
<b>Ethyl acrylate</b>	800mg/kg(Rat)	460mg/kg(Rabbit)	5.790mg/L(Rat)
<b>Methyl acrylate</b>	277mg/kg(Rat)	1243mg/kg(Rabbit)	4.753mg/L(Rat)
<b>Carbon disulphide</b>	1200mg/kg(Rat)	No information available	No information available
<b>Butyl acrylate</b>	900mg/kg(Rat)	1770mg/kg(Rabbit)	14.311mg/L(Rat)

#### Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP
<b>Carbon disulphide</b>	Not Listed	Not Listed
<b>Methyl acrylate</b>	Category 2B	Not Listed
<b>Ethyl acrylate</b>	Category 2B	Not Listed
<b>Propyl acrylate</b>	Not Listed	Not Listed
<b>Butyl acrylate</b>	Category 3	Not Listed
<b>Pentyl acrylate</b>	Not Listed	Not Listed

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Component	Endocrine disrupting properties
<b>Carbon disulphide</b>	No information available
<b>Methyl acrylate</b>	No information available
<b>Ethyl acrylate</b>	No information available

<b>Propyl acrylate</b>	No information available
<b>Butyl acrylate</b>	No information available
<b>Pentyl acrylate</b>	No information available

### 11.2.2 Other Information

<b>Other Information</b>	See Section 11.1
--------------------------	------------------

## 12 Ecological information

### 12.1 Toxicity

#### Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
<b>Ethyl acrylate</b>	LC <sub>50</sub> : 2.5mg/L (96h)(Fish)	EC <sub>50</sub> : 4.4mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 2.3mg/L (72h)(Algae)
<b>Methyl acrylate</b>	LC <sub>50</sub> : 1.4mg/L (96h)(Fish)	EC <sub>50</sub> : 2.6mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 3.1mg/L (72h)(Algae)
<b>Carbon disulphide</b>	LC <sub>50</sub> : 3mg/L (96h)(Fish)	No information available	ErC <sub>50</sub> : 21mg/L (96h)(Algae)
<b>Butyl acrylate</b>	LC <sub>50</sub> : 2.4mg/L (96h)(Fish)	EC <sub>50</sub> : 5.2mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 1.7mg/L (72h)(Algae)

#### Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
<b>Ethyl acrylate</b>	No information available	NOEC : 0.46mg/L(Crustaceans)	NOEC : 0.96mg/L(Algae)
<b>Methyl acrylate</b>	No information available	NOEC : 0.36mg/L(Crustaceans)	NOEC : 1.1mg/L(Algae)
<b>Butyl acrylate</b>	No information available	NOEC : 1.0mg/L(Crustaceans)	NOEC : 0.077mg/L(Algae)

### 12.2 Persistence and degradability

<b>Persistence and degradability</b>	No information available
--------------------------------------	--------------------------

### 12.3 Bioaccumulative potential

<b>Bioaccumulative potential</b>	No information available
----------------------------------	--------------------------

### 12.4 Mobility in soil

Component	log Koc	Remark
<b>Carbon disulphide</b>	1.53	20 °C
<b>Methyl acrylate</b>	0.81	20 °C
<b>Ethyl acrylate</b>	1.63	20 °C

### 12.5 Results of PBT and vPvB assessment

<b>Component</b>	<b>Results of PBT and vPvB assessment [according to (EC) No 1907/2006]</b>
------------------	--

<b>Carbon disulphide</b>	Not PBT/vPvB
<b>Methyl acrylate</b>	Not PBT/vPvB
<b>Ethyl acrylate</b>	Not PBT/vPvB
<b>Propyl acrylate</b>	Insufficient information, temporarily unable to evaluate
<b>Butyl acrylate</b>	Not PBT/vPvB
<b>Pentyl acrylate</b>	Insufficient information, temporarily unable to evaluate

## 12.6 Endocrine disrupting properties

Component	Endocrine disrupting properties
<b>Carbon disulphide</b>	No information available
<b>Methyl acrylate</b>	No information available
<b>Ethyl acrylate</b>	No information available
<b>Propyl acrylate</b>	No information available
<b>Butyl acrylate</b>	No information available
<b>Pentyl acrylate</b>	No information available

## 12.7 Other adverse effects

No information available
--------------------------

## 13 Disposal considerations

### 13.1 Waste treatment methods

<b>Waste chemicals</b>	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
<b>Contaminated packaging</b>	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
<b>Disposal recommendations</b>	Refer to section waste chemicals and contaminated packaging.

## 14 Transport information

### Label and Mark

<b>Transporting Label</b>	
---------------------------	---

### IMDG-CODE

<b>14.1 UN number</b>	1993
<b>14.2 UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>14.3 Transport hazard class</b>	3
<b>14.4 Packing group</b>	II
<b>14.5 Environmental hazards (Yes or no)</b>	No

### IATA-DGR

<b>14.1 UN number</b>	1993
-----------------------	------

14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

### UN-ADR

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

### Special precautions for user

	Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.
--	--

### Maritime transport in bulk according to IMO instruments

- ◆ Transport in bulk according to Annex II of MARPOL and the IBC code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with the IGC Code

	Not Available
--	---------------

## 15 Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International chemical inventory

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
Carbon disulphide	√	√	√	√	√	√	√	√	√	√	√	√	√
Methyl acrylate	√	√	√	√	√	√	√	√	√	√	√	√	√
Ethyl acrylate	√	√	√	√	√	√	√	√	√	√	√	√	√
Propyl acrylate	×	√	√	×	×	×	√	×	√	×	×	√	√
Butyl acrylate	√	√	√	√	√	√	√	√	√	√	√	√	√

<b>Pentyl acrylate</b>	x	√	√	x	x	x	√	x	x	x	x	x	√
------------------------	---	---	---	---	---	---	---	---	---	---	---	---	---

- [A] China Inventory of Existing Chemical Substances(IECSC)  
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)  
 [C] United States Toxic Substances Control Act Inventory(TSCA)  
 [D] Canadian Domestic Substances List(DSL)  
 [E] New Zealand Inventory of Chemicals(NZIoC)  
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)  
 [G] Korea Existing Chemicals Inventory(KECL)  
 [H] Australian. Inventory of Industrial Chemical (AIICS)  
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)  
 [J] Thailand Existing Chemicals Inventory(TECI)  
 [K] Mexico National Inventory of Chemical Substances (INSQ)  
 [L] Russia Inventory of Existing Substances(DRAFT)  
 [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

### List of Chemical Substances under International Conventions

Component	A	B	C
<b>Carbon disulphide</b>	x	x	x
<b>Methyl acrylate</b>	x	x	x
<b>Ethyl acrylate</b>	x	x	x
<b>Propyl acrylate</b>	x	x	x
<b>Butyl acrylate</b>	x	x	x
<b>Pentyl acrylate</b>	x	x	x

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer  
 [B] Stockholm Convention on Persistent Organic Pollutants (POPs)  
 [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

### European chemical inventory

Component	A	B	C	D	E	F	G	H	I
<b>Carbon disulphide</b>	x	x	x	√	√	√	x	x	x
<b>Methyl acrylate</b>	x	x	x	√	√	x	x	x	x
<b>Ethyl acrylate</b>	x	x	x	√	√	x	x	x	x
<b>Propyl acrylate</b>	x	x	x	√	x	x	x	x	x
<b>Butyl acrylate</b>	x	x	x	√	√	√	x	x	x
<b>Pentyl acrylate</b>	x	x	x	√	x	x	x	x	x

- [A] Candidate list of Substances of Very High Concern for authorization under EU REACH regulation  
 [B] Substances requiring authorisation under EU REACH regulation  
 [C] Substances restricted under EU REACH  
 [D] Pre-registered substances under EU REACH  
 [E] Registered substances under EU REACH  
 [F] Substance Evaluation – CoRAP under EU REACH  
 [G] List of priority substances under EU water policy ( Directive 2455/2001/EC )  
 [H] Substances subject to POPs Regulation  
 [I] Substances proposed as POPs

Note:

- “√” Indicates that the substance included in the regulations.  
 “x” No data or not included in the regulations.

**German water hazard class(WGK)**

Component	WGK	Remark
Carbon disulphide	WGK 2	
Methyl acrylate	WGK 2	
Ethyl acrylate	WGK 2	
Butyl acrylate	WGK 1	

- 【WGK 1】 slightly hazardous to water  
 【WGK 2】 obviously hazardous to water  
 【WGK 3】 highly hazardous to water  
 【nwg】 non-hazardous to water  
 【awg】 hazardous to water in general

**German technical instructions on air quality control(TA LUFT)**

Component	TA LUFT	Remark
Methyl acrylate	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m <sup>3</sup>	
Ethyl acrylate	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m <sup>3</sup>	

**German technical rules for hazardous substances(TRGS)**

Component	TRGS	Remark
Carbon disulphide	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 TRGS 523	
Methyl acrylate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Ethyl acrylate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Butyl acrylate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	

**15.2 Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16 Other information

### Information on revision

Creation Date	2025/12/22
Revision Date	-
Reason for revision	-

### Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

### Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC <sub>50</sub>	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD <sub>50</sub>	Lethal Dose 50%	NTP	National Toxicology Program
EC <sub>50</sub>	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC <sub>x</sub>	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P <sub>ow</sub>	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor		

### Disclaimer

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.