

Safety Data Sheet

13 Mix VOC in acetonitrile

Version : V2.0.0.1

Report No. : BWQ9232-2016-MSDS-EP

Creation Date : 2025/12/31

Revision Date : -



*Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name	13 Mix VOC in acetonitrile
Cat No.	BWQ9232-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable
REACH Registration Number	-
UFI	No information available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

1.4 Emergency telephone number

Emergency telephone number	010-58103678
Opening hours	24h

2 Hazards identification

2.1 CLP classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Acute Toxicity - Dermal	Category 4
Serious eye damage/irritation	Category 2
Acute Toxicity - Inhalation	Category 3

2.2 Label elements

Hazard pictograms	 
Signal word	Danger

Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H319	Causes serious eye irritation
H331	Toxic if inhaled

Precautionary statements

◆ Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

◆ Response

P311	Call a POISON CENTER/ doctor.
P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P301+P312	IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

◆ Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

◆ Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

2.3 Other hazards

◆ Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Acetonitrile	Not PBT/vPvB
Methanol	Not PBT/vPvB
Ethanol	Not PBT/vPvB
Propan-1-ol	Insufficient information, temporarily unable to evaluate
Propan-2-ol	Not PBT/vPvB
Butan-1-ol	Not PBT/vPvB
2-methylpropan-1-ol	Not PBT/vPvB
Triethylamine	Not PBT/vPvB
2-dimethylaminoethanol	Not PBT/vPvB
2-amino-2-methylpropanol	Not PBT/vPvB
Ethane-1,2-diol	Not PBT/vPvB
1,2-Propanediol	Not PBT/vPvB
2,2'-oxydiethanol	Not PBT/vPvB
2,2,4-trimethylpentane-1,3-diol	Not PBT/vPvB

◆ Results of endocrine disrupting properties assessment

Component	Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605]
Acetonitrile	Insufficient information, temporarily unable to evaluate
Methanol	Insufficient information, temporarily unable to evaluate
Ethanol	Insufficient information, temporarily unable to evaluate
Propan-1-ol	Insufficient information, temporarily unable to evaluate
Propan-2-ol	Insufficient information, temporarily unable to evaluate
Butan-1-ol	Insufficient information, temporarily unable to evaluate
2-methylpropan-1-ol	Insufficient information, temporarily unable to evaluate
Triethylamine	Insufficient information, temporarily unable to evaluate
2-dimethylaminoethanol	Insufficient information, temporarily unable to evaluate
2-amino-2-methylpropanol	Insufficient information, temporarily unable to evaluate
Ethane-1,2-diol	Insufficient information, temporarily unable to evaluate

1,2-Propanediol	Insufficient information, temporarily unable to evaluate
2,2'-oxydiethanol	Insufficient information, temporarily unable to evaluate
2,2,4-trimethylpentane-1,3-diol	Insufficient information, temporarily unable to evaluate

◆ Other

Not applicable.

3 Composition/information on ingredients

3.1 Substance

Not applicable

3.2 Mixture

Component	Weight % content(or range)	Classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707 [CLP]	Specific Conc. Limits, M-factors
Acetonitrile CAS : 75-05-8 EC : 200-835-2 Index No. : 608-001-00-3	98.31	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 4, H302; Acute Toxicity - Dermal, Category 4, H312; Serious eye damage/irritation, Category 2, H319; Acute Toxicity - Inhalation, Category 4, H332	-
Methanol CAS : 67-56-1 EC : 200-659-6 Index No. : 603-001-00-X	0.13	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 3, H301; Acute Toxicity - Dermal, Category 3, H311; Acute Toxicity - Inhalation, Category 3, H331; Specific target organ toxicity - single exposure, Category 1, H370	H370:C ≥ 10% H371:3% ≤ C < 10%
Ethanol CAS : 64-17-5 EC : 200-578-6 Index No. : 603-002-00-5	0.13	Flammable liquids, Category 2, H225	-
Propan-1-ol CAS : 71-23-8 EC : 200-746-9 Index No. : 603-003-00-0	0.13	Flammable liquids, Category 2, H225; Serious eye damage/irritation, Category 1, H318; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336	-
Propan-2-ol CAS : 67-63-0 EC : 200-661-7 Index No. : 603-117-00-0	0.13	Flammable liquids, Category 2, H225; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336	-
Butan-1-ol CAS : 71-36-3 EC : 200-751-6 Index No. : 603-004-00-6	0.13	Flammable liquids, Category 3, H226; Acute Toxicity - Oral, Category 4, H302; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 1, H318; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336	-
2-methylpropan-1-ol CAS : 78-83-1 EC : 201-148-0 Index No. : 603-108-00-1	0.13	Flammable liquids, Category 3, H226; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 1, H318; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Specific target organ toxicity - single exposure; narcotic	-

		effects, Category 3, H336	
Triethylamine CAS : 121-44-8 EC : 204-469-4 Index No. : 612-004-00-5	0.13	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 3, H301; Acute Toxicity - Dermal, Category 3, H311; Skin corrosion/irritation, Category 1A, H314; Serious eye damage/irritation, Category 1, H318; Acute Toxicity - Inhalation, Category 3, H331	H335:C ≥ 1%;H331:ATE = 7.2 mg/L (vapours) H311:ATE = 300 mg/kg bw H301:ATE = 100 mg/kg bw
2-dimethylaminoethanol CAS : 108-01-0 EC : 203-542-8 Index No. : 603-047-00-0	0.13	Flammable liquids, Category 3, H226; Acute Toxicity - Oral, Category 4, H302; Acute Toxicity - Dermal, Category 4, H312; Skin corrosion/irritation, Category 1B, H314; Acute Toxicity - Inhalation, Category 4, H332	H335:C ≥ 5%
2-amino-2-methylpropanol CAS : 124-68-5 EC : 204-709-8 Index No. : 603-070-00-6	0.13	Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 3, H412	-
Ethane-1,2-diol CAS : 107-21-1 EC : 203-473-3 Index No. : 603-027-00-1	0.13	Acute Toxicity - Oral, Category 4, H302	-
1,2-Propanediol CAS : 57-55-6 EC : 200-338-0 Index No. : -	0.13	Not Classified	-
2,2'-oxydiethanol CAS : 111-46-6 EC : 203-872-2 Index No. : 603-140-00-6	0.13	Acute Toxicity - Oral, Category 4, H302	-
2,2,4-trimethylpentane-1,3-diol CAS : 144-19-4 EC : 205-619-1 Index No. : -	0.13	Serious eye damage/irritation, Category 2, H319	-

4 First-aid measures

4.1 Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse skin with plenty of water or shower. Refer for medical attention.
Ingestion	Rinse mouth. Induce vomiting (ONLY IN CONSCIOUS PERSONS!). Give plenty of water to drink. Refer for medical attention.
Inhalation	Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

4.2 Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

4.3 Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
Unsuitable extinguishing media	Use of water spray when fighting fire may be inefficient.

5.2 Specific hazards arising from the substance or mixture

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
4	Liquid and vapour are flammable.
5	Development of hazardous combustion gases or vapor possible in the event of fire.
6	May expand or decompose explosively when heated or involved in fire.

5.3 Advice for firefighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

1	Avoid breathing vapours and contacting with skin and eye.
2	Beware of vapours accumulating to form explosive concentrations.
3	Vapours can accumulate in low areas.
4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
6	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
7	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

1	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
2	In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
3	In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to

	reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Cut off the source of the leak as much as possible.
9	Keep leaks in a ventilated place.
10	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
11	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
12	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
13	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4 Reference to other sections

1	Personal Protective Equipment advice is contained in Section 8 of the SDS.
2	Disposal considerations advice is contained in Section 13 of the SDS.

7 Handling and storage

7.1 Precautions for safe handling

◆ Protective measures

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.

◆ Measures to prevent fire

1	Use only non-sparking tools.
2	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
3	Use explosion proof equipment.
4	Keep away from heat/sparks/open flames/ hot surfaces.

◆ Measures to prevent aerosol and dust generation

1	Not applicable.
---	-----------------

◆ Advice on general occupational hygiene

1	Wash hands and face after using the substances.
2	Replace the contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

7.3 Specific end use(s)

1	In addition to use mentioned in the Section 1.2, unforeseen other specific end uses.
---	--

8 Exposure controls/personal protection

8.1 Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m ³	ppm	mg/m ³
Acetonitrile	Permissible exposure standards for workers in the workplace	40	67	60	100.5
	European Union	40	70	-	-
	France	40	70	-	-
	Germany (AGS)	10	17	20	34
	Germany (DFG)	10	17	20	34
	Italy	20	35	-	-
Methanol	Japan - JSOH(2024-2025)	200	260	-	-
	Permissible exposure standards for workers in the workplace	200	262	250	327.5
	European Union	200	260	-	-
	France	200	260	-	-
	Germany (AGS)	100	130	200	260
	Germany (DFG)	100	130	200	260
Ethanol	Permissible exposure standards for workers in the workplace	1000	1880	1000	1880
	France	1000	1900	5000	9500
	Germany (AGS)	200	380	800	1520
	Germany (DFG)	200	380	800	1520
	United Kingdom	1000	1920	-	-
	Austria	1000	1900	2000	3800
Propan-1-ol	Permissible exposure standards for workers in the workplace	200	491	250	613.75
	France	200	500	-	-
	United Kingdom	200	500	250	625
	Austria	200	500	-	-
	Belgium	100	250	-	-

	Denmark	200	500	400	1000
Propan-2-ol	Japan - JSOH(2024–2025)	-	-	-	-
	Permissible exposure standards for workers in the workplace	400	983	500	1228.75
	France	-	-	400	980
	Germany (AGS)	200	500	400	1000
	Germany (DFG)	200	500	400	1000
	United Kingdom	400	999	500	1250
Butan-1-ol	Japan - JSOH(2024–2025)	-	-	-	-
	Permissible exposure standards for workers in the workplace	100	303	125	378.75
	France	-	-	50	150
	Germany (AGS)	100	310	100	310
	Germany (DFG)	100	310	100	310
	United Kingdom	-	-	50	154
2-methylpropan-1-ol	Japan - JSOH(2024–2025)	50	150	-	-
	Permissible exposure standards for workers in the workplace	50	152	75	190
	France	50	150	-	-
	Germany (AGS)	100	310	100	310
	Germany (DFG)	100	310	100	310
	United Kingdom	50	154	75	231
Triethylamine	Permissible exposure standards for workers in the workplace	10	41	15	61.5
	European Union	2	8.4	3	12.6
	France	1	4.2	3	12.6
	Germany (AGS)	1	4.2	2	8.4
	Germany (DFG)	1	4.2	2	8.4
	Italy	2	8.4	3	12.6
2-dimethylaminoethanol	United Kingdom	2	7.4	6	22
	Denmark	10(provisional	-	-	-

)			
	Latvia	-	5	-	-
	New Zealand	2	7.4	6	22
	Canada - Ontario	3	11	6	22
2-amino-2-methylpropanol	Germany (AGS)	1	3.7	2	7.4
	Germany (DFG)	1	3.7	2	7.4
	Switzerland	2.4	8.7	4.8	17.4
Ethane-1,2-diol	Permissible exposure standards for workers in the workplace	-	10(mist)	-	15(mist)
	Permissible exposure standards for workers in the workplace	-	-	-	-
	European Union	20	52	40	104
	France	20	52	40	104
	Germany (AGS)	10	26	20	52
	Germany (DFG)	10	26	20	52
1,2-Propanediol	United Kingdom	-	10(particulates)	-	-
	Ireland	150(vapour and particulates)	470(vapour and particulates)	-	-
	Latvia	-	7	-	-
	New Zealand	150	474	-	-
	Norway	25	79	-	-
	Poland	-	100	-	-
2,2'-oxydiethanol	Germany (AGS)	10	44	40	176
	Germany (DFG)	10	44	40	176
	United Kingdom	23	101	-	-
	Austria	10	44	40	176
	Denmark	2.5	11	5	22
	Ireland	23	100	-	-

◆ Biological limit values

Component	Standard	Biological monitoring index	Biological limits value	Sampling time	Remark
Methanol	USA -ACGIH	Methanol(Urine)	15mg/L	End of shift	
Propan-2-ol	USA -ACGIH	Acetone(Urine)	40mg/L	End of shift at end of work week	

◆ Monitoring methods

1	EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
2	GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.

◆ Derived No effect level (DNEL)

Component	Route of exposure	DNEL for Workers			
		Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Acetonitrile	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Methanol	Inhalation	No data available	No data available	130 mg/m ³	130 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Ethanol	Inhalation	No data available	No data available	No data available	380 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Propan-1-ol	Inhalation	No data available	No data available	No data available	268 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Propan-2-ol	Inhalation	No data available	No data available	No data available	500 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Butan-1-ol	Inhalation	No data available	No data available	310 mg/m ³	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2-methylpropan-1-ol	Inhalation	No data available	No data available	310 mg/m ³	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Triethylamine	Inhalation	No data available	No data available	8.4 mg/m ³	8.4 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2-dimethylaminoethanol	Inhalation	No data available	No data available	1.76 mg/m ³	1.76 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2-amino-2-methylpropanol	Inhalation	No data available	No data available	No data available	6.5 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Ethane-1,2-diol	Inhalation	No data available	No data available	35 mg/m ³	No data available
	Oral	No data available	No data available	No data available	No data available

	Dermal	No data available	No data available	No data available	No data available
1,2-Propanediol	Inhalation	No data available	No data available	10 mg/m3	168 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2,2'-oxydiethanol	Inhalation	No data available	No data available	60 mg/m3	44 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
2,2,4-trimethylpentane-1,3-diol	Inhalation	No data available	No data available	No data available	6.61 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

◆ Predicted No Effect Concentration (PNEC)

Component	A	B	C	D	E	F	G	H
Acetonitrile	10 mg/L	1 mg/L	32 mg/L	40.5 mg/kg sediment dw	4.05 mg/kg sediment dw	No hazard identified	2.23 mg/kg soil dw	No potential for bioaccumulation
Methanol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Ethanol	960 µg/L	790 µg/L	580 mg/L	3.6 mg/kg sediment dw	2.9 mg/kg sediment dw	No hazard identified	630 µg/kg soil dw	380 - 720 mg/kg food
Propan-1-ol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Propan-2-ol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Butan-1-ol	82 µg/L	8.2 µg/L	2.476 g/L	324 µg/kg sediment dw	32.4 µg/kg sediment dw	No hazard identified	16.6 µg/kg soil dw	No potential for bioaccumulation
2-methylpropan-1-ol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Triethylamine	110 µg/L	11 µg/L	100 mg/L	1.575 mg/kg sediment dw	158 µg/kg sediment dw	No hazard identified	250 µg/kg soil dw	No potential for bioaccumulation
2-dimethylaminoethanol	66.1 µg/L	4 µg/L	10 mg/L	246 µg/kg sediment	15 µg/kg sediment dw	No hazard identified	10 µg/kg soil dw	No potential for

				dw				bioaccumulation
2-amino-2-methylpropanol	188 µg/L	18.8 µg/L	10 mg/L	710 µg/kg sediment dw	71 µg/kg sediment dw	No hazard identified	30 µg/kg soil dw	No potential for bioaccumulation
Ethane-1,2-diol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
1,2-Propanediol	260 mg/L	26 mg/L	20 g/L	572 mg/kg sediment dw	57.2 mg/kg sediment dw	No hazard identified	50 mg/kg soil dw	No potential for bioaccumulation
2,2'-oxydiethanol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
2,2,4-trimethylpentane-1,3-diol	109.1 µg/L	10.91 µg/L	20 mg/L	903 µg/kg sediment dw	90.3 µg/kg sediment dw	No hazard identified	117 µg/kg soil dw	No data available

Note 1:

A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).

Note 2:

The PNEC values of the remaining components not shown in the product are not available yet.

8.2 Exposure controls

8.2.1 Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

8.2.2 Personal protection equipment

General requirement	
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear anti static chemical protective gloves.
Respiratory protection	Must wear appropriate personal dust proof gas mask.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

8.2.3 Environmental exposure controls

Environmental exposure controls	No information available
--	--------------------------

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	clear or yellow liquid
Colour	clear or yellow liquid
Odor	No information available
Odor threshold	No information available
pH	No information available
Melting point/freezing point(°C)	-46 (Acetonitrile)
Initial boiling point and boiling range(°C)	82 (Acetonitrile)
Flash point(Closed cup,°C)	2 (Acetonitrile)
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit : 17 (Acetonitrile); Lower limit : 3 (Acetonitrile)
Vapor pressure	9.9kPa (25°C,Acetonitrile)
Vapor density(Air = 1)	1.4 (Acetonitrile)
Relative density(Water=1)	0.8 (Acetonitrile)
Solubility	1000000mg/L (25 °C,Acetonitrile)
n-octanol/water partition coefficient	-0.3 (Acetonitrile)
Auto-ignition temperature(°C)	524 (Acetonitrile)
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Particle characteristics	Not applicable

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Information with regard to physical hazard classes	No information available
--	--------------------------

9.2.2 Other safety characteristics

Other safety characteristics	No information available
------------------------------	--------------------------

10 Stability and reactivity

Stability and reactivity

10.1 Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
10.2 Chemical stability	Stable under proper operation and storage conditions.
10.3 Possibility of hazardous reactions	In contact with N-halogen compounds may cause a potensive explosive hazardous. In contact with oxidants causes severe reactions, and may cause a fire or explosion. In contact with oxidants, anhydrides, metals, metal oxides / KMnO4 metal salts, nitro-compounds may cause a fire or explosion.
10.4 Conditions to avoid	Incompatible materials, heat, flame and spark.
10.5 Incompatible materials	N - halogenated compounds, sulfuric acid and strong oxidants. Oxidants, alkali metals, alkaline earth metals and aluminum. Oxidants, halogen, anhydrides,

	acids, metals, metal oxides, potassium permanganate, nitro-compounds and metal salts.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

13 Mix VOC in acetonitrile	
Skin corrosion/irritation	Based on available data, the classification criteria are not met
Serious eye damage/irritation	Causes serious eye irritation(Category 2)
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Ethane-1,2-diol	4700mg/kg(Rat)	10600mg/kg(Rabbit)	No information available
Butan-1-ol	790mg/kg(Rat)	3400mg/kg(Rabbit)	24.252mg/L(Rat)
Triethylamine	460mg/kg(Rat)	415mg/kg(Rabbit)	No information available
2,2,4-trimethylpentane-1,3-diol	2000mg/kg(Rat)	5900mg/kg(Rabbit)	No information available
Propan-2-ol	5045mg/kg(Rat)	12800mg/kg(Rabbit)	No information available
2-methylpropan-1-ol	2460mg/kg(Rat)	3400mg/kg(Rabbit)	No information available
2-dimethylaminoethanol	2000mg/kg(Rat)	1220mg/kg(Rabbit)	5.983mg/L(Rat)
Methanol	5628mg/kg(Rat)	15800mg/kg(Rabbit)	83.867mg/L(Rat)
2-amino-2-methylpropano I	2900mg/kg(Rat)	No information available	No information available
Acetonitrile	2460mg/kg(Rat)	> 2000mg/kg(Rabbit)	4.748mg/L(Rabbit)
2,2'-oxydiethanol	12565mg/kg(Rat)	11890mg/kg(Rabbit)	No information available
Propan-1-ol	1870mg/kg(Rat)	5040mg/kg(Rabbit)	No information available
1,2-Propanediol	20000mg/kg(Rat)	20800mg/kg(Rabbit)	No information available
Ethanol	7060mg/kg(Rat)	No information available	39mg/L(Mouse)

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP
Acetonitrile	Not Listed	Not Listed
Methanol	Not Listed	Not Listed

Ethanol	Category 1(Remark 1)	Not Listed
Propan-1-ol	Not Listed	Not Listed
Propan-2-ol	Category 3	Not Listed
Butan-1-ol	Not Listed	Not Listed
2-methylpropan-1-ol	Not Listed	Not Listed
Triethylamine	Not Listed	Not Listed
2-dimethylaminoethanol	Not Listed	Not Listed
2-amino-2-methylpropanol	Not Listed	Not Listed
Ethane-1,2-diol	Not Listed	Not Listed
1,2-Propanediol	Not Listed	Not Listed
2,2'-oxydiethanol	Not Listed	Not Listed
2,2,4-trimethylpentane-1,3-diol	Not Listed	Not Listed

Remark 1: for alcoholic beverages only

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Component	Endocrine disrupting properties
Acetonitrile	No information available
Methanol	No information available
Ethanol	No information available
Propan-1-ol	No information available
Propan-2-ol	No information available
Butan-1-ol	No information available
2-methylpropan-1-ol	No information available
Triethylamine	No information available
2-dimethylaminoethanol	No information available
2-amino-2-methylpropanol	No information available
Ethane-1,2-diol	No information available
1,2-Propanediol	No information available
2,2'-oxydiethanol	No information available
2,2,4-trimethylpentane-1,3-diol	No information available

11.2.2 Other Information

Other Information	See Section 11.1
-------------------	------------------

12 Ecological information

12.1 Toxicity

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Ethane-1,2-diol	LC ₅₀ : >100mg/L (96h)(Fish)	EC ₅₀ : >1100mg/L (48h)(Crustaceans)	ErC ₅₀ : >1000mg/L (72h)(Algae)
Butan-1-ol	LC ₅₀ : >100mg/L (96h)(Fish)	EC ₅₀ : >1000mg/L (48h)(Crustaceans)	ErC ₅₀ : >1000mg/L (72h)(Algae)
Triethylamine	LC ₅₀ : 24mg/L (96h)(Fish)	EC ₅₀ : 34mg/L (48h)(Crustaceans)	ErC ₅₀ : 8.0mg/L (72h)(Algae)
2,2,4-trimethylpentane-1,3-diol	LC ₅₀ : > 700mg/L (96h)(Fish)	EC ₅₀ : > 109.1mg/L (48h)(Crustaceans)	ErC ₅₀ : > 110.1mg/L (72h)(Algae)
Propan-2-ol	LC ₅₀ : 9640mg/L (96h)(Fish)	EC ₅₀ : >1000mg/L (48h)(Crustaceans)	ErC ₅₀ : >1000mg/L (72h)(Algae)
2-methylpropan-1-ol	LC ₅₀ : 1510mg/L (96h)(Fish)	EC ₅₀ : 1200mg/L (48h)(Crustaceans)	No information available
2-dimethylaminoethanol	LC ₅₀ : 146.63mg/L (96h)(Fish)	EC ₅₀ : 98.37mg/L (48h)(Crustaceans)	ErC ₅₀ : 66.08mg/L (72h)(Algae)
Methanol	LC ₅₀ : 24000mg/L (96h)(Fish)	EC ₅₀ : 24500mg/L (48h)(Crustaceans)	No information available
2-amino-2-methylpropano I	LC ₅₀ :200mg/L (96h)(Fish)	No information available	No information available
Acetonitrile	LC ₅₀ : > 100mg/L (96h)(Fish)	EC ₅₀ : > 1000mg/L (48h)(Crustaceans)	ErC ₅₀ : >700mg/L (72h)(Algae)
2,2'-oxydiethanol	LC ₅₀ : 75200mg/L (96h)(Fish)	No information available	No information available
Propan-1-ol	LC ₅₀ : 4555mg/L (96h)(Fish)	EC ₅₀ : 4130mg/L (48h)(Crustaceans)	ErC ₅₀ : 4480mg/L (96h)(Algae)
1,2-Propanediol	LC ₅₀ : > 100mg/L (96h)(Fish)	EC ₅₀ : >1000mg/L (48h)(Crustaceans)	ErC ₅₀ : >1000mg/L (72h)(Algae)
Ethanol	LC ₅₀ : 11200mg/L (96h)(Fish)	EC ₅₀ : 9950mg/L (48h)(Crustaceans)	No information available

Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Ethane-1,2-diol	No information available	NOEC : 100mg/L(Crustaceans)	NOEC : 1000mg/L(Algae)
Acetonitrile	NOEC : 102mg/L(Fish)	NOEC : >960mg/L(Crustaceans)	NOEC : 700mg/L(Algae)
Triethylamine	No information available	NOEC : 11mg/L(Crustaceans)	NOEC : 1.1mg/L(Algae)
Butan-1-ol	NOEC : 46mg/L(Fish)	NOEC : 4.1mg/L(Crustaceans)	NOEC : 180mg/L(Algae)
Propan-2-ol	NOEC : > 100mg/L(Fish)	NOEC : >100mg/L(Crustaceans)	NOEC : 1000mg/L(Algae)
1,2-Propanediol	NOEC : >100mg/L(Fish)	NOEC : 1000mg/L(Crustaceans)	NOEC : 1000mg/L(Algae)

12.2 Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Methanol	Low	Low

Ethanol	Low(Half-life = 2.17 days)	Low(Half-life = 5.08 days)
Butan-1-ol	Low(Half-life = 54 days)	Low(Half-life = 3.65 days)
2-amino-2-methylpropanol	Low	Low
Ethane-1,2-diol	Low(Half-life = 24 days)	Low(Half-life = 3.46 days)
1,2-Propanediol	Low	Low
2,2'-oxydiethanol	Low	Low
2,2,4-trimethylpentane-1,3-diol	Low	Low

12.3 Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Methanol	Low	BCF=10
Ethanol	Low	Log Kow=-0.31
Butan-1-ol	Low	BCF=64
2-amino-2-methylpropanol	Low	BCF=330
Ethane-1,2-diol	Low	BCF=200
1,2-Propanediol	Low	BCF=1
2,2'-oxydiethanol	Low	BCF=180
2,2,4-trimethylpentane-1,3-diol	Low	Log Kow=1.24

12.4 Mobility in soil

Component	log Koc	Remark
Acetonitrile	0.653	
Methanol	0.000	
Ethanol	0	
Propan-2-ol	0.54	20 °C
Butan-1-ol	0.54	20 °C
Triethylamine	2.03	20 °C
2-dimethylaminoethanol	0.09	20 °C
2-amino-2-methylpropanol	0.083	log Kow method
Ethane-1,2-diol	0.000	
1,2-Propanediol	0.46	20 °C
2,2'-oxydiethanol	0.000	
2,2,4-trimethylpentane-1,3-diol	0.000	

12.5 Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Acetonitrile	Not PBT/vPvB

Methanol	Not PBT/vPvB
Ethanol	Not PBT/vPvB
Propan-1-ol	Insufficient information, temporarily unable to evaluate
Propan-2-ol	Not PBT/vPvB
Butan-1-ol	Not PBT/vPvB
2-methylpropan-1-ol	Not PBT/vPvB
Triethylamine	Not PBT/vPvB
2-dimethylaminoethanol	Not PBT/vPvB
2-amino-2-methylpropanol	Not PBT/vPvB
Ethane-1,2-diol	Not PBT/vPvB
1,2-Propanediol	Not PBT/vPvB
2,2'-oxydiethanol	Not PBT/vPvB
2,2,4-trimethylpentane-1,3-diol	Not PBT/vPvB

12.6 Endocrine disrupting properties

Component	Endocrine disrupting properties
Acetonitrile	No information available
Methanol	No information available
Ethanol	No information available
Propan-1-ol	No information available
Propan-2-ol	No information available
Butan-1-ol	No information available
2-methylpropan-1-ol	No information available
Triethylamine	No information available
2-dimethylaminoethanol	No information available
2-amino-2-methylpropanol	No information available
Ethane-1,2-diol	No information available
1,2-Propanediol	No information available
2,2'-oxydiethanol	No information available
2,2,4-trimethylpentane-1,3-diol	No information available

12.7 Other adverse effects

	No information available
--	--------------------------

13 Disposal considerations

13.1 Waste treatment methods

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
------------------------	--

Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label	
--------------------	---

IMDG-CODE

14.1 UN number	1212
14.2 UN proper shipping name	ISOBUTANOL(ISOBUTYL ALCOHOL)
14.3 Transport hazard class	3
14.4 Packing group	III
14.5 Environmental hazards (Yes or no)	No

IATA-DGR

14.1 UN number	1212
14.2 UN proper shipping name	ISOBUTANOL (ISOBUTYL ALCOHOL)
14.3 Transport hazard class	3
14.4 Packing group	III
14.5 Environmental hazards (Yes or no)	No

UN-ADR

14.1 UN number	1212
14.2 UN proper shipping name	ISOBUTANOL(ISOBUTYL ALCOHOL)
14.3 Transport hazard class	3
14.4 Packing group	III
14.5 Environmental hazards (Yes or no)	No

Special precautions for user

	<p>Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature.</p> <p>Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.</p>
--	--

Maritime transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

15 Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****International chemical inventory**

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
Acetonitrile	√	√	√	√	√	√	√	√	√	√	√	√	√
Methanol	√	√	√	√	√	√	√	√	√	√	√	√	√
Ethanol	√	√	√	√	√	√	√	√	√	√	√	√	√
Propan-1-ol	√	√	√	√	√	√	√	√	√	√	√	√	√
Propan-2-ol	√	√	√	√	√	√	√	√	√	√	√	√	√
Butan-1-ol	√	√	√	√	√	√	√	√	√	√	√	√	√
2-methylpropan-1-ol	√	√	√	√	√	√	√	√	√	√	√	√	√
Triethylamine	√	√	√	√	√	√	√	√	√	√	√	√	√
2-dimethylaminoethanol	√	√	√	√	√	√	√	√	√	√	√	√	√
2-amino-2-methylpropanol	√	√	√	√	√	√	√	√	√	√	√	√	√
Ethane-1,2-diol	√	√	√	√	√	√	√	√	√	√	√	√	√
1,2-Propanediol	√	√	√	√	√	√	√	√	√	√	√	√	√
2,2'-oxydiethanol	√	√	√	√	√	√	√	√	√	√	√	√	√
2,2,4-trimethylpentane-1,3-diol	√	√	√	√	√	√	√	√	√	√	√	√	√

- [A] China Inventory of Existing Chemical Substances(IECSC)
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
 [C] United States Toxic Substances Control Act Inventory(TSCA)
 [D] Canadian Domestic Substances List(DSL)
 [E] New Zealand Inventory of Chemicals(NZIoC)
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
 [G] Korea Existing Chemicals Inventory(KECL)
 [H] Australian. Inventory of Industrial Chemical (AIICS)
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)
 [J] Thailand Existing Chemicals Inventory(TECI)
 [K] Mexico National Inventory of Chemical Substances (INSQ)
 [L] Russia Inventory of Existing Substances(DRAFT)
 [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	B	C
Acetonitrile	×	×	×

Methanol	x	x	x
Ethanol	x	x	x
Propan-1-ol	x	x	x
Propan-2-ol	x	x	x
Butan-1-ol	x	x	x
2-methylpropan-1-ol	x	x	x
Triethylamine	x	x	x
2-dimethylaminoethanol	x	x	x
2-amino-2-methylpropano l	x	x	x
Ethane-1,2-diol	x	x	x
1,2-Propanediol	x	x	x
2,2'-oxydiethanol	x	x	x
2,2,4-trimethylpentane-1,3 -diol	x	x	x

[A] The Montreal Protocol on Substances that Deplete the Ozone Layer

[B] Stockholm Convention on Persistent Organic Pollutants (POPs)

[C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

European chemical inventory

Component	A	B	C	D	E	F	G	H	I
Acetonitrile	x	x	x	√	√	x	x	x	x
Methanol	x	x	√	√	√	√	x	x	x
Ethanol	x	x	x	√	√	x	x	x	x
Propan-1-ol	x	x	x	√	√	x	x	x	x
Propan-2-ol	x	x	x	√	√	x	x	x	x
Butan-1-ol	x	x	x	√	√	√	x	x	x
2-methylpropan-1- ol	x	x	x	√	√	√	x	x	x
Triethylamine	x	x	x	√	√	x	x	x	x
2-dimethylaminoet hanol	x	x	x	√	√	x	x	x	x
2-amino-2-methylp ropanol	x	x	x	√	√	x	x	x	x
Ethane-1,2-diol	x	x	x	√	√	x	x	x	x
1,2-Propanediol	x	x	x	√	√	x	x	x	x
2,2'-oxydiethanol	x	x	x	√	√	√	x	x	x
2,2,4-trimethylpent ane-1,3,2-diol	x	x	x	√	√	x	x	x	x

[A] Candidate list of Substances of Very High Concern for authorization under EU REACH regulation

[B] Substances requiring authorisation under EU REACH regulation

[C] Substances restricted under EU REACH

[D] Pre-registered substances under EU REACH

[E] Registered substances under EU REACH

[F] Substance Evaluation – CoRAP under EU REACH

[G] List of priority substances under EU water policy (Directive 2455/2001/EC)

[H] Substances subject to POPs Regulation

[I] Substances proposed as POPs

Note:

“√” Indicates that the substance included in the regulations.

“x” No data or not included in the regulations.

German water hazard class(WGK)

Component	WGK	Remark
Acetonitrile	WGK 2	
Methanol	WGK 2	
Ethanol	WGK 1	The assessment refers to pure ethanol. Denatured alcohol must be classified in accordance with Annex 1 No. 5 of the AwSV.
Propan-1-ol	WGK 1	
Propan-2-ol	WGK 1	
Butan-1-ol	WGK 1	
2-methylpropan-1-ol	WGK 1	
Triethylamine	WGK 1	
2-dimethylaminoethanol	WGK 1	
2-amino-2-methylpropanol	WGK 1	
Ethane-1,2-diol	WGK 1	The assessment refers to the unadditived substance. If additives are added, higher WGK are possible in accordance with the rules specified in Annex 1 No. 5 of the AwSV.
1,2-Propanediol	WGK 1	
2,2'-oxydiethanol	WGK 1	
2,2,4-trimethylpentane-1,3-diol	WGK 1	

【WGK 1】 slightly hazardous to water

【WGK 2】 obviously hazardous to water

【WGK 3】 highly hazardous to water

【nwg】 non-hazardous to water

【awg】 hazardous to water in general

German technical instructions on air quality control(TA LUFT)

Component	TA LUFT	Remark
Methanol	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
Ethanol	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5	

	Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Propan-1-ol	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Propan-2-ol	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Butan-1-ol	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
2-methylpropan-1-ol	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Triethylamine	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
2-dimethylaminoethanol	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
2-amino-2-methylpropanol	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not	

	allowed to exceed 1,5 kg/h.	
Ethane-1,2-diol	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
1,2-Propanediol	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
2,2'-oxydiethanol	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
2,2,4-trimethylpentane-1,3-diol	Chapter 5.2.5 Organic Substances, dust,including fine dust.To be treated as overall dust. The emissions of dust in the exhaust gas are not allowed to exceed the following values:Mass flow:0,20 kg/hr or Mass conc.:20 mg/m ³ The mass per unit volume of 0,15 g/m ³ in exhaust gas is not allowed to be exceeded also on observance or lower deviation of a mass flow of 0,20 kg/h.For emission sources that exceed the mass flow rate of 0.40 kg/h, the mass concentration in waste gas the mass concentration must not exceed 10 mg/m ³ .	

German technical rules for hazardous substances(TRGS)

Component	TRGS	Remark
Acetonitrile	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Methanol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS	

	721 TRGS 722 TRGS 723 TRGS 724	
Ethanol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Propan-1-ol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Propan-2-ol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 TRGS 906	
Butan-1-ol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
2-methylpropan-1-ol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Triethylamine	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
2-dimethylaminoethanol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
2-amino-2-methylpropanol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Ethane-1,2-diol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
1,2-Propanediol	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
2,2'-oxydiethanol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
2,2,4-trimethylpentane-1,3-diol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 500 TRGS 509 TRGS 510 TRGS 800	

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16 Other information

Information on revision

Creation Date	2025/12/31
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC _x	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P _{ow}	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor		

Disclaimer

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.