

Safety Data Sheet

18 Mix phthalates in hexane

Version : V2.0.0.1

Report No. : BWQ9776-2016-MSDS-EP

Creation Date : 2026/01/19

Revision Date : -



*Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name	18 Mix phthalates in hexane
Cat No.	BWQ9776-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable
REACH Registration Number	-
UFI	No information available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

1.4 Emergency telephone number

Emergency telephone number	010-58103678
Opening hours	24h

2 Hazards identification

2.1 CLP classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707

Flammable liquids	Category 2
Aspiration hazard	Category 1
Skin Corrosion/Irritation	Category 2
Specific target organ toxicity - single exposure; narcotic effects	Category 3

Reproductive toxicity	Category 2
Specific target organ toxicity - repeated exposure	Category 1
Hazardous to the aquatic environment - short-term (acute) hazard	Category 1
Hazardous to the aquatic environment - long-term (chronic) hazard	Category 2

2.2 Label elements

Hazard pictograms	
Signal word	Danger

Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361f	Suspected of damaging fertility
H372	Causes damage to organs through prolonged or repeated exposure(nervous system)
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
EUH208	Contains sensitising substance. May produce an allergic reaction

Precautionary statements

◆ Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

◆ Response

P312	Call a POISON CENTRE/ doctor/... if you feel unwell.
P314	Get medical advice/ attention if you feel unwell.
P321	Specific treatment (see related instructions on the label).
P331	Do NOT induce vomiting.
P391	Collect spillage.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].

◆ Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

◆ Disposal

P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
-------------	--

2.3 Other hazards

◆ Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
N-hexane	Not PBT/vPvB
Benzyl butyl phthalate	Not PBT/vPvB
Diphenyl phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-butoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
Dibutyl phthalate	Not PBT/vPvB
Dicyclohexyl phthalate	Not PBT/vPvB
Dimethyl phthalate	Not PBT/vPvB
Dipentyl phthalate	Insufficient information, temporarily unable to evaluate
Diethyl phthalate	Not PBT/vPvB
Diisobutyl phthalate	the substance is handled as if it were a PBT/vPvB
Dihexyl phthalate	Insufficient information, temporarily unable to evaluate
Diocetyl phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-methoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate

Bis(2-ethoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
BIS(4-METHYL-2-PENTYL) PHTHALATE	Insufficient information, temporarily unable to evaluate
Bis(2-ethylhexyl) phthalate	Not PBT/vPvB
Dinonyl phthalate	Insufficient information, temporarily unable to evaluate
Di-"isononyl" phthalate	Not PBT/vPvB
Diallyl phthalate	Insufficient information, temporarily unable to evaluate

◆ Results of endocrine disrupting properties assessment

Component	Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605]
N-hexane	Insufficient information, temporarily unable to evaluate
Benzyl butyl phthalate	Insufficient information, temporarily unable to evaluate
Diphenyl phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-butoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
Dibutyl phthalate	Insufficient information, temporarily unable to evaluate
Dicyclohexyl phthalate	ED
Dimethyl phthalate	Insufficient information, temporarily unable to evaluate
Dipentyl phthalate	Insufficient information, temporarily unable to evaluate
Diethyl phthalate	Insufficient information, temporarily unable to evaluate
Diisobutyl phthalate	Insufficient information, temporarily unable to evaluate
Dihexyl phthalate	Insufficient information, temporarily unable to evaluate
Dioctyl phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-methoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-ethoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
BIS(4-METHYL-2-PENTYL) PHTHALATE	Insufficient information, temporarily unable to evaluate
Bis(2-ethylhexyl) phthalate	Insufficient information, temporarily unable to evaluate
Dinonyl phthalate	Insufficient information, temporarily unable to evaluate
Di-"isononyl" phthalate	Insufficient information, temporarily unable to evaluate
Diallyl phthalate	Insufficient information, temporarily unable to evaluate

◆ Other

	Not applicable.
--	-----------------

3 Composition/information on ingredients

3.1 Substance

	Not applicable
--	----------------

3.2 Mixture

Component	Weight % content(or range)	Classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707 [CLP]	Specific Conc. Limits, M-factors
N-hexane CAS : 110-54-3 EC : 203-777-6 Index No. : 601-037-00-0	97.7266	Flammable liquids, Category 2, H225; Aspiration hazard, Category 1, H304; Skin Corrosion/Irritation, Category 2, H315; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 1, H372; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 2, H411	-
Benzyl butyl phthalate CAS : 85-68-7 EC : 201-622-7 Index No. : 607-430-00-3	0.1263	Reproductive toxicity, Category 1B, H360; Hazardous to the aquatic environment - short-term (acute) hazard, Category 1, H400; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 1, H410	-
Diphenyl phthalate CAS : 84-62-8 EC : 201-546-4 Index No. : -	0.1263	Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335; Hazardous to the aquatic environment - short-term (acute) hazard, Category 1, H400	-
Bis(2-butoxyethyl) phthalate CAS : 117-83-9 EC : 204-213-1 Index No. : -	0.1263	Serious eye damage/irritation, Category 2, H319	-
Dibutyl phthalate CAS : 84-74-2 EC : 201-557-4 Index No. : 607-318-00-4	0.1263	Reproductive toxicity, Category 1B, H360; Hazardous to the aquatic environment - short-term (acute) hazard, Category 1, H400	-
Dicyclohexyl phthalate CAS : 84-61-7 EC : 201-545-9 Index No. : 607-719-00-4	0.1263	Sensitization - skin, Category 1, H317; Reproductive toxicity, Category 1B, H360	-
Dimethyl phthalate CAS : 131-11-3 EC : 205-011-6 Index No. : -	0.1263	Serious eye damage/irritation, Category 2, H319	-
Dipentyl phthalate CAS : 131-18-0 EC : 205-017-9 Index No. : 607-426-00-1	0.1263	Reproductive toxicity, Category 1B, H360; Hazardous to the aquatic environment - short-term (acute) hazard, Category 1, H400	-
Diethyl phthalate CAS : 84-66-2 EC : 201-550-6 Index No. : -	0.1263	Specific target organ toxicity - repeated exposure, Category 2, H373	-
Diisobutyl phthalate CAS : 84-69-5 EC : 201-553-2 Index No. : 607-623-00-2	0.1263	Reproductive toxicity, Category 1B, H360	-
Dihexyl phthalate CAS : 84-75-3 EC : 201-559-5 Index No. : 607-702-00-1	0.1263	Reproductive toxicity, Category 1B, H360	-

Diocetyl phthalate CAS : 117-84-0 EC : 204-214-7 Index No. : -	0.1263	Reproductive toxicity, Category 2, H361	-
Bis(2-methoxyethyl) phthalate CAS : 117-82-8 EC : 204-212-6 Index No. : 607-228-00-5	0.1263	Reproductive toxicity, Category 1B, H360	-
Bis(2-ethoxyethyl) phthalate CAS : 605-54-9 EC : 210-090-5 Index No. : -	0.1263	Not Classified	-
BIS(4-METHYL-2-PENTYL)PHthalate CAS : 146-50-9 EC : - Index No. : -	0.1263	No information available	-
Bis(2-ethylhexyl) phthalate CAS : 117-81-7 EC : 204-211-0 Index No. : 607-317-00-9	0.1263	Reproductive toxicity, Category 1B, H360	-
Dinonyl phthalate CAS : 84-76-4 EC : 201-560-0 Index No. : -	0.1263	Acute Toxicity - Oral, Category 4, H302	-
Di-"isononyl" phthalate CAS : 28553-12-0 EC : 249-079-5 Index No. : -	0.1263	Not Classified	-
Diallyl phthalate CAS : 131-17-9 EC : 205-016-3 Index No. : 607-086-00-4	0.1263	Acute Toxicity - Oral, Category 4, H302; Hazardous to the aquatic environment - short-term (acute) hazard, Category 1, H400; Hazardous to the aquatic environment - long-term (chronic) hazard, Category 1, H410	-

4 First-aid measures

4.1 Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse and then wash skin with water and soap. Refer for medical attention.
Ingestion	Rinse mouth. Do NOT induce vomiting. Rest. Refer for medical attention.
Inhalation	Fresh air, rest. Refer for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

4.2 Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

4.3 Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
Unsuitable extinguishing media	Use of water spray when fighting fire may be inefficient.

5.2 Specific hazards arising from the substance or mixture

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
4	Liquid and vapour are flammable.
5	Development of hazardous combustion gases or vapor possible in the event of fire.
6	May expansion or decompose explosively when heated or involved in fire.

5.3 Advice for firefighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

1	Avoid breathing vapours and contacting with skin and eye.
2	Beware of vapours accumulating to form explosive concentrations.
3	Vapours can accumulate in low areas.
4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
6	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
7	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

1	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
2	In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
3	In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to

	reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Cut off the source of the leak as much as possible.
9	Keep leaks in a ventilated place.
10	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
11	Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
12	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
13	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4 Reference to other sections

1	Personal Protective Equipment advice is contained in Section 8 of the SDS.
2	Disposal considerations advice is contained in Section 13 of the SDS.

7 Handling and storage

7.1 Precautions for safe handling

◆ Protective measures

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.

◆ Measures to prevent fire

1	Use only non-sparking tools.
2	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
3	Use explosion proof equipment.
4	Keep away from heat/sparks/open flames/ hot surfaces.

◆ Measures to prevent aerosol and dust generation

1	Not applicable.
---	-----------------

◆ Advice on general occupational hygiene

1	Wash hands and face after using the substances.
2	Replace the contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

7.3 Specific end use(s)

1	In addition to use mentioned in the Section 1.2, unforeseen other specific end uses.
---	--

8 Exposure controls/personal protection

8.1 Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m ³	ppm	mg/m ³
N-hexane	Japan - JSOH(2024–2025)	40	140	-	-
	Permissible exposure standards for workers in the workplace	50	176	75	220
	European Union	20	72	-	-
	France	20	72	-	-
	Germany (AGS)	50	180	400	1440
	Germany (DFG)	50	180	400	1440
Benzyl butyl phthalate	Germany (AGS)	-	20	-	40
	Germany (DFG)	-	20	-	40
	United Kingdom	-	5	-	-
	Austria	-	3	-	5
	Denmark	-	3	-	6
	New Zealand	-	5	-	-
Dibutyl phthalate	Japan - JSOH(2024–2025)	-	5	-	-
	Permissible exposure standards for workers in the workplace	-	5	-	10
	France	-	5	-	-
	Germany (AGS)	0.05	0.58	0.1	1.16
	Germany (DFG)	0.05	0.58	0.1	1.16
	United Kingdom	-	5	-	10
Dicyclohexyl phthalate	United Kingdom	-	5	-	-
	Austria	-	5	-	-
	Denmark	-	3	-	6
	Ireland	-	5	-	-
	New Zealand	-	5	-	-
Dimethyl phthalate	Permissible exposure standards for workers in the workplace	-	5	-	10

	France	-	5	-	-
	United Kingdom	-	5	-	10
	Belgium	-	5	-	-
	Denmark	-	3	-	6
	Finland	-	5	-	10
Diethyl phthalate	Japan - JSOH(2024–2025)	-	5	-	-
	Permissible exposure standards for workers in the workplace	-	5	-	10
	France	-	5	-	-
	United Kingdom	-	5	-	10
	Austria	-	3	-	5
	Belgium	-	5	-	-
Diisobutyl phthalate	United Kingdom	-	5	-	-
	Denmark	-	3	-	6
	Ireland	-	5	-	-
	Latvia	-	1	-	-
	New Zealand	-	5	-	-
Dioctyl phthalate	Austria	-	5	-	-
	Norway	-	3	-	-
	Romania	0.1	2	0.3	5
	Sweden	-	3	-	5
	Singapore	-	5	-	-
Bis(2-ethylhexyl) phthalate	Japan - JSOH(2024–2025)	-	5	-	-
	Permissible exposure standards for workers in the workplace	-	5	-	10
	France	-	5	-	-
	Germany (AGS)	-	2	-	4
	Germany (DFG)	-	2	-	4
	United Kingdom	-	5	-	10
Dinonyl phthalate	United Kingdom	-	5	-	-
	Austria	-	5	-	-
	Ireland	-	5	-	-
	Latvia	-	1	-	-
	New Zealand	-	5	-	-

Di-"isononyl" phthalate	United Kingdom	-	5	-	-
	Denmark	-	3	-	6
	Ireland	-	5	-	-
	New Zealand	-	5	-	-
Diallyl phthalate	United Kingdom	-	5	-	-
	Austria	-	5	-	-
	Denmark	-	3	-	6
	Ireland	-	5	-	-
	Latvia	-	1	-	-
	New Zealand	-	5	-	-

◆ Biological limit values

Component	Standard	Biological monitoring index	Biological limits value	Sampling time	Remark
N-hexane	USA -ACGIH	2,5-Hexanedione, without hydrolysis(Urine)	0.5mg/L	End of shift	
Bis(2-ethylhexyl) phthalate	USA -ACGIH	Mono(2-ethylhexyl)phthalate(Creatinine in urine)	5µg/g	End of shift	
		Mono(2-ethyl-5-hydroxyhexyl)phthalate(Creatinine in urine)	20µg/g	End of shift	
		Mono(2-ethyl-5-oxohexyl)phthalate(Creatinine in urine)	15µg/g	End of shift	
		Mono(2-ethyl-5-carboxypentyl)phthalate(Creatinine in urine)	25µg/g	End of shift	

◆ Monitoring methods

1	EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
2	GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.

◆ Derived No effect level (DNEL)

Component	Route of exposure	DNEL for Workers			
		Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
N-hexane	Inhalation	No data available	No data available	No data available	75 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Benzyl butyl phthalate	Inhalation	No data available	No data available	No data available	4.36 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

[illegible]

PENTYL)PHTHALATE	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Bis(2-ethylhexyl) phthalate	Inhalation	No data available	No data available	No data available	1.6 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Dinonyl phthalate	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Di-"isononyl" phthalate	Inhalation	No data available	No data available	No data available	18.8 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Diallyl phthalate	Inhalation	No data available	No data available	No data available	3.52 mg/m3
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

◆ Predicted No Effect Concentration (PNEC)

Component	A	B	C	D	E	F	G	H
N-hexane	No data available	No data available	No data available	No data available	No data available	No hazard identified	No data available	No potential for bioaccumulation
Benzyl butyl phthalate	7.5 µg/L	750 ng/L	20 mg/L	7.89 mg/kg sediment dw	789 µg/kg sediment dw	No data available	1.57 mg/kg soil dw	100 mg/kg food
Dibutyl phthalate	10 µg/L	1 µg/L	220 µg/L	1.19 mg/kg sediment dw	119 µg/kg sediment dw	No hazard identified	50 µg/kg soil dw	1.33 mg/kg food
Dicyclohexyl phthalate	1.04 µg/L	104 ng/L	10 mg/L	1.06 mg/kg sediment dw	110 µg/kg sediment dw	No hazard identified	310 µg/kg soil dw	133 g/kg food
Dimethyl phthalate	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Diethyl phthalate	12 µg/L	1.2 µg/L	2 mg/L	137 µg/kg sediment dw	13.7 µg/kg sediment dw	No hazard identified	137 µg/kg soil dw	33 mg/kg food
Diisobutyl phthalate	1 µg/L	100 ng/L	1.45 mg/L	118 µg/kg sediment dw	11.8 µg/kg sediment dw	No hazard identified	23.1 µg/kg soil dw	No potential for bioaccumulation
Bis(2-ethylhexyl) phthalate	No hazard identified	No hazard identified	201 mg/L	100 mg/kg sediment dw	20 mg/kg sediment dw	No hazard identified	13 mg/kg soil dw	3.3 mg/kg food

Di-"isononyl" phthalate	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	30 mg/kg soil dw	No potential for bioaccumulation
Diallyl phthalate	2.3 µg/L	23 ng/L	22 mg/L	0.154 ng/kg sediment dw	0.002 ng/kg sediment dw	No hazard identified	1.77 µg/kg soil dw	No potential for bioaccumulation

Note 1:

A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).

Note 2:

The PNEC values of the remaining components not shown in the product are not available yet.

8.2 Exposure controls

8.2.1 Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

8.2.2 Personal protection equipment

General requirement	    
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear anti static chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

8.2.3 Environmental exposure controls

Environmental exposure controls	No information available
---------------------------------	--------------------------

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Clear, colorless liquid
Colour	Clear, colorless liquid
Odor	No information available
Odor threshold	No information available
pH	No information available
Melting point/freezing point(°C)	-95 (N-hexane)
Initial boiling point and boiling range(°C)	69 (N-hexane)
Flash point(Closed cup,°C)	-22 (N-hexane)
Evaporation rate	No information available

Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit : 7.5 (N-hexane); Lower limit : 1.1 (N-hexane)
Vapor pressure	17kPa (20°C,N-hexane)
Vapor density(Air = 1)	3.0 (N-hexane)
Relative density(Water=1)	0.66~0.68 (20 °C,N-hexane)
Solubility	Insoluble in water (N-hexane)
n-octanol/water partition coefficient	3.9 (N-hexane)
Auto-ignition temperature(°C)	225 (N-hexane)
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Particle characteristics	Not applicable

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Information with regard to physical hazard classes	No information available
---	--------------------------

9.2.2 Other safety characteristics

Other safety characteristics	No information available
-------------------------------------	--------------------------

10 Stability and reactivity

Stability and reactivity

10.1 Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
10.2 Chemical stability	Stable under proper operation and storage conditions.
10.3 Possibility of hazardous reactions	In contact with an open flame may cause a fire or explosion.
10.4 Conditions to avoid	Incompatible materials, heat, flame and spark.
10.5 Incompatible materials	Oxidantss and halogen.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

18 Mix phthalates in hexane	
Skin corrosion/irritation	Causes skin irritation(Category 2)
Serious eye damage/irritation	Based on available data, the classification criteria are not met
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Suspected of damaging fertility(Category 2)
STOT-single exposure	May cause drowsiness or dizziness(Category 3)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure(nervous

	system)(Category 1)
Aspiration hazard	May be fatal if swallowed and enters airways(Category 1)
Germ cell mutagenicity	Based on available data, the classification criteria are not met

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Dibutyl phthalate	7499mg/kg(Rat)	> 20900mg/kg(Rabbit)	No information available
Dioctyl phthalate	47000mg/kg(Rat)	No information available	No information available
N-hexane	25000mg/kg(Rat)	No information available	169.188mg/L(Rat)
Diethyl phthalate	8600mg/kg(Rat)	No information available	No information available
Diphenyl phthalate	8000mg/kg(Rat)	No information available	No information available
Dimethyl phthalate	8200mg/kg(Rat)	> 23800mg/kg(Rabbit)	No information available
Dinonyl phthalate	21500mg/kg(Mouse)	No information available	No information available
Diisobutyl phthalate	15000mg/kg(Rat)	No information available	No information available
Benzyl butyl phthalate	2330mg/kg(Rat)	> 10000mg/kg(Rabbit)	No information available
Bis(2-methoxyethyl) phthalate	3200mg/kg(Mouse)	No information available	No information available
Bis(2-butoxyethyl) phthalate	8380mg/kg(Rat)	No information available	No information available
Diallyl phthalate	656mg/kg(Rat)	3300mg/kg(Rabbit)	No information available
Dicyclohexyl phthalate	34400mg/kg(Rat)	No information available	No information available
Dihexyl phthalate	29600mg/kg(Rat)	No information available	No information available
Bis(2-ethylhexyl) phthalate	30000mg/kg(Rat)	25000mg/kg(Rabbit)	No information available

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP
N-hexane	Not Listed	Not Listed
Benzyl butyl phthalate	Category 3	Not Listed
Diphenyl phthalate	Not Listed	Not Listed
Bis(2-butoxyethyl) phthalate	Not Listed	Not Listed
Dibutyl phthalate	Not Listed	Not Listed
Dicyclohexyl phthalate	Not Listed	Not Listed
Dimethyl phthalate	Not Listed	Not Listed
Dipentyl phthalate	Not Listed	Not Listed
Diethyl phthalate	Not Listed	Not Listed
Diisobutyl phthalate	Not Listed	Not Listed
Dihexyl phthalate	Not Listed	Not Listed
Dioctyl phthalate	Not Listed	Not Listed
Bis(2-methoxyethyl) phthalate	Not Listed	Not Listed

Bis(2-ethoxyethyl) phthalate	Not Listed	Not Listed
BIS(4-METHYL-2-PENTYL) PHTHALATE	Not Listed	Not Listed
Bis(2-ethylhexyl) phthalate	Category 2B	Category R
Dinonyl phthalate	Not Listed	Not Listed
Di-"isononyl" phthalate	Not Listed	Not Listed
Diallyl phthalate	Not Listed	Not Listed

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Component	Endocrine disrupting properties
N-hexane	No information available
Benzyl butyl phthalate	No information available
Diphenyl phthalate	No information available
Bis(2-butoxyethyl) phthalate	No information available
Dibutyl phthalate	No information available
Dicyclohexyl phthalate	This substance causes developmental toxicity in male reproductive organs in the absence of marked maternal toxicity. A plausible mechanistic link between the toxic effects of concern and endocrine disruption (an anti-androgenic mode of action) is consider.
Dimethyl phthalate	No information available
Dipentyl phthalate	No information available
Diethyl phthalate	No information available
Diisobutyl phthalate	No information available
Dihexyl phthalate	No information available
Dioctyl phthalate	No information available
Bis(2-methoxyethyl) phthalate	No information available
Bis(2-ethoxyethyl) phthalate	No information available
BIS(4-METHYL-2-PENTYL) PHTHALATE	No information available
Bis(2-ethylhexyl) phthalate	No information available
Dinonyl phthalate	No information available
Di-"isononyl" phthalate	No information available
Diallyl phthalate	No information available

11.2.2 Other Information

Other Information	See Section 11.1
-------------------	------------------

12 Ecological information

12.1 Toxicity

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Dibutyl phthalate	LC ₅₀ : 1.51mg/L (96h)(Fish)	EC ₅₀ : 2.99mg/L (48h)(Crustaceans)	ErC ₅₀ : 0.4mg/L (96h)(Algae)
Diocetyl phthalate	LC ₅₀ : >20mg/L (96h)(Fish)	EC ₅₀ : >0.00067mg/L (48h)(Crustaceans)	ErC ₅₀ : >20mg/L (72h)(Algae)
Dimethyl phthalate	LC ₅₀ : 39mg/L (96h)(Fish)	EC ₅₀ : 45.9mg/L (48h)(Crustaceans)	ErC ₅₀ : 35.8mg/L (96h)(Algae)
Diisobutyl phthalate	LC ₅₀ : 3.0mg/L (96h)(Fish)	EC ₅₀ : 6.7mg/L (48h)(Crustaceans)	ErC ₅₀ : 1.8mg/L (72h)(Algae)
N-hexane	LC ₅₀ : 57.8mg/L (96h)(Fish)	No information available	No information available
Benzyl butyl phthalate	LC ₅₀ : >1.1mg/L (96h)(Fish)	EC ₅₀ : 1.8mg/L (48h)(Crustaceans)	ErC ₅₀ : 0.11mg/L (96h)(Algae)
Diethyl phthalate	LC ₅₀ : 12mg/L (96h)(Fish)	EC ₅₀ : 86mg/L (48h)(Crustaceans)	ErC ₅₀ : 45.2mg/L (96h)(Algae)
Diallyl phthalate	LC ₅₀ : 0.23mg/L (96h)(Fish)	EC ₅₀ : 5.5mg/L (48h)(Crustaceans)	ErC ₅₀ : 4.5mg/L (96h)(Algae)
Dicyclohexyl phthalate	LC ₅₀ : 2mg/L (96h)(Fish)	EC ₅₀ : >2.0mg/L (48h)(Crustaceans)	ErC ₅₀ : >2.0mg/L (72h)(Algae)
Bis(2-ethylhexyl) phthalate	LC ₅₀ : 75mg/L (96h)(Fish)	EC ₅₀ : >100mg/L (48h)(Crustaceans)	ErC ₅₀ : >100mg/L (72h)(Algae)

Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Dibutyl phthalate	NOEC : 1.1mg/L(Fish)	NOEC : 0.33mg/L(Crustaceans)	NOEC : 0.3mg/L(Algae)
Diocetyl phthalate	No information available	NOEC : >0.00061mg/L(Crustaceans)	NOEC : 20mg/L(Algae)
Diisobutyl phthalate	NOEC : 0.39mg/L(Fish)	NOEC : 0.27mg/L(Crustaceans)	NOEC : 0.37mg/L(Algae)
Benzyl butyl phthalate	No information available	NOEC : 0.52mg/L(Crustaceans)	No information available
Diallyl phthalate	No information available	NOEC : 4.3mg/L(Crustaceans)	NOEC : 2.4mg/L(Algae)
Dicyclohexyl phthalate	No information available	NOEC : 0.18mg/L(Crustaceans)	NOEC : 2.0mg/L(Algae)
Bis(2-ethylhexyl) phthalate	No information available	NOEC : 10mg/L(Crustaceans)	NOEC : 100mg/L(Algae)

12.2 Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
N-hexane	Low	Low
Benzyl butyl phthalate	High(Half-life = 180 days)	Low(Half-life = 2.5 days)
Bis(2-butoxyethyl) phthalate	Low	Low

Dicyclohexyl phthalate	High	High
Dimethyl phthalate	Low(Half-life = 14 days)	Low(Half-life = 46.58 days)
Dipentyl phthalate	Low	Low
Diethyl phthalate	Media(Half-life = 112 days)	Low(Half-life = 8.83 days)
Diisobutyl phthalate	Low	Low
Dihexyl phthalate	Low	Low
Diethyl phthalate	High(Half-life = 365 days)	Low(Half-life = 1.87 days)
Bis(2-methoxyethyl) phthalate	Low	Low
Bis(2-ethylhexyl) phthalate	High(Half-life = 389 days)	Low(Half-life = 1.21 days)
Dinonyl phthalate	Low	Low
Di-"isononyl" phthalate	High	High
Diallyl phthalate	Low	Low

12.3 Bioaccumulative potential

Component	Bioaccumulative potential	Comments
N-hexane	Medium	Log Kow=3.9
Benzyl butyl phthalate	Medium	BCF=663
Bis(2-butoxyethyl) phthalate	Medium	Log Kow=4.0612
Dicyclohexyl phthalate	High	Log Kow=5.6
Dimethyl phthalate	Low	BCF=57
Dipentyl phthalate	High	Log Kow=5.62
Diethyl phthalate	Low	BCF=117
Diisobutyl phthalate	Medium	BCF=780
Dihexyl phthalate	High	Log Kow=6.82
Diethyl phthalate	Low	Log Kow=8.1
Bis(2-methoxyethyl) phthalate	Low	Log Kow=1.1146
Bis(2-ethylhexyl) phthalate	High	BCF=24500
Dinonyl phthalate	Low	Log Kow=9.521
Di-"isononyl" phthalate	Low	BCF=183.8
Diallyl phthalate	Low	Log Kow=3.23

12.4 Mobility in soil

Component	log Koc	Remark
N-hexane	$\geq 2.37 - \leq 3.16$	20 °C , pH=7.0
Benzyl butyl phthalate	3.971	
Bis(2-butoxyethyl)	2.231	

phthalate		
Dibutyl phthalate	3.14	
Dicyclohexyl phthalate	3.46	20 °C
Dimethyl phthalate	1.569	
Dipentyl phthalate	3.696	
Diethyl phthalate	2.34	20 °C
Diisobutyl phthalate	3.06	20 °C
Dihexyl phthalate	4.228	
Diethyl phthalate	5.291	
Bis(2-methoxyethyl) phthalate	1.000	
Bis(2-ethylhexyl) phthalate	5.219	
Dinonyl phthalate	5.823	
Di-"isononyl" phthalate	0.78	20 °C
Diallyl phthalate	2.63	20 °C

12.5 Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
N-hexane	Not PBT/vPvB
Benzyl butyl phthalate	Not PBT/vPvB
Diphenyl phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-butoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
Dibutyl phthalate	Not PBT/vPvB
Dicyclohexyl phthalate	Not PBT/vPvB
Dimethyl phthalate	Not PBT/vPvB
Dipentyl phthalate	Insufficient information, temporarily unable to evaluate
Diethyl phthalate	Not PBT/vPvB
Diisobutyl phthalate	the substance is handled as if it were a PBT/vPvB
Dihexyl phthalate	Insufficient information, temporarily unable to evaluate
Diethyl phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-methoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
Bis(2-ethoxyethyl) phthalate	Insufficient information, temporarily unable to evaluate
BIS(4-METHYL-2-PENTYL) PHTHALATE	Insufficient information, temporarily unable to evaluate
Bis(2-ethylhexyl) phthalate	Not PBT/vPvB
Dinonyl phthalate	Insufficient information, temporarily unable to evaluate
Di-"isononyl" phthalate	Not PBT/vPvB

Diallyl phthalate	Insufficient information, temporarily unable to evaluate
-------------------	--

12.6 Endocrine disrupting properties

Component	Endocrine disrupting properties
N-hexane	No information available
Benzyl butyl phthalate	No information available
Diphenyl phthalate	No information available
Bis(2-butoxyethyl) phthalate	No information available
Dibutyl phthalate	No information available
Dicyclohexyl phthalate	This substance is classified as an environmental endocrine disruptor, but detailed assessment data is not yet publicly available.
Dimethyl phthalate	No information available
Dipentyl phthalate	No information available
Diethyl phthalate	No information available
Diisobutyl phthalate	No information available
Dihexyl phthalate	No information available
Dioctyl phthalate	No information available
Bis(2-methoxyethyl) phthalate	No information available
Bis(2-ethoxyethyl) phthalate	No information available
BIS(4-METHYL-2-PENTYL) PHTHALATE	No information available
Bis(2-ethylhexyl) phthalate	No information available
Dinonyl phthalate	No information available
Di-"isononyl" phthalate	No information available
Diallyl phthalate	No information available

12.7 Other adverse effects

	No information available
--	--------------------------

13 Disposal considerations

13.1 Waste treatment methods

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label	
--------------------	---

IMDG-CODE

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	Yes

IATA-DGR

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	Yes

UN-ADR

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	Yes

Special precautions for user

	Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.
--	--

Maritime transport in bulk according to IMO instruments

- ◆ Transport in bulk according to Annex II of MARPOL and the IBC code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with the IGC Code

Not Available

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International chemical inventory

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
N-hexane	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Benzyl butyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Diphenyl phthalate	✗	✓	✓	✗	✗	✗	✓	✓	✓	✗	✗	✓	✓
Bis(2-butoxyethyl) phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✓
Dibutyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dicyclohexyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dimethyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dipentyl phthalate	✓	✓	✓	✓	✓	✗	✓	✗	✗	✗	✗	✓	✓
Diethyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Diisobutyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dihexyl phthalate	✓	✓	✓	✓	✓	✗	✓	✓	✓	✗	✗	✓	✓
Diocetyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Bis(2-methoxyethyl) phthalate	✓	✓	✓	✓	✗	✗	✗	✓	✓	✗	✗	✓	✓
Bis(2-ethoxyethyl) phthalate	✗	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓
BIS(4-METHYL-2-PENTYL) PHTHALATE	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗	✗	✓	✓
Bis(2-ethylhexyl) phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dinonyl phthalate	✓	✓	✓	✓	✓	✗	✓	✓	✓	✗	✗	✓	✓
Di-"isononyl" phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Diallyl phthalate	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

- [A] China Inventory of Existing Chemical Substances(IECSC)
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
 [C] United States Toxic Substances Control Act Inventory(TSCA)
 [D] Canadian Domestic Substances List(DSL)
 [E] New Zealand Inventory of Chemicals(NZIoC)
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
 [G] Korea Existing Chemicals Inventory(KECL)
 [H] Australian. Inventory of Industrial Chemical (AIICS)
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)
 [J] Thailand Existing Chemicals Inventory(TECI)
 [K] Mexico National Inventory of Chemical Substances (INSQ)
 [L] Russia Inventory of Existing Substances(DRAFT)
 [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	B	C
-----------	---	---	---

N-hexane	×	×	×
Benzyl butyl phthalate	×	×	×
Diphenyl phthalate	×	×	×
Bis(2-butoxyethyl) phthalate	×	×	×
Dibutyl phthalate	×	×	×
Dicyclohexyl phthalate	×	×	×
Dimethyl phthalate	×	×	×
Dipentyl phthalate	×	×	×
Diethyl phthalate	×	×	×
Diisobutyl phthalate	×	×	×
Dihexyl phthalate	×	×	×
Dioctyl phthalate	×	×	×
Bis(2-methoxyethyl) phthalate	×	×	×
Bis(2-ethoxyethyl) phthalate	×	×	×
BIS(4-METHYL-2-PENTYL)PHTHALATE	×	×	×
Bis(2-ethylhexyl) phthalate	×	×	×
Dinonyl phthalate	×	×	×
Di-"isononyl" phthalate	×	×	×
Diallyl phthalate	×	×	×

【A】 The Montreal Protocol on Substances that Deplete the Ozone Layer

【B】 Stockholm Convention on Persistent Organic Pollutants (POPs)

【C】 Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

European chemical inventory

Component	A	B	C	D	E	F	G	H	I
N-hexane	×	×	×	✓	✓	✓	×	×	×
Benzyl butyl phthalate	✓	✓	✓	✓	✓	×	×	×	×
Diphenyl phthalate	×	×	×	✓	×	×	×	×	×
Bis(2-butoxyethyl) phthalate	×	×	×	✓	×	×	×	×	×
Dibutyl phthalate	✓	✓	✓	✓	✓	×	×	×	×
Dicyclohexyl phthalate	✓	×	✓	✓	✓	✓	×	×	×
Dimethyl phthalate	×	×	×	✓	✓	×	×	×	×
Dipentyl phthalate	✓	✓	✓	✓	×	×	×	×	×
Diethyl phthalate	×	×	×	✓	✓	✓	×	×	×
Diisobutyl phthalate	✓	✓	✓	✓	✓	×	×	×	×
Dihexyl phthalate	✓	✓	✓	✓	×	×	×	×	×

Diethyl phthalate	×	×	✓	✓	×	×	×	×	×
Bis(2-methoxyethyl) phthalate	✓	✓	✓	✓	×	×	×	×	×
Bis(2-ethoxyethyl) phthalate	×	×	×	✓	×	×	×	×	×
BIS(4-METHYL-2-PENTYL)PHTHALATE	×	×	×	×	×	×	×	×	×
Bis(2-ethylhexyl) phthalate	✓	✓	✓	✓	✓	×	✓	×	×
Dinonyl phthalate	×	×	×	✓	×	×	×	×	×
Di-"isononyl" phthalate	×	×	✓	✓	✓	×	×	×	×
Diallyl phthalate	×	×	×	✓	✓	✓	×	×	×

- [A] Candidate list of Substances of Very High Concern for authorization under EU REACH regulation
[B] Substances requiring authorisation under EU REACH regulation
[C] Substances restricted under EU REACH
[D] Pre-registered substances under EU REACH
[E] Registered substances under EU REACH
[F] Substance Evaluation – CoRAP under EU REACH
[G] List of priority substances under EU water policy (Directive 2455/2001/EC)
[H] Substances subject to POPs Regulation
[I] Substances proposed as POPs

Note:

- “✓” Indicates that the substance included in the regulations.
“×” No data or not included in the regulations.

German water hazard class(WGK)

Component	WGK	Remark
N-hexane	WGK 3	
Benzyl butyl phthalate	WGK 3	
Dibutyl phthalate	WGK 3	
Dicyclohexyl phthalate	WGK 1	
Dimethyl phthalate	WGK 1	
Dipentyl phthalate	WGK 3	
Diethyl phthalate	WGK 2	
Diisobutyl phthalate	WGK 3	
Diethyl phthalate	WGK 1	
Bis(2-methoxyethyl) phthalate	WGK 1	
Bis(2-ethylhexyl) phthalate	WGK 1	
Dinonyl phthalate	WGK 1	
Di-"isononyl" phthalate	WGK 1	
Diallyl phthalate	WGK 3	

- 【WGK 1】 slightly hazardous to water
【WGK 2】 obviously hazardous to water
【WGK 3】 highly hazardous to water
【nwg】 non-hazardous to water
【awg】 hazardous to water in general

German technical instructions on air quality control(TA LUFT)

Component	TA LUFT	Remark
N-hexane	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas:Mass flow:0,10 kg/hr or Mass conc.:20 mg/m ³	
Benzyl butyl phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Dibutyl phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Dicyclohexyl phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Dimethyl phthalate	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Dipentyl phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Diethyl phthalate	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Diisobutyl phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Dihexyl phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Dioctyl phthalate	Chapter 5.2.5 Organic Substances.The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas:Mass flow:0,50 kg/hr or Mass conc.:50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Bis(2-methoxyethyl) phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or Mass conc.: 1 mg/m ³	
Bis(2-ethylhexyl) phthalate	Chapter 5.2.7.1.3 Substances toxic to reproductionMass flow: 2,5 g/hr or	

	Mass conc.: 1 mg/m ³	
Dinonyl phthalate	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Di-"isononyl" phthalate	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	
Diallyl phthalate	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	

German technical rules for hazardous substances (TRGS)

Component	TRGS	Remark
N-hexane	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Benzyl butyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Dibutyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 402 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Dicyclohexyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724 TRGS 560	
Dimethyl phthalate	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Dipentyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	

Diethyl phthalate	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Diisobutyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Dihexyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Dioctyl phthalate	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Bis(2-methoxyethyl) phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Bis(2-ethylhexyl) phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Dinonyl phthalate	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Di-"isononyl" phthalate	TRGS 500 TRGS 509 TRGS 510 TRGS 800	
Diallyl phthalate	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800	

15.2 Chemical safety assessment

	No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.
--	--

16 Other information

Information on revision

Creation Date	2026/01/19
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association

NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC _x	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P _{ow}	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor		

Disclaimer

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.