

Tetrabutylammonium hydroxide titration solution



Version : V2.0.0.1

Report No. : BWZ8356-2016-MSDS-EP

Creation Date : 2026/01/10

Revision Date : -

***Prepared in accordance with EU REACH Regulation (REACH 1907/2006 with amendment 2020/878)**

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name	Tetrabutylammonium hydroxide titration solution
Cat No.	BWZ8356-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable
REACH Registration Number	-
UFI	No information available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

1.3 Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

1.4 Emergency telephone number

Emergency telephone number	010-58103678
Opening hours	24h

2 Hazards identification

2.1 CLP classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Aspiration hazard	Category 1
Acute Toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1B

Sensitization - skin	Category 1
Serious eye damage/irritation	Category 1
Acute Toxicity - Inhalation	Category 4
Specific target organ toxicity - single exposure; narcotic effects	Category 3
Reproductive toxicity	Category 2
Specific target organ toxicity - single exposure	Category 1
Specific target organ toxicity - repeated exposure	Category 2

2.2 Label elements

Hazard pictograms	
Signal word	Danger

Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary statements

◆ Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.

P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

◆ Response

P310	Immediately call a POISON CENTER/doctor.
P314	Get medical advice/ attention if you feel unwell.
P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P363	Wash contaminated clothing before reuse.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

◆ Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

◆ Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

2.3 Other hazards

◆ Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Methanol	Not PBT/vPvB
Toluene	Not PBT/vPvB
Tetrabutylammonium hydroxide	Not PBT/vPvB
Silver (II) oxide	Insufficient information, temporarily unable to evaluate

◆ Results of endocrine disrupting properties assessment

Component	Results of endocrine disrupting properties assessment [according to (EU) No 2017/2100 or (EU) No 2018/605]
Methanol	Insufficient information, temporarily unable to evaluate
Toluene	Insufficient information, temporarily unable to evaluate
Tetrabutylammonium hydroxide	Insufficient information, temporarily unable to evaluate
Silver (II) oxide	Insufficient information, temporarily unable to evaluate

◆ Other

	Not applicable.
--	-----------------

3 Composition/information on ingredients

3.1 Substance

	Not applicable
--	----------------

3.2 Mixture

Component	Weight % content(or range)	Classification according to Regulation (EC) No. 1272/2008 with amendment 2023/707 [CLP]	Specific Conc. Limits, M-factors
Methanol CAS : 67-56-1 EC : 200-659-6 Index No. : 603-001-00-X	22.375	Flammable liquids, Category 2, H225; Acute Toxicity - Oral, Category 3, H301; Acute Toxicity - Dermal, Category 3, H311; Acute Toxicity - Inhalation, Category 3, H331; Specific target organ toxicity - single exposure, Category 1, H370	H370:C ≥ 10% H371:3% ≤ C < 10%
Toluene CAS : 108-88-3 EC : 203-625-9 Index No. : 601-021-00-3	67.125	Flammable liquids, Category 2, H225; Aspiration hazard, Category 1, H304; Skin Corrosion/Irritation, Category 2, H315; Specific target organ toxicity - single exposure; narcotic effects, Category 3, H336; Reproductive toxicity, Category 2, H361; Specific target organ toxicity - repeated exposure, Category 2, H373	-
Tetrabutylammonium hydroxide CAS : 2052-49-5 EC : 218-147-6 Index No. : -	6	Flammable liquids, Category 3, H226; Acute Toxicity - Oral, Category 4, H302; Skin corrosion/irritation, Category 1B, H314; Sensitization - skin, Category 1, H317; Serious eye damage/irritation, Category 1, H318	-
Silver (II) oxide CAS : 1301-96-8 EC : 215-098-2 Index No. : -	4.5	Oxidizing solids, Category 2, H272; Skin Corrosion/Irritation, Category 2, H315; Serious eye damage/irritation, Category 2, H319; Specific target organ toxicity - single exposure; respiratory tract irritation, Category 3, H335	-

4 First-aid measures

4.1 Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily

	possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse and then wash skin with water and soap. Refer for medical attention.
Ingestion	Rinse mouth. Do NOT induce vomiting. Refer for medical attention.
Inhalation	Fresh air, rest. Refer for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

4.2 Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

4.3 Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
Unsuitable extinguishing media	Use of water spray when fighting fire may be inefficient.

5.2 Specific hazards arising from the substance or mixture

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
4	Liquid and vapour are flammable.
5	Development of hazardous combustion gases or vapor possible in the event of fire.
6	May expansion or decompose explosively when heated or involved in fire.

5.3 Advice for firefighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

1	Avoid breathing vapours and contacting with skin and eye.
2	Beware of vapours accumulating to form explosive concentrations.
3	Vapours can accumulate in low areas.
4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Use personal protective equipment, do not breathe gas/mist/vapour/spray.

6	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
7	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

1	It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
2	In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
3	In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Cut off the source of the leak as much as possible.
9	Keep leaks in a ventilated place.
10	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
11	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
12	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
13	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4 Reference to other sections

1	Personal Protective Equipment advice is contained in Section 8 of the SDS.
2	Disposal considerations advice is contained in Section 13 of the SDS.

7 Handling and storage

7.1 Precautions for safe handling

◆ Protective measures

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.

◆ Measures to prevent fire

1	Use only non-sparking tools.
2	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
3	Use explosion proof equipment.
4	Keep away from heat/sparks/open flames/ hot surfaces.

◆ Measures to prevent aerosol and dust generation

1	Not applicable.
---	-----------------

◆ Advice on general occupational hygiene

1	Wash hands and face after using the substances.
2	Replace the contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

7.3 Specific end use(s)

1	In addition to use mentioned in the Section 1.2, unforeseen other specific end uses.
---	--

8 Exposure controls/personal protection

8.1 Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m ³	ppm	mg/m ³
Methanol	Japan - JSOH(2024-2025)	200	260	-	-
	Permissible exposure standards for workers in the workplace	200	262	250	327.5
	European Union	200	260	-	-
	France	200	260	-	-
	Germany (AGS)	100	130	200	260
	Germany (DFG)	100	130	200	260
Toluene	Japan - JSOH(2024-2025)	50	188	-	-
	Permissible exposure standards for workers in the workplace	50	188	75	235
	European Union	50	192	100	384
	France	20	76.8	100	384
	Germany (AGS)	50	190	100	380
	Germany (DFG)	50	190	100	380
Silver (II) oxide	Japan - JSOH(2024-2025)	-	0.01(as Ag)	-	-

◆ Biological limit values

Component	Standard	Biological monitoring index	Biological limits value	Sampling time	Remark
Methanol	USA -ACGIH	Methanol(Urine)	15mg/L	End of shift	
Toluene	USA -ACGIH	o-Cresol, with hydrolysis(Creatinine in urine)	0.3mg/g	End of shift	
		Toluene(Urine)	0.03mg/L	End of shift	
		Toluene(Blood)	0.02mg/L	Prior to last shift of work week	

◆ Monitoring methods

1	EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
2	GBZ/T 300 and GBZ/T 160 series standard Determination of toxic substances in workplace air.

◆ Derived No effect level (DNEL)

Component	Route of exposure	DNEL for Workers			
		Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Methanol	Inhalation	No data available	No data available	130 mg/m ³	130 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Toluene	Inhalation	No data available	No data available	192 mg/m ³	192 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Tetrabutylammonium hydroxide	Inhalation	No data available	No data available	No data available	4.93 mg/m ³
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available
Silver (II) oxide	Inhalation	No data available	No data available	No data available	No data available
	Oral	No data available	No data available	No data available	No data available
	Dermal	No data available	No data available	No data available	No data available

◆ Predicted No Effect Concentration (PNEC)

Component	A	B	C	D	E	F	G	H
Methanol	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No hazard identified	No potential for bioaccumulation
Toluene	74 - 680 µg/L	7.4 - 680 µg/L	840 - 13610 µg/L	1.78 - 16.39 mg/kg sediment dw	178 - 16390 µg/kg sediment dw	No hazard identified	313 - 2890 µg/kg soil dw	No potential for bioaccumulation
Tetrabutylammonium hydroxide	16.5 µg/L	1.65 µg/L	28.4 mg/L	2.16 mg/kg sediment dw	216 µg/kg sediment dw	No hazard identified	421 µg/kg soil dw	No potential for bioaccumulation

Note 1:

A: Freshwater; B: Seawater; C: Sewage treatment plant; D: Sediment (freshwater); E: Sediment (seawater); F: Air; G: Soil; H: Secondary poisoning(Hazard for Predators).

Note 2:

The PNEC values of the remaining components not shown in the product are not available yet.

8.2 Exposure controls

8.2.1 Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

8.2.2 Personal protection equipment

General requirement	
Eye protection	Must wear appropriate anti-corrosion goggles.
Hand protection	Must wear acid and alkali resistant chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

8.2.3 Environmental exposure controls

Environmental exposure controls	No information available
---------------------------------	--------------------------

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	clear or clear yellow liquid
Colour	clear or clear yellow liquid
Odor	No information available
Odor threshold	No information available
pH	No information available
Melting point/freezing point(°C)	-95 (Toluene)
Initial boiling point and boiling range(°C)	111 (Toluene)
Flash point(Closed cup, °C)	4 (Toluene)
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit : 7.1 (Toluene); Lower limit : 1.1 (Toluene)
Vapor pressure	3.8kPa (25°C, Toluene)

Vapor density(Air = 1)	3.1 (Toluene)
Relative density(Water=1)	0.87 (Toluene)
Solubility	Insoluble in water (Toluene)
n-octanol/water partition coefficient	2.69 (Toluene)
Auto-ignition temperature(°C)	480 (Toluene)
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Particle characteristics	Not applicable

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Information with regard to physical hazard classes	No information available
--	--------------------------

9.2.2 Other safety characteristics

Other safety characteristics	No information available
------------------------------	--------------------------

10 Stability and reactivity

Stability and reactivity

10.1 Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
10.2 Chemical stability	Stable under proper operation and storage conditions.
10.3 Possibility of hazardous reactions	In contact with oxidants causes severe reactions, and may cause a fire or explosion. In contact with halides may cause an active reaction.
10.4 Conditions to avoid	Incompatible materials, heat, flame and spark.
10.5 Incompatible materials	Oxidants, alkali metals, alkaline earth metals and aluminum. Halides, oxidants and halogen.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 with amendment 2023/707

Tetrabutylammonium hydroxide titration solution	
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1B)
Serious eye damage/irritation	Causes serious eye damage(Category 1)
Skin sensitization	May cause an allergic skin reaction(Category 1)
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Suspected of damaging the unborn child(Category 2)
STOT-single exposure	May cause drowsiness or dizziness(Category 3); Causes damage to organs(Category 1)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure(Category 2)

Aspiration hazard	May be fatal if swallowed and enters airways(Category 1)
Germ cell mutagenicity	Based on available data, the classification criteria are not met

| Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Methanol	5628mg/kg(Rat)	15800mg/kg(Rabbit)	83.867mg/L(Rat)
Toluene	636mg/kg(Rat)	12200mg/kg(Rabbit)	49mg/L(Rat)

| Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP
Methanol	Not Listed	Not Listed
Toluene	Category 3	Not Listed
Tetrabutylammonium hydroxide	Not Listed	Not Listed
Silver (II) oxide	Not Listed	Not Listed

| 11.2 Information on other hazards

| 11.2.1 Endocrine disrupting properties

Component	Endocrine disrupting properties
Methanol	No information available
Toluene	No information available
Tetrabutylammonium hydroxide	No information available
Silver (II) oxide	No information available

| 11.2.2 Other Information

Other Information	See Section 11.1
--------------------------	------------------

12 Ecological information

| 12.1 Toxicity

| Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Methanol	LC ₅₀ : 24000mg/L (96h)(Fish)	EC ₅₀ : 24500mg/L (48h)(Crustaceans)	No information available
Tetrabutylammonium hydroxide	LC ₅₀ : > 100mg/L (96h)(Fish)	EC ₅₀ : 16.5mg/L (48h)(Crustaceans)	ErC ₅₀ : > 200mg/L (72h)(Algae)
Toluene	LC ₅₀ : 25mg/L (96h)(Fish)	EC ₅₀ : 4.1mg/L (48h)(Crustaceans)	ErC ₅₀ : 29mg/L (72h)(Algae)

| Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
-----------	------	-------------	------------------------

			plants
Toluene	No information available	NOEC : 1.2mg/L(Crustaceans)	NOEC : 9.1mg/L(Algae)

12.2 Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Methanol	Low	Low

12.3 Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Methanol	Low	BCF=10

12.4 Mobility in soil

Component	log Koc	Remark
Methanol	0.000	
Toluene	2.31	20 °C
Tetrabutylammonium hydroxide	3.104	25 °C , pH=8.0

12.5 Results of PBT and vPvB assessment

Component	Results of PBT and vPvB assessment [according to (EC) No 1907/2006]
Methanol	Not PBT/vPvB
Toluene	Not PBT/vPvB
Tetrabutylammonium hydroxide	Not PBT/vPvB
Silver (II) oxide	Insufficient information, temporarily unable to evaluate

12.6 Endocrine disrupting properties

Component	Endocrine disrupting properties
Methanol	No information available
Toluene	No information available
Tetrabutylammonium hydroxide	No information available
Silver (II) oxide	No information available

12.7 Other adverse effects

	No information available
--	--------------------------

13 Disposal considerations

13.1 Waste treatment methods

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
-----------------	--

Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label	
---------------------------	---

IMDG-CODE

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

IATA-DGR

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

UN-ADR

14.1 UN number	1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3
14.4 Packing group	II
14.5 Environmental hazards (Yes or no)	No

Special precautions for user

	<p>Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature.</p> <p>Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.</p>
--	--

Maritime transport in bulk according to IMO instruments

- ◆ Transport in bulk according to Annex II of MARPOL and the IBC code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with the IGC Code

	Not Available
--	---------------

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International chemical inventory

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
Methanol	√	√	√	√	√	√	√	√	√	√	√	√	√
Toluene	√	√	√	√	√	√	√	√	√	√	√	√	√
Tetrabutylammonium hydroxide	√	√	√	√	√	√	√	√	×	×	√	√	√
Silver (II) oxide	×	√	√	×	×	×	√	√	√	×	×	√	√

- [A] China Inventory of Existing Chemical Substances(IECSC)
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
 [C] United States Toxic Substances Control Act Inventory(TSCA)
 [D] Canadian Domestic Substances List(DSL)
 [E] New Zealand Inventory of Chemicals(NZIoC)
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
 [G] Korea Existing Chemicals Inventory(KECL)
 [H] Australian. Inventory of Industrial Chemical (AIICS)
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)
 [J] Thailand Existing Chemicals Inventory(TECI)
 [K] Mexico National Inventory of Chemical Substances (INSQ)
 [L] Russia Inventory of Existing Substances(DRAFT)
 [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	B	C
Methanol	×	×	×
Toluene	×	×	×
Tetrabutylammonium hydroxide	×	×	×
Silver (II) oxide	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
 [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
 [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

European chemical inventory

Component	A	B	C	D	E	F	G	H	I
Methanol	×	×	√	√	√	√	×	×	×
Toluene	×	×	√	√	√	√	×	×	×
Tetrabutylammonium hydroxide	×	×	×	√	√	×	×	×	×
Silver (II) oxide	×	×	×	√	×	×	×	×	×

[A] Candidate list of Substances of Very High Concern for authorization under EU REACH regulation

[B] Substances requiring authorisation under EU REACH regulation

[C] Substances restricted under EU REACH

[D] Pre-registered substances under EU REACH

[E] Registered substances under EU REACH

[F] Substance Evaluation – CoRAP under EU REACH

[G] List of priority substances under EU water policy (Directive 2455/2001/EC)

[H] Substances subject to POPs Regulation

[I] Substances proposed as POPs

Note:

“√” Indicates that the substance included in the regulations.

“×” No data or not included in the regulations.

German water hazard class(WGK)

Component	WGK	Remark
Methanol	WGK 2	
Toluene	WGK 3	
Tetrabutylammonium hydroxide	WGK 1	

[WGK 1] slightly hazardous to water

[WGK 2] obviously hazardous to water

[WGK 3] highly hazardous to water

[nwg] non-hazardous to water

[awg] hazardous to water in general

German technical instructions on air quality control(TA LUFT)

Component	TA LUFT	Remark
Methanol	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
Toluene	Chapter 5.2.5 Organic Substances, class I. The following values are in all not allowed to be exceeded in the exhaust gas: Mass flow: 0,10 kg/hr or Mass conc.: 20 mg/m ³	
Tetrabutylammonium hydroxide	Chapter 5.2.5 Organic Substances. The following values, specified as overall carbon, are in all not allowed to be exceeded in exhaust gas: Mass flow: 0,50 kg/hr or Mass conc.: 50 mg/m ³ At old units with an annual mass flow till 1,5 Mg/a, specified as total carbon, the emissions in exhaust gas are not allowed to exceed 1,5 kg/h.	

German technical rules for hazardous substances(TRGS)

Component	TRGS	Remark
Methanol	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Toluene	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 402 TRGS 401 TRGS 500 TRGS 509 TRGS 510 TRGS 800 TRGS 720 TRGS 721 TRGS 722 TRGS 723 TRGS 724	
Tetrabutylammonium hydroxide	TRGS 201 TRGS 400 TRGS 555 TRGS 600 TRGS 401 TRGS 500 TRGS 509 TRGS 510	

15.2 Chemical safety assessment

	No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.
--	--

16 Other information

Information on revision

Creation Date	2026/01/10
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
- [2] IARC, website: <http://www.iarc.fr/>.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.
- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
- [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
- [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
- [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
- [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC _x	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P _{OW}	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor		

Disclaimer

This Safety Data Sheet (SDS) was prepared according to REACH Regulation. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.